Defining context-specific scenarios to design vegetated buffer zones that limit pesticide transfer via surface runoff

Nadia Carluer, Claire Lauvernet, Dominikus Noll, R. Muñoz Carpena

► To cite this version:

Nadia Carluer, Claire Lauvernet, Dominikus Noll, R. Muñoz Carpena. Defining context-specific scenarios to design vegetated buffer zones that limit pesticide transfer via surface runoff. *Science of the Total Environment*, 2017, 575, pp.701-712. 10.1016/j.scitotenv.2016.09.105 . hal-02605064

HAL Id: hal-02605064

<https://hal.inrae.fr/hal-02605064>

Submitted on 16 May 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Defining context-specific scenarios to design vegetated buffer zones that limit pesticide transfer via surface runoff.

N. Carlier¹, C. Lauvernet¹, D. Noll¹, R. Munoz-Carpena²

[1]{Irrstea, UR MALY, centre de Lyon-Villeurbanne, 5 rue de la Doua-CS 70077, F-69626 Villeurbanne cedex, France}

[2]{University of Florida, Agricultural and Biological Engineering, 287 Frazier Rogers Hall, PO Box 110570 Gainesville, FL 32611-0570, USA}

Correspondence to N. Carlier: nadia.carlier@irstea.fr

Keywords: vegetative filter strip; buffer zone modelling; process-based model; VFS sizing; shallow water table; watershed

Introduction

Diffuse pollution (nitrates, phosphates, suspended matter, pesticides, and metals) has a significant effect on water resources. These contaminants are likely to harm the ecological quality of waterways and to compromise capacities to meet the "good ecological status" ambitious target set in 2015 by the WFD (Water Framework Directive). They may also compromise the drinking water supplies of populations and necessitate the use of expensive treatments to reach drinking water standards. For plant protection products, it is necessary to act at several levels to minimize non-point pollution: limiting their use and preventing and limiting their transfer from agricultural fields to water resources. Regarding this solution, vegetative buffer zones (grass strips, wood, riparian forests, etc.) are considered to be the most efficient buffers for pollutants transported mainly through surface runoff and sediment, by enhancing the retention and degradation of active substances (eg Poletika et al., 2009; Reichenberger et al., 2007). However, several factors related to topographical features and agricultural practices can affect vegetative filter zones (i.e., vegetative filter strips (VFSs)), determining their performance and limiting their effectiveness: to be efficient, they must be correctly designed in consideration of their positioning (Tomer et al., 2008), type, and size (Daniels and Gilliam 1996; Dosskey et al. 2002, 2011). Furthermore, fixed VFS widths do not prevent water, sediment and pesticide transfer, as surface runoff is never spatially uniform on a field given heterogeneities of topographical and soil characteristics (Beven et al, 1998). For VFS sizing, a field diagnosis must be performed, ideally at the watershed scale, to identify the main potential sources and pathways of contamination. It should be based on soil characteristics, crops, cultural practices, topographical features and observed runoff pathways. It is then possible to determine which mitigation solutions to adopt and to select appropriate VFS sizes and positions when this choice is relevant (Bernard et al, 2014. *in French*). The first solution for VFS sizing involves using field expert knowledge or recommendations from national or local institutions, functioning in a given context (e.g., CORPEN/Cemagref in France and the USDA in the US). Yet conditions that influence pollutant retention through a buffer (e.g., soil, slope, and hydrology) can differ substantially from one location to another (Lowrance et al., 1997, Dosskey

2006), and pollutants do not behave similarly in buffer soils, as a function of their physico-chemical properties. This is why simple laws cannot represent the diversity of soil, agronomic, climatic and chemical scenarios. More deterministic methods can then be used (e.g., abacus or “decision rules” developed for some specific watersheds) via physical modelling depending on soil survey attributes (mainly slope, soil and rainfall factors) (e.g., Dosskey et al., 2006). A physical approach to sizing vegetated buffers involves directly applying a physical model that is specifically parameterized to a given local context. The Vegetative Filter Strip MODEL VFSMOD (Munoz-Carpena et al, 1999) is a vegetative filter strip physically based model that can be applied directly as a VFS sizing tool either for one given VFS location (Dosskey et al., 2006, 2008, 2011) or at a larger scale by coupling it to a watershed model (White and Arnold, 2009) or to GIS tools (e.g., Park et al. 2013). This tool, however, must be properly parameterized to determine local characteristics of flow entering a filter as well as rainfall typical events, initial conditions, soil characteristics, and buffer properties. The method proposed by Dosskey et al (2008, 2011), which involves using soil surveys to determine widths of filter strips based on laws of VFSMOD simulations, is currently the most appropriate approach available, as it is physically based but also simple enough to be used in an operational context. However, the method can be applied and tested for sediment reduction only and not to examine pesticides, and the authors note several limitations to their method: the Green-Ampt solution used in the VFSMOD does not allow one to examine conditions wherein a VFS is bounded by a shallow (perched) water table. This boundary condition can severely limit VFS infiltration capacities by causing runoff by saturation. This is an important restriction, as VFSs can be located in an area where a shallow impermeable soil layer can form perched water tables and also because VFSs are often located along river networks, increasing the probability of shallow river connection formation (Reichenberger et al., 2007; Lacas et al., 2012) The latest version of VFSMOD (Munoz-Carpena et al., submitted) simulates infiltration under shallow water table conditions. Other limitations of the (Dosskey et al 2008, 2011) method concern infiltrated pollutants, for which behaviour in soil is not represented by VFSMOD. However, a model representing pollutant transport through soil would need to represent lateral transfer and chemical reactions, adding a large set of input parameters. It would thus likely lose operational properties that allow non-modellers to use this method. In this study, we propose a new method that improves modelling scenarios and their applicability in the field through physical basis. Scenarios take into account initial states of humidity and water table effects on VFS infiltration. The proposed method is then based on (i) the quantification of water flows produced by the contributing area and (ii) on VFS capacities to infiltrate incoming flows. We first briefly review the main physical processes that occur in a VFS to properly apply the method. The method then is presented and applied to a test catchment in north-western France. Our construction of nomograms from a large sample of simulated scenarios is then described as a method to be used by non-modellers.

I. Physical processes of a vegetative buffer zone

The contributive area of a buffer zone is defined as the part of a watershed where flows entering the buffer zone are generated. Incoming surface runoff on a buffer zone is very sensitive to contributive area extension and characteristics. Consequently, it is important that the sizing step occurs after diagnosis at the watershed

level to ensure that the nature of the buffer zone and its positioning are relevant in consideration of environmental conditions. Ideally, buffer zone implementation should occur at the catchment scale for optimal sizing.

I.1 Water flow components within a buffer zone

Water flows into and on the ground through the following three main pathways: infiltration and deep percolation, shallow subsurface lateral flow, and surface runoff. This article focuses on dry buffer zones, which are mainly of relevance to the latter mode of circulation. We distinguish here between “dry” buffer zones where soil surfaces are not supposed to be durably ponded (grass strips, wood, riparian forests, etc.) and “wet” buffer zones where major dissipating processes are linked to wet conditions (artificial wetlands). Surface runoff can be generated when rainfall rates exceed soil surface hydraulic conductivity so that excess water does not infiltrate, and generate surface flow (Hortonian runoff) or when an entire soil profile becomes saturated with water (before or during an event) so that all incoming water contributes to surface runoff (runoff on a saturated surface). These two main forms of runoff, and Hortonian runoff in particular, can be erosive and can transport fine particles detached from the ground through raindrops or flow. Nevertheless, erosion is not systematic when runoff occurs, and especially when simplified cultural practices are used and when soil is rich in clay or organic matter.

I.2 Key drivers of vegetative buffer strip efficiency

Three features allow buffers to reduce runoff and retain pesticides (see Figure 1). VFS soil permeability is higher than that of cultivated plot permeability due to the significant root density of grass cover of the former (the existence of a root mat, i.e., a dense layer rich in fine living and dead roots, linked to the presence of permanent vegetation in the upper ten centimetre layer of soil). This high infiltration capacity usually reduces incoming water flows significantly. A second property is high roughness due to the density of the aerial component of vegetation. This slows runoff on one hand while settling eroded particles and molecules adsorbed on their surface on the other. Finally, high organic carbon content levels increase the adsorption capacity of the buffer zone relative to that of a cultivated soil. Regarding degradation, it seems that although it is rich in organic matter and promotes microbial activity, buffer zone soil does not generally contain a significant number of microorganisms adapted to degrade specific pesticides entering an area. As a consequence, microbial activity remains nonspecific (Madriral-Monarrez, 2004, *In French*); the microbial community can however be adapted to degrade specific pesticides in cases of repeated exposure (Devers-Lamrani et al., 2014).

Dry buffer mitigation efficiency levels are dependent on their width (dimension in the direction of flow) and on the following ratio in particular: contributing area / buffer zone area (Arora et al., 1996). The effective length (perpendicular to the flow direction) also influences buffer efficiency, and especially in cases of concentrated flow. Indeed, both field and modelling studies have confirmed that constant-width filter strips are less effective at trapping sediment, nitrogen, phosphorus and pesticides when concentrated flow occurs than when flow is uniform (Dosskey et al., 2011; Fox et al., 2010). The VFS infiltration capacity can in this case be exceeded, as only part of the surface contributes to infiltration. As a consequence, the width needed to infiltrate incoming

runoff may be much higher. The calculated design method is then relevant only when concentration phenomena are prevented or mitigated (e.g., using additional upslope elements as fagots, hedges or embankments).

II. Design method

II.1 Framework

The infiltration of water and pesticides is often the main process shaping pesticide transport reduction (Lacas, Voltz et al. 2005, Reichenberger, Bach et al. 2007). On top of this, pesticide behaviour in and on soils varies depending on active substance physico-chemical characteristics, and in particular: Koc, reflecting their capacities to be sorbed on soil aggregates and DT50, reflecting their capacities to be quickly degraded. Yet, VFSs are semi-permanent devices and their sizes may not change from one year to another. They should thus be efficient for a broad range of pesticides owing to their physico-chemical characteristics.

As a consequence, the method presented in this paper only considers surface runoff reduction. We propose that pesticide exportation attenuation should be at least equal to surface water flow reduction. This hypothesis is based on the finding that VFSSMOD (the model used to simulate VFS behaviour -see below-), simulations always leads to sediment retention higher than surface runoff attenuation. As a consequence, for a given surface runoff attenuation level, attenuation will be the same for pesticides in solution or for pesticides sorbed on fine sediments, which will infiltrate along with water, and will at least be the same for pesticides sorbed on sediments settled on the upslope boundary of a VFS. This overall level of efficiency is increased by pesticide fraction that is sorbed on the VFS soil surface. As a consequence, this hypothesis will at worse lead to an underestimation of buffer zone effectiveness, as it does not take into account the deposition of sediments along the upstream boundary of a buffer zone or the adsorption of active substances on the surface of a buffer zone. However, mainly coarse sediments settle upstream from buffer zones while pesticides are mainly adsorbed on fine sediment. Though under very erosive conditions, the previous assumption may be exaggerated.

The simulation method for deriving buffer sizes involves two steps (see the flowchart in Figure 2). First, surface runoff traveling from a contributive area to a buffer zone is assessed for a variety of representative rainfall events considering climatic characteristics of the geographic region examined and the contributive area's topographical and crop features. Second, buffer zone efficiency is evaluated in consideration of implementation area features of each surface runoff scenario and for a range of sizes using a numerical model that simulates water flows in a vegetative buffer zone (VFSSMOD). Finally, an optimal size is derived for the chosen desired efficiency rate.

II.2 Assessment of surface runoff generated on contributive areas

The objective of this first step is to cover a range of realistic conditions on surface runoff entering a VFS. This involves considering several scenarios (in terms of soil, agriculture, and climate) to explore variety of events that can occur in a given area. Each scenario is defined by a season, crop (which influences soil surface

characteristics and pesticide application periods), and typical rainfall event. A corresponding surface runoff hydrograph is then derived via the Curve Number method (USDA-SCS 1972). A return period of one year (precipitation event occurring once per season on average) is considered to define rainfall events so that the VFS is designed for frequent runoff events.

II.2.1 Rainfall event characterization

Through a long term rainfall data analysis, Intensity-Duration-Frequency rainfall data were derived for 4*4 km square zones covering the French territory (Aubert et al., 2014). Although this method is usually used to assess the probability for extreme events, we focused on frequent events (return period of one year). VFSs are here designed to mitigate pesticide transfer instead of flooding. From this point of view, extreme events are linked to the occurrence of surface runoff events shortly after pesticide application and not necessarily to the occurrence of severe runoff events. Two seasons are considered in the rainfall analysis: winter (November to April) and summer (May to October). Rainfall regimes can differ significantly in the winter and summer. As a result, rainfall volumes occurring once a year on average for 1 h to 48 h are available for France based on a 4-km grid for the winter and summer. Such a method, which prevents the designer from being subjective when choosing a “representative rainfall event” for an area, could be applied to study other countries provided data are available. For each location in France, season and rainfall duration, a hyetograph can be generated for an intensive or moderate event (see for example Figure 3 on the Fontaine du Theil catchment in northern France, which is described in following section).

II.2.2 Incoming runoff event assessment

One of the most influential characteristics of a contributive area is its capacity to generate surface runoff: highly permeable soils facilitate water infiltration while less permeable and capping soils turn large proportions of incoming rainfall into surface runoff. Much runoff is also produced when the soil top layer is permeable but situated above a shallow groundwater table (e.g., less than 1 m below the soil surface) or when an impermeable soil layer exists at a shallow depth (e.g., a plough layer) and inhibits water infiltration into deeper subsoil.

For a rainfall event, the resulting surface runoff hydrogram is determined via the Curve number method (USDA-SCS 1972). The Curve Number is dependent on the soil hydrological class and crop considered, on hydrological conditions and on the soil humidity status (i.e., soil humidity at the beginning of the rainfall event). As it significantly influences generated surface runoff and is very sensitive, it must be selected carefully and, when possible, validated with observed data. The USDA-SRC (1972) considers 4 classes of soil with typical characteristics summarized in Table 7, Appendix 1 (class A highly permeable to class D hardly permeable). Impermeable layers or a higher water table can influence soil water infiltration capacities and can change a soil hydrological group, based on its texture only. Hydrological conditions are dependent on soil occupation features: the more a crop covers the soil, the more these conditions are considered to be favourable. Thus, this parameter evolves over time.

Nominal values are associated with average initial humidity conditions (CN_{II}), but it is possible to calculate a Curve Number CN_I for dry humidity conditions and a Curve Number CN_{III} representative of wet initial humidity conditions using Chow et al. (1988) method as follows:

$$\text{Equation 1: } CN_I = 4.2 * \frac{CN_{II}}{10 - 0.058 * CN_{II}} \text{ and } CN_{III} = 23 * \frac{CN_{II}}{10 + 0.13 * CN_{II}}$$

Finally, the incoming hydrogram is defined based on the contributive area average slope, surface, and longest hydraulic path using a GIS tool. However, one must determine whether the examined area can be ascribed to a plane surface or not so that water enters the VFS in a more or less concentrated way. This should be accounted for in the second step (buffer zone efficiency modelling) by increasing the incoming hydrograph of corresponding proportions of the VFS non-efficient/total length.

Thus, **for a given VFS position, modelling scenario definition involves selecting a season, rainfall length and intensity, soil occupation (and crop state of development) and antecedent humidity status**; the latter two factors allow one to define the corresponding Curve Number based on the contributive area soil. This choice should be based on main periods of pesticide application to take into account main risk contamination periods.

II.3 Buffer zone efficiency modelling approach

A numerical overland flow and transport model is used to simulate the vegetative buffer zone efficiency of the defined scenario. The VFSSMOD model (Munoz-Carpena et al., 2010) is a physically based model that calculates infiltration volume and sediment trapping levels in a buffer over a defined event (rainfall hyetograph, runoff hydrograph and sediment characteristics entering the filter). Using the optimization mode allows one to determine which width is optimal with respect to the required efficiency level. Concentrated flows in a filter can be taken into account by reducing the effective flow dimension of the strip perpendicular to the flow (called FWIDTH in VFSSMOD) or by reducing dimensions of the field or source area edge (Muñoz-Carpena and Parsons, 2004, Fox et al., 2010, Dosskey et al. 2011). Water tables can drastically lower the buffer zone capacity to infiltrate water, and particularly for fine soils (Simpkins et al., 2002; Arora et al., 2010; Lacas et al., 2005, Lauvernet and Muñoz-Carpena, submitted). The vertical infiltration level is then determined using the SWINGO algorithm coupled to other processes, as it takes into account the effect of a shallow water table underlying a buffer zone (Muñoz-Carpena et al., submitted). Sediment trapping efficiency is based on sediment transport equations (Muñoz-Carpena et al., 1999) by simulating the filtration of suspended solids through artificial grass media. An extension that allows one to assess pesticide dissipation in the VFS was recently added to VFSSMOD (Sabbagh et al., 2009). Yet, this extension is based on statistical regressions derived from observations on a range of efficient VFS values: it does not explicitly represent processes involved in pesticide behaviour.

Three classes of characteristics or parameters must be defined to use VFSSMOD and to characterize the VFS infiltration capacity: (i) its topography and dimensions, (ii) soil hydrodynamic characteristics at the surface and in the soil, and (iii) initial humidity status and the presence or absence of a water table. The effective length (perpendicular to the flow) of the buffer zone must be determined to simulate its efficiency using VFSSMOD. In the field, it is better to maximally prevent runoff concentration, preferably through the implantation of dispersive facilities. The length can be parameterized in several ways: field measurements or through the use

of a GIS tool that considers runoff concentrations. Similarly, slopes can be determined through field measurements or by using a GIS. Saturated hydraulic conductivity is a key parameter of the model and is often the most influential, together with water table depth depending on the hydraulic loading (Muñoz-Carpena et al., 2010; Lauvernet and Muñoz-Carpena, submitted). It is therefore important to assign a value as representative as possible of the real conductivity value. It is thus possible to consider two distinct horizons: the root mat and the rest of the vertical profile. These are then combined through a harmonic mean as recommended by Bouwer (1969). As is done for the contributory surface, the presence or absence of a shallow water table is determined through field observations or through the use of database (e.g., the DONESOL database for France and the USGS database for the US). Other parameters affect buffer efficiency less and can be set as default values (including sediment characteristics), as the main assumptions of this method consider runoff reduction only. However, for a user with access to the necessary data, VFSMOD allows one to study other processes such as the transport of sediment and pesticides.

The output of the model in optimization mode gives the outflow surface runoff percentage of the buffer area according to the width for each scenario, on a width range set by the user. The desired level of efficiency allows one to graphically visualize the necessary width for each typical rainfall event. Figure 4 presents 70% efficiency sizing results for a rainfall event set at 21 mm for 6 hours (“Summer, Moderate, 6 h” of Figure 3).

Thus, this toolkit allows one to define scenarios that correspond closely to the considered buffer zone project in regards to rainfall events, contributive areas, and buffer zone areas, and to their characteristics evolution year round. This allows one to carefully optimize buffer zones and to achieve desired efficiency levels without consuming more agricultural surface area than is necessary.

III. Application on a test catchment

III.1 Design method implementation

The application site is the Fontaine du Theil catchment (128 ha) near Rennes in western France. The climate is temperate oceanic with a nearly 12°C mean annual air temperature, an approximately 800 mm mean annual precipitation level since the early 1990’s and a 750 mm mean annual potential evapotranspiration level. Crop rotations involve maize, wheat and meadows in equal proportions of the total catchment area. Slopes are moderate with an average of 3.9% and a standard deviation of 2.7%. Soils have developed on rather impermeable schist and can be classified into three main types: G1 for hill-slope brown soil, G2 for hill-slope leached brown soil and G3 for low-lying hydromorphic brown soil. **Erreur ! Source du renvoi introuvable.** presents a soil map of the area. Soils here are quite shallow, and thus a water table usually lies on the schist layer. Its roof can be near the soil surface, in particular along the valley bottom in the winter. As a consequence, surface runoff occurs quite frequently, and especially in low-lying areas. In addition, depending on crop and tillage practices used, soils can be subject to slaking, leading to surface runoff. Shallow lateral flows on the hill-slopes supply river flows, which can stop during drier summers.

A field diagnosis of soil distributions, soil occupation patterns, potential buffer zones (vegetated buffer zones, hedges and embankments), water short circuits (ditches, tile drainage, and roads) and consequent water

pathways involving agronomists, hydrologists and farmers was performed for the watershed. We in turn identified zones where surface runoff is most likely to occur and pesticide fluxes to be generated. From this analysis, a range of vegetative buffer strip potential positions was identified as illustrated in Figure 5. To design the resulting VFS, contributive areas characteristics were assessed and namely topographic characteristics and curve numbers. The former were calculated using a GIS and the corresponding results are presented in **Erreur ! Source du renvoi introuvable.** Scenarios must be chosen carefully, as they determine the resulting VFS size. Such scenarios must represent a variety of realistic situations for the considered catchment. Each scenario is defined by one rainfall event (duration and intensity), one crop and an initial humidity state for the contributive area. Based on expert knowledge, twelve different scenarios were considered for the Fontaine du Theil catchment: (i) For the winter period, two crops were taken into account: winter wheat and intermediate nitrate trapping crops (assimilated to meadows). Wheat was considered poorly developed (10% of soil cover) whereas trapping crops were considered well developed. A 24-hour-long moderately intensive rainfall period was considered in addition to a 3-hour-long intensive one (**Erreur ! Source du renvoi introuvable.**). For the former, soils were considered to be moderately wet at the beginning of the event, when they were considered to be wet for the second case. According to piezometer data available on the catchment, the water table was supposed to be 5 meters deep for G1 and G2 soils and 1 meter deep for G3 soils. (ii) For the summer period, both winter wheat and corn crops were considered, and two rainfall events were taken into account: a 2-hour-long intensive event and a 6-hour-long moderately intensive event. For each crop and rainfall event, intermediate and initially high soil humidity conditions were modelled. Here, wheat was considered well developed (90% soil covering) when maize was deemed recently seeded (25%). The water table depth was set to 5 m for G1 and G2 soils and to 2.5 m for G3 soils.

The surface layer conductivity level estimated using SWC (Soil Water Characteristics software, Saxton and Rawls, 2006) was considered to assess the curve number value for each case. Original Curve Number tables were initially proposed for North American conditions based on data for a range of small American rural catchments. Yet, an analysis of three experimental sites in France (northern France with permeable and silty but highly capping soils, western France with less permeable and moderately loamy clay soils and southeastern France with very permeable clayed sand) for which data were available showed that CN values derived from USDA tables were systematically too low to make runoff predictions. Increasing these original CN values by 7-8 points made it possible to satisfactorily represent the observed runoff of the three sites. As a result, for this application, CN values derived from USDA tables were also increased by 8 points. **Erreur ! Source du renvoi introuvable.** summarizes these values.

For vegetative filter strip soil Van Genuchten parameters, each second soil layer was taken into account because for this catchment on low permeable schists, this layer's infiltration effects heavily influence surface runoff generation. Yet, in regards to saturated hydraulic conductivity, a harmonic mean of 15 cm for the first layer and of 35 cm for the second layer was used. These parameters were also derived using SWC software and are summarized in **Erreur ! Source du renvoi introuvable.**

III.2 Results and discussion

Taking into account the hydrodynamics of flows in this catchment, a typical catchment of western France (Gascuel Odoux et al., 2010; Rouxel et al., 2011), our risk contamination diagnosis led us to set vegetated buffer zones at the hill-slope base in addition to pre-existing buffer zones (banks, hedges and vegetated buffer zones) as is illustrated in Figure 5. The figure shows optimal VFS sizes determined via this method. In addition to intercepting all surface runoff generated on hill-slopes, such a position is consistent with optimal agri-environmental conditions prescribed in France. Moreover, it minimizes drawbacks of VFS implantation for farmers. Yet, as the experts who performed the diagnosis were aware of hydromorphic characteristics of low-altitude areas and as surface runoff fluxes are maximal at the hill-slope bases of such catchments, they proposed an alternative or supplementary implantation of some buffer zones that are situated on G3 soil and/or are bound to experience large surface runoff fluxes. When a grass strip is located on low-lying land on hydromorphic soil with an underlying shallow water table (e.g., n56, n62, or n26), its effectiveness is limited, resulting in widths exceeding 25 meters. Conversely, n25 located just above n26 intercepts an area similar to that collected by n26, although it is slightly lower (146 m² of the contributive area per meter of VFS for n25 versus 156 m² of the contributive area per meter of VFS for n26). However, as it is located on healthy soil with a deep water table that does not interfere with its infiltration, its width may be more moderate. Findings are similar for n17, which is situated on permeable soil (G1) but which accumulates a large area (204 m² per meter of VFS). If this buffer zone is supposed to exist alone on the hill-slope, the most demanding scenario involves a 14.25 m width VFS when 9.25 is sufficient when a VFS (n28) is implanted higher on the hill-slope. The total area (right-of-way) generated from two VFSs is similar to that based on one, but the first solution eliminates more sediment and is thus preferred.

Effects of the different scenarios show that winter scenarios lead to narrow VFSs provided that infiltration is possible (i.e., when the water table is not too shallow). This is related to the pluviometric context of this area, where winter rainfall events are frequent and long but moderate in intensity, causing soil hydraulic conductivity to almost never be exceeded (see Figure 3). By contrast, summer scenarios with high initial moisture conditions (III) lead to high widths and especially when contributive areas are supposed to be seeded with corn, corresponding to low soil cover at the beginning of the summer and thus a high curve number. This shows that results are shaped heavily by chosen scenarios, which should emanate from discussions with stakeholders. In the same way, design selection should involve a compromise between the targeted efficiency and acceptable dimensions, and possibly by relativizing the significance of some very adverse scenarios.

When applied to the Fontaine du Theil Catchment, the proposed design method allows one to design each buffer zone individually. Yet, processing the entire method for each buffer zone proved quite tedious. As a result, we decided to develop an alternative approach based on a broad range of pre-calculated scenarios and resulting in ready-to-use nomograms. This approach is briefly presented in the following section.

IV. Towards a more user-friendly approach

The proposed approach is based on the definition and pre-calculation of a large number of scenarios covering a wide range of conditions and making it possible to build nomograms where the user can select the result that best reflects his own situation. Two climates were considered. The first, a northern oceanic temperate climate (N in the nomograms), is based on Amiens data (Northern France: X = 597 212 m; Y = 2 543 947 m in Lambert II). The mean annual precipitation level here is 771 mm. The second is a southern Mediterranean climate (S in the nomograms) based on Roujan data (Southern France: X = 678 888 m; Y = 1 834 131 m). The mean annual rainfall level here is 654 mm. Monthly rainfall levels are presented in Figure 6.

For each representative climatic region, three realistic worst-case rainfall events were considered: one 12-hour-long winter rainfall event and two summer events (one 2 hours long and one 6 hours long) (Table 3).

Contributive areas were considered to be rectangular and planar, feeding a buffer zone of the same dimension. When this was not the case (trapezoidal forms in the contributive area or flows converging into a talweg), we took this into account by considering an equivalent contributive area length. Simulations considered slope lengths (assuming a rectangular field) of 50 m to 300 m at 50 m increments and contributive area slopes of 2, 5 and 10%.

Simulations were performed for the four classes of soils (A to D) distinguished by the USDA and assuming that: (i) winter crop is wheat and summer crop is corn ; (ii) initial humidity level is high in the winter (III) and either at field capacity (II) or high (III) in the summer. Curve values used for the simulations are summarized in **Erreur ! Source du renvoi introuvable.** Equation 1 was used to assess curve numbers for humidity conditions III).

Following Brown et al. (2012), four classes of soils were considered as vegetative buffer zones in the VFS scenario project: silt loam, sandy loam, clay loam and sandy clay loam. Soil parameters were assessed via the Rosetta pedotransfer function (Schaap et al, 2001) for n, alpha and Theta_r. Ksat and Theta_s values were drawn from Brown et al. (2012), as they take into account soil structure modifications induced by perennial vegetation. Two initial water table depths were simulated: 2.5 m and 1 m. To make realistic calculations, for a given VFS, simulated water table depths were combined for the summer and winter as follows: 2.5 m in the winter and 2.5 m in the summer, 1 m in the winter and 2.5 m in the summer, and 1 m in the winter and 1 m in the summer. Initial humidity conditions are set at hydrostatic equilibrium above the water table. The VFS slope must be the same as the contributive area's slope: 2, 5 and 10%. These combinations led to 4,284 scenarios. 11 VFS widths were simulated for each scenario (from 5 to 25 m) generating nearly 50,000 simulations. This allowed us to assess an **optimal VFS width for each set of scenarios with 70% efficiency**. This means at least 70 % of the incoming water (runoff + rain) was infiltrated within the vegetative buffer zone soil (or 30% may reach downslope areas) for the four rainfall and humidity status scenarios defined for a given VFS situation. As suspended matter can deposit upslope of a VFS and adsorption can occur on VFS soil, a VFS can be oversized for 70% efficiency. In any case, a VFS must also prove efficient for low sorbing pesticides, and 30% of incoming water may still exit a strip during a yearly maximum runoff event. The 70% efficiency level selected for this application may seem arbitrary. It is designed to be pragmatic in consideration of constraints on farmers. We made a compromise, as reducing risks of transfers to zero does not seem reasonable: such a choice would also require one to consider less frequent and more intense rainfall events with the corresponding return period

also being arbitrary. In addition, the most intensive runoff events do not necessarily coincide with the highest pesticide concentrations and fluxes. **Pesticide concentrations and fluxes in surface runoff are mainly dependent on time between application and rainfall, which determines available pesticide storage levels.** Pesticide concentrations in surface runoff are higher when surface water flows are low (models usually consider perfect mixing between surface water and a given depth of soil), but exported amounts are higher when water cumulated discharge is higher.

Figure 7 presents a nomogram including several informations. **The blue curve** represents the size of the optimal buffer zone for a given contributive area length for the winter rainfall event (15 mm falling over 12 hours with moderate maximal intensity) and an intermediate slope of 5%. The blue shadow area shows how the buffer size varies with different slopes (the higher the slope, the wider the buffer, with slopes varying from 2 to 10% in the performed simulations). For example, when the contributive area length is 125 m, the optimal buffer width is roughly 7.5 m. When the optimal size is greater than 25 m, the exact value is not calculated (denoted by a value of 25+), as this may mean that a vegetated filter strip may not be the best or only necessary mitigation solution. Typically, an artificial wetland area can be more efficient in such cases or may need to be used in addition to a reduced buffer width of less than 20 m. **The yellow curve** corresponds to the worst scenario with summer rainfall falling on soil at field capacity. Depending on the situation, this can involve 17 mm of rainfall falling for 6 hours with moderate maximal intensity or 12 mm of rainfall falling for 2 hours with high maximal intensity. For this example, the second case is the worst scenario. Looking at Figure 7 hill-slope, when the contributive area length reaches 125 m, a 5-meter-wide buffer is sufficient. **The grey curve** illustrates a case whereby a rainfall event occurs on wet soil in the summer with moderate rain of 17 mm falling over 6 hours. Successive rainfall events occurring in the summer can create wet soil. This simulation illustrates that buffers work in certain situations but do not guarantee zero risk when several adverse conditions are involved. The explored scenarios and generated abacus are still prospective and are designed to assess the feasibility of the proposed approach.

Conclusions and perspectives

The design methodology presented here allows one to consider a broad range of local characteristics (hydrodynamic characteristics of a contributive area and VFS soils, crops, rainfall events, and seasons) in optimally designing vegetated buffer strips based on local conditions. For a given buffer zone, different widths are obtained for individual agronomic and climatic scenarios. As a consequence, final selection will depend on the size of action plan objectives and ambitions: a width is selected to cover the whole set of scenarios provided that establishing such a buffer zone is reasonable from an operational point of view. Such an approach allows one to generate a VFS large enough to be efficient without consuming unnecessarily large agricultural surfaces. However, one must be aware that VFSs must be used along with sound agricultural practices and that regardless of their size, they cannot fully prevent pesticide entry into surface water, where even low quantities of pesticides may have significant ecotoxicological effects depending on their ecotoxicological properties. In some unfavourable cases (flow concentrations or waterlogged soils), the method will generate VFS widths that are too large from a farmer's perspective. These results will then serve as an

impartial basis to initiate dialog between different stakeholders on possible solutions. These can involve various outcomes, e.g., better runoff dissemination, buffer zone completion using other devices or buffer zones higher up on hill-slopes (reducing the contributive area of the studied buffer zone), or moving a buffer zone to a more favourable area (e.g., an area without waterlogging). Thus, the location and sizing of buffer zones on a watershed can be a recursive task. To guarantee the acceptability of results, it seems necessary that definitions of “typical” scenarios and of desired levels of efficiency are discussed with stakeholders. Given processes considered through the proposed method (namely surface runoff attenuation), the design method may apply to contaminants other than pesticides submitted through similar processes (e.g., veterinary medicines, pathogens, phosphorus or heavy metals). However, as nitrogen exportation occurs mainly through subsurface flows, the proposed method does not seem applicable to cases of nitrogen contamination.

To our knowledge, the proposed methodology is the first to explicitly consider shallow water tables, which are commonly found in VFS locations, and especially those along waterways. Yet, the method is still limited, at least in the form presented here, as it does not consider suspended matters or pesticide transfer and dissipation within a VFS. In fact, this should be partly possible, as VFSMOD can manage suspended matter deposition and pesticide transfer attenuation (using a statistic relation) as stated above. Yet, it must be stressed that data on hill-slope erosion or pesticide application are rare and that one must ensure data quality before addressing such questions. In addition, the main process involved in VFS efficiency is water infiltration within buffer soils. As a consequence, except when only strongly sorbed pesticides are used in a very erosive context, it seems more relevant to focus data acquisition efforts on soil data. Rather, results are heavily dependent on the contributive curve number, on the hydraulic conductivity of the buffer zone soil, and of course on the presence or absence of a shallow water table (Lauvernet and Muñoz-Carpena, submitted). Another limitation pertains to the fact that infiltrated water and pesticide fates are not considered: in certain contexts, it may be necessary to consider possible subsurface lateral flows towards a stream or percolation into a vulnerable aquifer.

Our application of the method to the La Fontaine du Theil catchment led to relevant results, but applying the sizing method to each buffer zone individually proved quite tedious. This recognition led to the development of nomograms based on numerous simulations covering a wide range of scenarios in consideration of climatic, soil, topographical and crop features. These nomograms are easier to use, and yet their sound application requires providing data and adhering to the hypothesis of the present method. The complete method, nevertheless, will still prove useful in specific situations not covered by the pre-simulated scenarios. These nomograms must be enriched with more scenarios. Such work is currently on-going for a wider range of curve numbers and rainfall scenarios that cover the entire French territory and a user-chosen level of efficiency. The resulting tool will be freely accessible online. It could be extended to other countries provided rainfall data are available. Such nomograms could be applied to refine the homologation process employed in step 4. They could also be used for purposes of contamination risk management (e.g., in the case of permanent vegetated devices which are now compulsory in France to commercialize certain phytosanitary products (MAAP, 2006), whereby they could allow for the protection surface water without becoming oversized.

Acknowledgements

This work was achieved within the framework of a research and development project funded by the French Agriculture Ministry, which determines agricultural policies (DGPAAT. Convention MAAF(DGPAAT / S Dir B&E / BSE) – Irstea. Agriculture et gestion durable de l’eau- 2012-2014) focused on developing an operational VFS sizing method. The abacus study was funded by the ECPA through the TOPPS-Prowadis project (<http://www.topps-life.org>) aimed at developing methods and tools for protecting water from non-point pesticide pollution. Irstea directed the VFS diagnosis and sizing work. The authors wish to thank Clotaire Catalogne, Guy Le Hénaff and Jean-Joel Gril for their contributions and Alexandra Fontaine for providing an early version of the contributive area hydrograph assessment tool using a spreadsheet..

References

- Arora, K., Mickelson, S.K., Baker, J.L., Tierney, D.P., Peters, C.J., 1996. Herbicide retention by vegetative buffer strips from runoff under natural rainfall. *Trans. ASAE* 39, 2155-2162.
- Arora, K., Mickelson, S.K., Helmers, M.J., Baker, J.L., 2010. Review of Pesticide Retention Processes Occurring in Buffer Strips Receiving Agricultural Runoff1. *JAWRA Journal of the American Water Resources Association* 46, 618–647. doi:10.1111/j.1752-1688.2010.00438.x
- Aubert, Y., Arnaud, P., Ribstein, P., Fine, J.-A., 2014. The SHYREG flow method-application to 1605 basins in metropolitan France *Hydrological Sciences Journal*. 59, 993-1005.
- Bernard, K., Carluier, N., Le Henaff, G., 2014. Limitation du transfert hydrique des produits phytosanitaires par les zones tampons : caractérisation de l’existant et propositions de dispositifs correctifs et complémentaires. *Techniques Sciences Méthodes* 83–99. doi:10.1051/tsm/201412083 (*in French*).
- Beven, K.J., Wood, E.F., Sivapalan, M., 1988. On hydrological heterogeneity — Catchment morphology and catchment response. *Journal of Hydrology* 100, 353–375. doi:10.1016/0022-1694(88)90192-8
- Brown, C., Balderacchi, M., van Beinum, w., Capri, E., Trevisan, M., 2012. Definition of vegetative filter strip scenarios for Europe. Environment Department, University of York, Heslington, York, YO10 5DD, UK, p. pp. 71.
- Bouwer, H., 1969. Infiltration of water into nonuniform soil. *Journal of Irrigation and Drainage Division* 95, 451–462.
- Carluier, N., Noll, D., Bernard, K., Fontaine, A., Lauvernet, C., 2014. Dimensionner les zones tampons enherbées et boisées pour réduire le transfert hydrique des produits phytosanitaires. *Techniques, Sciences et Méthodes* 12, 101-120 (*in French*).
- Chow, V.T., Maidment, D.R., Mays, L.W., 1988. *Applied Hydrology*. New York.
- CORPEN, 2007. Les fonctions environnementales des zones tampons – Les bases scientifiques et techniques des fonctions de protection des eaux, première édition, Comité d’orientation pour des pratiques agricoles respectueuses de l’environnement.
- CORPEN, 1997. Produits phytosanitaires et dispositifs enherbés – État des connaissances et propositions de mise en œuvre . Comité d’orientation pour la réduction de la pollution des eaux par les nitrates, les

- phosphates et les produits phytosanitaires provenant des activités agricoles.
- Daniels, R.B., Gilliam, J.W., 1996. Sediment and Chemical Load Reduction by Grass and Riparian Filters. *Soil Science Society of America Journal* 60, 246. doi:10.2136/sssaj1996.03615995006000010037x
- Devers-Lamrani, M., Pesce, S., Rouard, N., Martin-Laurent, F., 2014. Evidence for cooperative mineralization of diuron by *Arthrobacter* sp. BS2 and *Achromobacter* sp. SP1 isolated from a mixed culture enriched from diuron exposed environments. *Chemosphere* 117, 208–215. doi:10.1016/j.chemosphere.2014.06.080
- Dosskey, M.G., Helmers, M.J., Eisenhauer, D.E., 2006. An Approach for Using Soil Surveys to Guide the Placement of Water Quality Buffers. *Journal of Soil and Water Conservation* 61, 344–354.
- Dosskey, M.G., M.J. Helmers, D.E. Eisenhauer. 2008. A design aid for determining width of filter strips. *Journal of Soil and Water Conservation* 63(4):232-241, doi:10.2489/jswc.63.4.232.
- Dosskey, M.G., Helmers, M.J., Eisenhauer, D.E., 2011. A design aid for sizing filter strips using buffer area ratio. *Journal of Soil and Water Conservation* 66, 29–39. doi:10.2489/jswc.66.1.29
- Fox, G., Munoz-Carpena, R., Sabbagh, G., 2010. Influence of flow concentration on parameter importance and prediction uncertainty of pesticide trapping by vegetative filter strips. *Journal of Hydrology* 384, 164–173. doi:10.1016/j.jhydrol.2010.01.020
- Gascuel Odoux, C., Weiler, M., Molenat, J., 2010. Effect of the spatial distribution of physical aquifer properties on modelled water table depth and stream discharge in a headwater catchment. *Hydrol. Earth Syst. Sci* 14, 1179-1194.
- Helmers, M.J., Isenhardt, T.M., Dosskey, M., Dabney, S.M., Strock, J.S., 2008. Buffers and Vegetative Filter Strips. USDA Forest Service / UNL Faculty Publications.
- Lacas, J.-G., Voltz, M., Gouy, V., Carluier, N., Gril, J.-J., 2005. Using grassed strips to limit pesticide transfer to surface water: a review. *Agron. Sustain. Dev.* 25, 253–266. doi:10.1051/agro:2005001
- Lacas, J.-G., Carluier, N., Voltz, M., 2012. Efficiency of a Grass Buffer Strip for Limiting Diuron Losses from an Uphill Vineyard Towards Surface and Subsurface Waters. *Pedosphere* 22, 580–592. doi:10.1016/S1002-0160(12)60043-5
- Lauvernet, C. and Muñoz-Carpena, R., *submitted*. Shallow water table effects on water, sediment and pesticide transport in vegetative filter strips, II. Overland flow and transport coupling, factor importance and uncertainty.
- Lowrance, R., Hubbard, R.K., Williams, R.G., 2000. Effects of a managed three zone riparian buffer system on shallow groundwater quality in the southeastern Coastal Plain. *Journal of Soil and Water Conservation* 55, 212–220.
- MAAP (2006). Arrêté du 12 septembre 2006 relatif à la mise sur le marché et à l'utilisation des produits visés à l'article L. 253-1 du code rural et de la pêche maritime
- Madrigal-Monarrez, I., 2004. Rétention de pesticides dans les sols des dispositifs tampon, enherbés et boisés. Rôle des matières organiques. Institut Agronomique Paris-Grignon, p. 212
- Muñoz-Carpena, R., Parsons, J.E., Gilliam, J.W., 1999. Modeling hydrology and sediment transport in vegetative filter strips. *Journal of Hydrology* 214, 111–129. doi:10.1016/S0022-1694(98)00272-8

- 512 Muñoz-Carpena, R., Parsons, J.E., 2004. A design procedure for vegetative filter strips using VFSDMOD-W.
513 Transactions of the ASAE 47, 1933–1941. doi:10.13031/2013.17806
- 514 Muñoz-Carpena, R., Fox, G., Sabbagh, G., 2010. Parameter Importance and Uncertainty in Predicting Runoff
515 Pesticide Reduction with Filter Strips. Journal of Environmental Quality 39, 630–641.
516 doi:10.2134/jeq2009.0300
- 517 Muñoz-Carpena, R., Lauvernet, C., Carluier, N., *submitted*. Shallow water table effects on water, sediment and
518 pesticide transport in vegetative filter strips, I. Unsteady rainfall infiltration and soil water
519 redistribution.
- 520 Park, Y.S., Engel, B.A., Shin, Y., Choi, J., Kim, N.-W., Kim, S.-J., Kong, D.S., Lim, K.J., 2013. Development of Web
521 GIS-Based VFSDMOD System with Three Modules for Effective Vegetative Filter Strip Design. Water 5,
522 1194–1210. doi:10.3390/w5031194
- 523 Poletika, N.N., Coody, P.N., Fox, G.A., Sabbagh, G.J., Dolder, S.C., White, J., 2009. Chlorpyrifos and Atrazine
524 Removal from Runoff by Vegetated Filter Strips: Experiments and Predictive Modeling. Journal of
525 Environmental Quality 38, 1042–1052. doi:10.2134/jeq2008.0404
- 526 Reichenberger, S., Bach, M., Skitschak, A., Frede, H.-G., 2007. Mitigation strategies to reduce pesticide inputs
527 into ground- and surface water and their effectiveness; A review. Science of The Total Environment
528 384, 1–35. doi:10.1016/j.scitotenv.2007.04.046
- 529 Rouxel, M., Molénat, J., Ruiz, L., Legout, C., Fauchaux, M., Gascuel-Oudoux, C., 2011. Seasonal and spatial
530 variation in groundwater quality along the hillslope of an agricultural research catchment (Western
531 France). Hydrol. Process. 25, 831–841. doi:10.1002/hyp.7862
- 532 Sabbagh, G.J., Fox, G.A., Kamanzi, A., Roepke, B., Tang, J.-Z., 2009. Effectiveness of Vegetative Filter Strips in
533 Reducing Pesticide Loading: Quantifying Pesticide Trapping Efficiency. J. Environ. Qual. 38, 762.
534 doi:10.2134/jeq2008.0266
- 535 Saxton, K.E., Rawls, W.J., 2006. Soil Water Characteristic Estimates by Texture and Organic Matter for
536 Hydrologic Solutions. Soil Science Society of America Journal 70, 1569–1578.
537 doi:10.2136/sssaj2005.0117
- 538 Schaap, M.G., Leij, F.J., van Genuchten, M.T., 2001. rosetta: a computer program for estimating soil hydraulic
539 parameters with hierarchical pedotransfer functions. Journal of Hydrology 251, 163–176.
540 doi:10.1016/S0022-1694(01)00466-8
- 541 Simpkins W, Wineland T, Andress R, Johnston D, Caron G, Isenhardt T, Schultz R, 2002. Hydrogeological
542 constraints on riparian buffers for reduction of diffuse pollution: examples from the Bear Creek
543 watershed in Iowa, USA. Water Science and Tech. 45, 61–68.
- 544 Tomer, M., Dosskey, M., Burkart, M., James, D., Helmers, M., Eisenhauer, D., 2008. Methods to prioritize
545 placement of riparian buffers for improved water quality. Agroforestry Systems 17–25.
546 doi:10.1007/s10457-008-9134-5
- 547 USDA-SCS, 1972. National Engineering Handbook, Part 630 Hydrology., Washington, D.C.
- 548 White, M.J., Arnold, J.G., 2009. Development of a simplistic vegetative filter strip model for sediment and
549 nutrient retention at the field scale. Hydrol. Process. 23, 1602–1616. doi:10.1002/hyp.7291

Appendix 1

Table 7: Characterization of hydrologic soil groups for contributive areas (USDA, 1972).

SOIL - hydrology groups	A	B	C	D
Water transmission	Free	Still free	Somewhat restricted	Restricted
Clay amount	< 10%	10 to 20%	20 to 40%	➤ 40%
Sand / Gravel	➤ 90%	50 to 90%	< 50%	< 50%
Texture	Sand /Gravel	Loamy sand, sandy loam	Silt loam, sandy clay loam, silty clay loam	Clay (high shrinking and swelling potential)
Soil types	Loamy sand, sandy loam, silt loam	Loam, silt loam, sandy clay loam	Clay, silty clay, sandy clay	Clay (impermeable layer < 50 cm high water table)

Additional materials

- The VFSSMOD model with a shallow water table is opensource and can be downloaded from <http://abe.ufl.edu/carpa/vfssmod/>.
- Nomograms resulting from simulations of the French scenarios shown in Tables 4 and 5 are in the file complete_nomograms_results.pdf
- Hyetohydro tool that generates hyetographs and hydrograms for France is available at ZT_eq_PollDiff@irstea.fr, as spreadsheets.
- The tool BUVARD online, which allows exploring nomograms and running the models within an interface will be available on Dec. 2016 on <http://www.irstea.fr/la-recherche/unites-de-recherche/maly/pollutions-agricoles-diffuses->

Table caption

Table 1: Curve number values for the different scenarios. Curve numbers II and III respectively denote average and wet antecedent conditions. Unf and fav respectively denote unfavourable and favourable hydrological conditions.

Table 2: VFS soil parameters by soil type.

Table 3: Sizing (dimensions in meters) for each VFS and for each scenario studied for the Fontaine du Theil catchment. Dimensions are obtained for winter scenarios (in blue), summer conditions with 2 hours of rainfall (in orange), and summer conditions with 6 hours of rainfall (in green). VFS values denote to plots from which runoff is collected. The n17a addresses cases where the VFS n28 is implemented, limiting the area intercepted by n17. A width of > 25 denotes any value obtained by the model that exceeds 25 m. Int.crop denotes “Intermediate crop to trap nitrates”. Ratio surface/length denotes: [contributive area surface/VFS length]. Slope designates the contributive area slope. For purposes of clarity, and because these VFSs run along several plots, n17 concerns plots 17, 18, 27 and 31; n60 concerns

Table 4: Representative rainfall event characteristics.

Table 5: Contributive area curve number values.

Table 6: Vegetative Filter Strip soil parameters.

Figure Caption

Figure 1: Processes occurring in a grassed filter strip. From (Lacas *et al.*, 2012)

Figure 2: Sizing method flowchart

Figure 3: Rainfall hyetographs on the Fontaine du Theil by season, duration, and type (left: moderate, right: intensive).

Figure 4: VFSMOD optimising example for the Fontaine du Theil catchment. The desired efficiency is a reduction of 70% of incoming runoff (green dotted line). Scenarios T1 to T4 correspond with upstream wheat crops (initial moisture conditions are average for T1 and wet for T2) and maize (initial moisture conditions are average for T3 and wet for T4). For the T1 scenario, a 5 m width is sufficient. The T2 scenario requires a width of 15 m to achieve the 70% efficiency level.

Figure 5: Fontaine du Theil Catchment soil map. Description of the plot and of soils in the river network and widths obtained for VFS. Dimensions in meters are obtained for winter scenarios (in blue), summer conditions with 2 hours of rainfall (in orange), and summer conditions with 6 hours of rainfall (in green). As it is not realistic to apply a VFS that exceeds 25 m in width in France or in Europe more generally, any value above is written as '>25'.

Figure 6: Monthly rainfall (Average, 20th and 80th centiles). Left: northern scenario. Right: southern Mediterranean scenario.

Figure 7: Example of a buffer sizing nomogram for a northern France climate scenario. Region N denotes northern France climatic conditions; Soil A denotes the contributive area soil hydrological class; VFS Soil sL denotes that the buffer zone soil has a sandy loam texture; and W1m & S2.5 m denotes the buffer zone location. The water table is very shallow in the winter (1 m) and deeper in the summer (2.5 m).

Table 7:

	Winter						Summer					
	G1		G2		G3		G1		G2		G3	
Crop	Wheat	Interme- diate crop	Wheat	Interme- diate crop	Wheat	Interme- diate crop	Wheat	Corn	Wheat	Corn	Wheat	Corn
Ksat (mm/h)	14,53		14,53		11,08		14,53		14,53		11,08	
Texture	silt-loam		silt-loam		silt-loam		silt-loam		silt-loam		silt-loam	
Initial hydrological group	C		C		C		C		C		C	
Water table depth	5		5		1		5		5		2.5	
Final hydrological group	B		B		C		B		B		C	
Hydrological conditions	unf	fav	unf	fav	unf	fav	fav	unf	fav	unf	fav	unf
Crop % soil covering	10	90	10	90	10	90	90	25	90	25	90	25
Curve Number II	84	69	84	69	92	82	83	89	83	89	83	89
Curve number III	92	84	92	84	96	91	92	95	92	95	92	95

Table 8:

	G1	G2	G3
Reference layer	B	E	S
Ksat (mm/h)	13.17	6.97	10.59
n	1.95	1.92	1.98
alpha (m ⁻¹)	0.44	0.33	0.38
m	0.49	0.48	0.49
Saturated water content	43.5	39.9	42.7
Residual water content	11.700	10.400	10.900

611 **Table 9:**

		Winter						Summer								
Rainfall duration (h)			Ratio area / length (m²/m)	Slope (%)	24		3		2				6			
Cumulated rainfall (mm)					26.7		11.0		14.6				21.4			
Land cover					wheat	Int.crop	wheat	Int.crop	wheat	corn			wheat	corn		
Initial soil humidity conditions					II	II	III	III	II	III	II	III	II	III	II	III
VFS soil	VFS N°															
G1, brown soil of hill slope	n3	435	4.2	5	5	5.28	5	5	12.7	5.9	23.7	5	19.2	13	>25	
	n10	312	4.6	5	5	5	5	5	9.15	5	17.5	5	13.9	9.5	21.3	
	n17	204	7.5	5	5	5	5	5	5.77	5	12.4	5	9.27	6.3	14.3	
	n17a	129	9.1	5	5	5	5	5	5	5	8.41	5	6.25	5	9.25	
	n28	96	4.7	5	5	5	5	5	5	5	6.7	5	5	5	7.5	
	n45	177	5.0	5	5	5	5	5	5	5	9.84	5	7.66	5.1	12.1	
	n60	314	2.7	5	5	5	5	5	7.27	5	15.3	5	13.2	8.7	20	
	n64	203	4.0	5	5	5	5	5	6.3	5	11.3	5	8.92	6.3	13.7	
G2, leached brown soil on hill-slope	n24	144	3.1	5	5	5	5	5	5.1	5	11	5	9.64	6.5	14.8	
	n25	146	3.0	5	5	5	5	5	6.2	5	12.2	5	10.3	6.8	15.8	
G3, low-lying hydromorphic brown	n26	156	3.3	> 25	> 25	> 25	> 25	5	7.5	5	14.3	5	15.1	10	24.6	
	n56	201	2.6	> 25	> 25	> 25	> 25	5	9.29	5	17.7	5.8	19.2	13	>25	
	n62	472	4.8	> 25	> 25	> 25	> 25	5	20.5	11	>25	12.3	>25	>25	>25	

612

613

614 **Table 10: Representative rainfall event characteristics.**

	Northern France (Amiens)			Southern France (Roujan)		
	Winter (12 h)	Summer (2 h)	Summer (6 h)	Winter (12 h)	Summer (2 h)	Summer (6 h)
Rainfall event volume (mm)	14.7	12.3	17.4	48.4	31.2	46.7
Type of rainfall event	Moderate	High	Moderate	Moderate	High	Moderate

615

616 **Table 11: Contributive area curve number values.**

Winter: Wheat.				
Type of soil*	A	B	C	D
Curve number value (Humidity condition: II)	70	81	89	93
Curve number value (Humidity condition: III)	84	91	95	97
Summer: Corn.				
Type of soil*	A	B	C	D
Curve number value (Humidity condition: II)	72	83	90	94
Curve number value (Humidity condition: III)	86	92	95	97

Table 12: Vegetative Filter Strip soil parameters.

VFS Soil	Silt loam	Sandy loam	Clay loam	Sandy clay loam
Nomenclature	SIL	SAL	CLO	SCL
n (Van Genuchten)	1.6647	1.44	1.45	1.3636
Alpha (1/m)	0.54	2.4	1.01	1.91
Theta _r	0.0679	0.055	0.0833	0.0655
Theta _{sat} VFS	0.458	0.478	0.456	0.49487
Ksat VFS (cm/day)	23	98.626	49.487	53.934

Figure 1

Figure 2

Figure 3

Figure 4

Figure 5

Figure 6

642

643

644 **Figure 7**

645