



MCEM algorithm for the log-Gaussian Cox process

Céline Delmas, Nathalie Dubois Peyrard Peyrard, Régis Sabbadin

► To cite this version:

Céline Delmas, Nathalie Dubois Peyrard Peyrard, Régis Sabbadin. MCEM algorithm for the log-Gaussian Cox process. workshop of Spatial Statistics for Image Analysis and Biology, May 2014, Aalborg, Denmark. 32 p. hal-02739481

HAL Id: hal-02739481

<https://hal.inrae.fr/hal-02739481>

Submitted on 2 Jun 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

MCEM algorithm for the log-Gaussian Cox process

Céline Delmas, Nathalie Peyrard, Régis Sabbadin

UR 875 - Unité de Mathématiques et Informatique Appliquées, Toulouse

INRA, 24 Chemin de Borde Rouge - Auzeville - CS 52627

31326 Castanet Tolosan cedex

Abstract Log-Gaussian Cox processes are an important class of models for aggregated point patterns. They have been largely used in spatial epidemiology (Diggle et al., 2005), in agronomy (Bourgeois et al., 2012), in forestry (Moller et al.), in ecology (sightings of wild animals) or in environmental sciences (radioactivity counts).

A log-Gaussian Cox process is a Poisson process with a stochastic intensity depending on a Gaussian random field. We consider the case where this Gaussian random field is centered with exponential covariance function. Moreover we assume that we observe count variables in disjoint quadrats assumed to be the same up to a translation. In that special case, we consider the problem of the estimation of the parameters of the log-Gaussian Cox process. We propose a MCEM algorithm and compare this algorithm to a moments method. Our MCEM algorithm considers the non observed count variables and the Gaussian random field as hidden variables. Simulations show that, in most cases, this MCEM algorithm improves the precision of the estimations in comparison to the moments method.

As a future direction of this work, we will discuss the problem of the optimal sampling for estimation and prediction. We will also discuss the problem of hypothesis testing.

Bibliography

- BOURGEOIS, A., GABA, S., MUNIER-JOLAIN, N., BORGY, B., MONESTIEZ, P., SOUBEYRAND, S. (2012) Inferring weed spatial distribution from multi-type data. *Ecological Modelling*, 226, 92-98.
- DIGGLE, P.J., ROWLINGSON, B., SU, T.L. (2005) Point process methodology for on-line spatio-temporal disease surveillance *Environmetrics*, 16, 423-434.
- EMERY, X., HERNANDEZ, J. (2010) A computer package for modeling and simulating regionalized count variables. *Computers & Geosciences*, 36, 24-33.
- MOLLER, J., SYVERSVEEN, A.R., WAAGEPETERSEN, R.P. Log Gaussian Cox Processes: A Statistical Model for Analyzing stand structural heterogeneity in Forestry.