



Cross-flow ultrafiltration of skim milk assisted by ultrasound: multi-scale approach

Y Jin, N. Hengl, F Pignon, N. Gondrexon, M Sztucki, T Narayanan,
Geneviève Gésan-Guiziou

► To cite this version:

Y Jin, N. Hengl, F Pignon, N. Gondrexon, M Sztucki, et al.. Cross-flow ultrafiltration of skim milk assisted by ultrasound: multi-scale approach. Euromembrane 2015, Sep 2015, Aachen, Germany. hal-02743704

HAL Id: hal-02743704

<https://hal.inrae.fr/hal-02743704>

Submitted on 3 Jun 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Cross-flow ultrafiltration of skim milk assisted by ultrasound: multi-scale approach

Jin Y.^a, Hengl N.^{a*}, Baup S.^a, Pignon F.^a, Gondrexon N.^a, Sztucki M.^b, Narayanan T.^b, Gésan-Guiziou G.^c

^a Laboratoire Rhéologie et Procédés, UJF, G-INP, CNRS, BP 53, 38041 Grenoble Cedex 9

^b European Synchrotron Radiation Facility, BP220 38043 Grenoble Cedex 9

^c INRA UMR1253 STLO Science et technologie du lait et de l'œuf, 65 rue de Saint-Brieuc - 35042 Rennes Cedex


^d Agrocampus Ouest, UMR1253 STLO 65 rue de Saint-Brieuc - 35042 Rennes Cedex

The bottleneck of skim milk ultrafiltration (UF) is the fouling phenomenon that affects the process performance thus limits the productivity. Several strategies have been chosen to control fouling. Some proposed to increase the shear rate close to the membrane^[3], others suggested different procedures such as backpulsing^[4], pulsating or reversed feed flows^[5]. The ultrasonic-assisted filtration processes have been also proposed to enhance the cleaning process or the permeate flux. Several successful examples can already be found in literature^[6-7].

Our recent work has shown a great interest to apply *in-situ* ultrasound (US) in colloidal suspensions filtration: with a designed 'Cross-Flow US-coupled Filtration Cell' at low US power (2 W.cm^{-2}), a significant increase of permeate flux was observed without damaging the membrane structure^[8].

Using the designed 'SAXS Cross-Flow US-coupled Filtration Cell', this study is devoted to enhance skim milk ultrafiltration by applying *in-situ* ultrasonication and to characterize effects of ultrasound at multi-scales: the macroscopic results, presented by the permeate flux, have been combined with simultaneous detections at nanometer length scale, revealed by *in-situ* SAXS measurements of synchrotron radiation^[9].

Skim milk suspensions were prepared from 'low heat' Bovine Skim Milk Powder at $C_0=27 \text{ g.L}^{-1}$ in casein micelle content. Figure.1a displays the evolution of permeate flux J_v , inlet/outlet pressures of filtration cell and cross-flow rate Q_v over time. The filtration run is divided into 4 steps according to different operating conditions.



* Hengl Nicolas: nicolas.hengl@ujf-grenoble.fr

Fig.1. Combination of macro-scale results and nano-scale detections during milk ultrafiltration ($C = C_0$, pH 6.8). $T = 25 \pm 1^\circ\text{C}$. Ultrasound: 20 kHz, 2 W.cm^{-2} . a) Cross-flow filtration curve, b) Related concentration profiles at steady state from the membrane surface to the bulk, deduced from *in-situ* SAXS measurements.

According to figure 1, a simultaneous ultrasonic irradiation has been shown as an efficient way to improve cross-flow ultrafiltration of skim milk with a factor of 2: It has led to a significant increase of permeate flux, which can be explained by a partial disruption of the concentrated layer, as evidenced from *in-situ* SAXS measurements. These results emphasize the promising potential in applying *in-situ* ultrasonication to membrane separation processes in dairy industry.

- [1] Paugam L., Delaunay D., Diagne N.W. et al., *Journal of Membrane Science*, 428 275–280. **2013**.
- [2] Rabiller-Baudry M., Bégoin L., Delaunay D. et al., *Chemical Engineering Process and Process Intensification*, 47 267–275. **2008**.
- [3] Krstić D.M., Tekić M.N., Carić M.Đ. et al., *Journal of Membrane Science*, 208 303–314. **2002**.
- [4] Redkar S., Kuberkar V., Davis R.H., *Journal of Membrane Science*, 121 229–242. **1996**.
- [5] Curcio S., Calabrò V., Iorio G., *Desalination*, 145 217–222. **2002**.
- [6] Muthukumaran S., Kentish S., Ashokkumar M. et al., *Journal of the Acoustical Society of America*, 123 (5), 3046-3046, **2008**.
- [7]. Mirzaie A, Mohammadi T., *Journal of Food engineering*, 108 77–86. **2012**.
- [8] Hengl N., Jin Y., Pignon F. et al., *Ultrasonics Sonochemistry*, 21 1018-1025. **2013**.
- [9] Jin Y., Hengl N., Baup S. et al, *Journal of Membrane Science*, 470 205–218. **2014**.