



HAL
open science

Developing a methodology for identifying action zones to protect and manage groundwater well fields

Sandra Bellier, Pascal Viennot, Emmanuel Ledoux, Céline Schott

► To cite this version:

Sandra Bellier, Pascal Viennot, Emmanuel Ledoux, Céline Schott. Developing a methodology for identifying action zones to protect and manage groundwater well fields. EGU General Assembly 2013, 2013, VIENNE, Austria. , Geophysical Research Abstracts, 15, 1 p., 2013, 10th EGU General Assembly. hal-02746960

HAL Id: hal-02746960

<https://hal.inrae.fr/hal-02746960>

Submitted on 3 Jun 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Developing a methodology for identifying action zones to protect and manage groundwater well fields

Sandra Bellier (1), Pascal Viennot (1), Emmanuel Ledoux (1), and Celine Schott (2)

(1) MINES ParisTech, Geosciences Department, 77305 Fontainebleau, France (sandra.bellier@mines-paristech.fr), (2) INRA/SAD- 88500 Mirecourt, France(Celine.Schott@mirecourt.inra.fr)

Implementation of a long term action plan to manage and protect well fields is a complex and very expensive process. In this context, the relevance and efficiency of such action plans on water quality should be evaluated. The objective of this study is to set up a methodology to identify relevant actions zones in which environmental changes may significantly impact the quantity or quality of pumped water.

In the Seine-et-Marne department (France), under French environmental laws three sectors integrating numerous well-field pumping in Champigny's limestone aquifer are considered as priority. This aquifer, located at south-east of Paris, supplies more than one million people with drinking water. Catchments areas of these abstractions are very large (2000 km²) and their intrinsic vulnerability was established by a simple parametric approach that does not permit to consider the complexity of hydrosystem. Consequently, a methodology based on a distributed modeling of the process of the aquifer was developed.

The basin is modeled using the hydrogeological model MODCOU, developed in MINES ParisTech since the 1980s. It simulates surface and groundwater flow in aquifer systems and allows to represent the local characteristics of the hydrosystem (aquifers communicating by leakage, rivers infiltration, supply from sinkholes and locally perched or dewatering aquifers). The model was calibrated by matching simulated river discharge hydrographs and piezometric heads with observed ones since the 1970s. Thanks to this modelling tool, a methodology based on the transfer of a theoretical tracer through the hydrosystem from the ground surface to the outlets was implemented to evaluate the spatial distribution of the contribution areas at contrasted, wet or dry recharge periods. The results show that the surface of areas contributing to supply most catchments is lower than 300 km² and the major contributory zones are located along rivers. This finding illustrates the importance of rivers seepage for groundwater recharge.

In parallel, validation of the modelled hydrodynamic system was reinforced by implementing nitrogenous contamination simulations. This pollution is linked to intensive farming activities practised on the basin since the early 70's. This modelling was realized by coupling the hydrological model MODCOU and the agronomic model STICS allowing to generate the spatio-temporal evolution of sub-root nitrogen fluxes stemming from intensive farming. The evolution of nitrate concentrations observed and simulated in groundwater confirms the strong reactivity of the Champigny's aquifer to nitrogen fluxes entering the system.

For the contributory zones, the calculated transfer time between these areas and catchments shows very short transfer times in stream infiltration sectors (less than 2 years), and longer transfer times (up to 10 years) from layers partially occupied by an upper aquifer existing in the overlying formation of Brie's limestones.

The relationship between the main recharge areas and transfer times, between these areas and a specific well field, allows to determine relevant priority action areas. Action plans of such protected areas should be applied to manage long term changes represented by an evolution of the polluting fluxes that result from land use change or evolution in the recharge conditions of hydrosystem.