

DIC process for treatment of organic materials

Magdalena Kristiawan, Vaclav Sobolik, Mazen Al Haddad, Karim Allaf

▶ To cite this version:

Magdalena Kristiawan, Vaclav Sobolik, Mazen Al Haddad, Karim Allaf. DIC process for treatment of organic materials. International Workshop on Process Intensification in Fluid and Particle Engineering, Oct 2006, Kobe, Japan. Chemical Engineering of Japan, Journal of Chemical Engineering of Japan, 40, pp.1021-1029, 2006, Isolation of Indonesian Cananga Oil by Instantaneous Controlled Pressure Drop: Influence of Processing Parameters on Compound Yields. hal-02754479

HAL Id: hal-02754479 https://hal.inrae.fr/hal-02754479v1

Submitted on 3 Jun2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

<u>C5. Int. Workshop on Process Intensification in Fluid and Particle Engng., Kobe</u> <u>University, Japan, Oct.15-18 2006, Abstract</u>

Full text article was published in Journal of Chemical Engineering of Japan: KRISTIAWAN M., SOBOLIK V., ALLAF K.: Isolation of Indonesian Cananga Oil by Instantaneous Controlled Pressure Drop: Influence of Processing Parameters on Compound Yields. Journal of Chemical Engineering of Japan. 40(11), 1021-1029 (2007).

DIC process for treatment of organic materials

V. Sobolik, Magdalena Kristiawan, M. Al Haddad, K. Allaf

University of La Rochelle, Pole Sciences, Laboratory Mastering of Agro-Industrial Technologies Avenue Michel Crépeau, 17042 La Rochelle, France

Abstract

A new process for material texturing, instantaneous controlled pressure drop (DIC), consists in heating wet materials in an autoclave, followed by a fast expansion ($\Delta P/\Delta t > 2.10^5$ Pa/s) into a pressure lower than the atmospheric one (5 kPa). The vapour, which evolves due to the rapid pressure drop, mechanically strains the material. This stress creates porous structures, breaks the cells and destroys micro-organisms. The temperature of the material before the expansion is usually higher than 100°C and the pressure in the autoclave corresponds to the saturated steam pressure. Manifold applications of this process are presented on the example of the extraction of essential oil from dried ylang-ylang flowers. The essential oil is separated from the condensate. The treated flowers are also analysed. The results are compared with the classical steam distillation.

Keywords: Ylang-ylang, extraction, essential oil, steam distillation, Instantaneous Controlled Pressure Drop

IWPI 2006 (http://www2.kobe-u.ac.jp/~iwpi/).