



**HAL**  
open science

## **Instant controlled pressure drop (DIC) as a process of extraction of volatile oils: the impact of the rate of pressure drop**

Magdalena Kristiawan, Colette Besombes, Vaclav Sobolik, Karim Allaf

### ► **To cite this version:**

Magdalena Kristiawan, Colette Besombes, Vaclav Sobolik, Karim Allaf. Instant controlled pressure drop (DIC) as a process of extraction of volatile oils: the impact of the rate of pressure drop. 37. International Symposium on essential oils ISEO 2006, Sep 2006, Grasse-Opio, France. hal-02757638

**HAL Id: hal-02757638**

**<https://hal.inrae.fr/hal-02757638v1>**

Submitted on 4 Jun 2020

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

**C6.**

**37th INTERNATIONAL SYMPOSIUM  
ON ESSENTIAL OILS  
ISEO 2006**

Grasse – Opio  
September 10-13, 2006

**PROGRAM  
BOOK OF ABSTRACTS  
LIST OF PARTICIPANTS**

Organization:

Club des Entrepreneurs du Pays de Grasse

PRODAROM

Association des Ingénieurs et Techniciens de la Parfumerie (AITP)

---

**Edited by Daniel Joulain**

## Instant Controlled Pressure Drop (DIC) as a process of extraction of volatile oils: the impact of the rate of pressure drop.

Magdalena Kristiawan, Colette Besombes, Vaclav Sobolik and Karim Allaf

La Rochelle University, Laboratory of Mastering Technologies for Agro-Industries LMTAI,  
Avenue Michel Crépeau, 17042 La Rochelle, France. E-mail: karim.allaf@univ-lr.fr

After having studied the use of the Instant Controlled Pressure Drop (DIC) technology as a process of extraction of volatile oils in the cases of some aromatic flowers and herbs as lavender and Indonesian ylang-ylang (*Cananga odorata*) flowers, we investigated the real impact of the rate of dropping the pressure on the process efficiency.

The DIC process is based on the thermo-mechanical effects induced by subjecting the raw material for a short time steam pressure (about  $1.10^5$  Pa to  $6.10^5$  Pa depending on the product), followed by an abrupt pressure drop towards vacuum (about 0.50 kPa.) (1). The fact of the use of abrupt pressure drop may provoke higher effect of autovaporization of volatile compounds, coupled to an instant cooling of the products allowing stopping thermal degradation, modification of the internal structure and eventually implies the rupture of cell walls, which enhances the internal diffusion.

In the present paper, we first describe the influence of process parameters, namely steam pressure ( $2.10^5$ - $6.10^5$  Pa), total processing time (30 sec - 20 min), and number of DIC cycles (1-9), on the oil yield and composition. The Instant Controlled Pressure Drop (DIC) (1) as a volatile oil extraction technique allows us to get a rapid, clean and environmentally friendly process: The DIC can be compared to the conventional technique of steam distillation (SD), but it is superior in terms of rapidity, oil yields and also oil quality. As an example, in the case of Indonesian ylang-ylang, the optimized total DIC processing time is 30 sec or 4 min versus 12 hours or 24 hours with steam distillation respectively; the oil yields are respectively 2.45% versus 2.4% or 2.74% versus 2.60%.

But we particularly studied the impact of the speed of pressure drop  $\Delta P/\Delta t$ . We increased this speed from  $2.10^5$  Pa.s<sup>-1</sup> up to  $5.10^6$  Pa.s<sup>-1</sup> with the same optimized processing parameters in terms of steam pressure, total processing time and number of DIC cycles. We proved systematically that the higher the pressure drop speed, the higher the total yields. In all cases, the total yield is doubled at the highest value of  $\Delta P/\Delta t$ ; the characteristic of DIC as "instant" pressure drop may then be quantified.

### References.

(1) K. Allaf, S.A. Rezzoug, F. Cioffi, M.P. Contento, *Processus de traitement thermo-mécanique par Détente Instantanée Contrôlée des fruits, jus et peaux d'agrumes*. PCT International Patent application WO 00/13352 (13/16/2000), Priority FR 98/11105 09/04/1998).

(2) H. Mellouk, G. Naji G, K. Allaf, in : Proceedings of 16<sup>th</sup> Agoral meeting, Nantes, France, 2004, pp. 265-269.