



**HAL**  
open science

## Electro-fermentation: a bio-electrochemical way to control glycerol fermentation

Roman Moscoviz, Eric Trably, Nicolas Bernet

### ► To cite this version:

Roman Moscoviz, Eric Trably, Nicolas Bernet. Electro-fermentation: a bio-electrochemical way to control glycerol fermentation. 5. International Meeting on Microbial Electrochemistry and Technologies - ISMET2015, Oct 2015, Tempe, United States. pp.1, 2015. hal-02794546

**HAL Id: hal-02794546**

**<https://hal.inrae.fr/hal-02794546>**

Submitted on 5 Jun 2020

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## Electro-fermentation: a bio-electrochemical way to control glycerol fermentation

Roman Moscoviz, Eric Trably and Nicolas Bernet

INRA, UR0050, Laboratoire de Biotechnologie de l'Environnement (LBE), Avenue des étangs, F-11100, Narbonne, France  
E-mail: roman.moscoviz@supagro.inra.fr; eric.trably@supagro.inra.fr; nicolas.bernet@supagro.inra.fr

In the field of fermentation biotechnologies, mixed cultures processes are more and more considered as a viable industrial alternative to pure culture fermentation, beyond their usual usages in waste and wastewater treatment or in food industry. From an industrial point of view, mixed-culture fermentations present many advantages. As an illustration, it is possible to work under non-sterile conditions and to use cheap and raw non-purified substrates. Yet the usual environmental parameters (pH, temperature, OLR...) are often not efficient enough to control the activity of the microbial community and the main drawback of using mixed cultures is their high versatility in metabolic patterns. It is therefore not rare to observe a lack of selectivity in the molecules produced, lowering the product yield.

In this work, we propose to use bio-electrochemical systems (BESs) as a new way to control fermentation patterns in a process named electro-fermentation. In this process, electricity is provided to the micro-organisms as it is in microbial electrosynthesis systems but not as sole electron donor. The electrochemical input of electrons is an additional reducing power to micro-organisms along with a fermentation substrate.

Electro-fermentation of glycerol to 1,3-propanediol (1,3-PDO) by a mixed culture in a minimal medium was performed and compared to conventional fermentation. The working electrode, used as a cathode, was precolonized by the electro-active bacteria *Geobacter sulfurreducens* and poised at  $-0.6V$  vs. SHE. The electron input represented less than 1% of the total reducing equivalent introduced in the reactor but the fermentation pattern was significantly different between fermentation and electro-fermentation. 1,3-PDO production yield was increased by 32% in electro-fermentation. The obtained value of  $0.62 \pm 0.07 \text{ mol}_{1,3\text{-PDO}} \text{ mol}^{-1}_{\text{glycerol}}$  was very close to the maximum theoretical yield of  $0.64 \text{ mol}_{1,3\text{-PDO}} \text{ mol}^{-1}_{\text{glycerol}}$ .