

Crust formation and runoff of a red soil from subtropical China: effect of rainfall kinetic energy

Hu Zhou, Frédéric Darboux, Xinhua Peng

▶ To cite this version:

Hu Zhou, Frédéric Darboux, Xinhua Peng. Crust formation and runoff of a red soil from subtropical China: effect of rainfall kinetic energy. 2. International Conference on Hydropedology 2012, Helmholtz Centre for Environmental Research (UFZ). Leipzig, DEU., Jul 2012, Leipzig, Germany. hal-02808015

HAL Id: hal-02808015 https://hal.inrae.fr/hal-02808015

Submitted on 6 Jun2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



S4: Soil Architecture - oral

Crust formation and runoff of a red clay soil from subtropical China: effect of rainfall kinetic energy

Hu Zhou⁽¹⁾, Frédéric Darboux⁽²⁾, Xinhua $\text{Peng}^{(1)}$

 ⁽¹⁾Institute of Soil Science, CAS, 71 Beijing East Road 210008 Nanjing CN
⁽²⁾INRA, UR 0272 Science du sol, Centre de recherche d'Orléans, Cs 40001 45075 Orléans Cedex 2 FR

Abstract: Red clay soils from subtropical China (Ultisol) are not considered currently as sensitive to crusting and erosion by water. However, recent field data showed erosion can be significant. To investigate the sensitivity of red clay soil to crusting and runoff, a laboratory rainfall study was carried out. Because rainfall kinetic energy is known to have an important effect on aggregate breakdown and therefore crust formation, two treatments were applied: high kinetic energy (HKE) and low kinetic energy (LKE). Air-dried soil was packed in a soil box (50 cm \times 50 cm) and was subjected to 38 mm.h-1 rain for 90 min (3 replicates per treatment). Samples were taken for preparing soil thin sections and runoff, splash, and percolation were measured during the rain. Crusts formed after 40 min and 60 min of rain for the HKE and LKE treatment, respectively. Runoff for the HKE treatment started after 25 min of rain and reached a steady state after the crust well formed (50 min). While for the LKE, runoff started after 40 min of rain and kept increasing to a final runoff rate similar to the HKE treatment. Percolation started after 57 min of rain for the LKE treatment while no percolation occurred for the HKE treatment. The total mass of splashed material was 12 times higher for the HKE treatment than for the LKE treatment and significantly more soil was eroded for the HKE treatment. Stability tests gave mean weight diameters of 0.55 mm, 1.48 mm, and 1.74 mm for the fast wetting, mechanical stirring, and slow wetting, respectively, indicating red clay soils are very sensitive to slaking. The results show that Ultisol is prone to crusting and that kinetic energy is a major driver of their crust formation. Reducing the rain kinetic energy can preserve aggregate structure and delay the development of crust, which subsequently increase infiltration and decrease runoff and erosion on red soils.

1