



**HAL**  
open science

## Experimental design to model infiltration into a water repellent soil using a crust-type infiltration equation

Dennis Fox, Cyriel Adnès, Jean Morschel, Frédéric Darboux

### ► To cite this version:

Dennis Fox, Cyriel Adnès, Jean Morschel, Frédéric Darboux. Experimental design to model infiltration into a water repellent soil using a crust-type infiltration equation. 3. International Meeting of Fire Effects on Soil Properties (FESP III), Mar 2011, Guimarães, Portugal. , 2011. hal-02810406

**HAL Id: hal-02810406**

**<https://hal.inrae.fr/hal-02810406>**

Submitted on 6 Jun 2020

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# EXPERIMENTAL DESIGN TO MODEL INFILTRATION INTO A WATER REPELLENT SOIL USING A CRUST-TYPE INFILTRATION EQUATION

Dennis M. Fox<sup>a,\*</sup>, Cyriel Adnès<sup>a</sup>, Jean Morschel<sup>a</sup>, Frédéric Darboux<sup>b</sup>

<sup>a</sup>UMR 6012 Espace CNRS, University of Nice Sophia Antipolis, BP 3209 Nice cedex 3, France. Tel: (33) 493 375 542. E-mail: fox@unice.fr

<sup>b</sup>INRA, UR 0272 Science du sol, Centre de recherche d'Orléans, CS 40001 - Ardon, F-45075 Orléans Cedex 2, France.

The combustion of vegetation during forest fires can lead to the condensation of hydrophobic compounds on mineral matter near the soil surface. The resulting water repellent layer then inhibits water infiltration by altering soil hydraulic conductivity and the water content–soil matric suction relationship. This situation resembles that of a crust or seal capped soil, where a thin layer of reduced hydraulic conductivity overlays a more permeable soil. Although the physical processes leading to a surface seal or crusted layer are different from those of a water repellent layer, the infiltration modelling approach can theoretically be the same, as would be the case for all layered soils. The objective of this study was to test the use of a crust type infiltration equation ( $IR = K_{wi}[(h_0 - \psi + Z_{wi})/Z_{wi}]$ ; where  $IR$ =Infiltration rate ( $\text{cm h}^{-1}$ ,  $K_{wi}$ =hydraulic conductivity of the water repellent layer ( $\text{cm h}^{-1}$ ),  $h_0$ =depth of ponded water at surface (cm),  $\psi$ =sub-layer matric suction (-cm),  $Z_{wi}$ =thickness of the water repellent layer (cm)) for water repellent conditions. The study was carried out by applying simulated rainfall on a column of soil with the following dimensions: column diameter=13 cm, soil depth within the column=10 cm, and an underlying coarse sand layer for drainage=10 cm. Runoff from the surface of the column was collected in a beaker that was weighed continuously at 30 s intervals.

Instantaneous infiltration was considered equal to the difference between the applied rainfall (about  $40 \text{ mm h}^{-1}$ ) and runoff rates. The soil column was equipped with a tensiometer located near the centre of the column at a depth of 3 cm below the soil surface, and it measured soil matric suction at 30 s intervals. Before each simulation, a mass of oven dried pine needles was applied to the surface and burned in-situ. Different levels of water repellency were generated by varying the amount of pine needles burnt, and water drop penetration time (WDPT) measurements were carried out on all samples before rainfall application. Hence, a range of water repellent conditions was tested for which instantaneous infiltration and matric suction values were recorded. Water repellent layer depth was estimated using WDPT measurements at different depths on separate samples. These samples also served for aggregate stability samples. The infiltration model was then compared to measured values.

Keywords: water repellency; hydrophobicity; layered soils; infiltration