

Lai products and validation for hydrological processes

Frédéric Baret, Bruno Combal, Sophie Moulin, Cédric Bacour, Marie Weiss, Sébastien Garrigues

▶ To cite this version:

Frédéric Baret, Bruno Combal, Sophie Moulin, Cédric Bacour, Marie Weiss, et al.. Lai products and validation for hydrological processes. 27. EGS/ European Geophysical Union general assembly, Apr 2002, Nice, France. 1 p. hal-02832602

HAL Id: hal-02832602 https://hal.inrae.fr/hal-02832602

Submitted on 7 Jun2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

LAI PRODUCTS AND VALIDATION FOR HYDROLOGICAL PROCESSES

<u>Frédéric Baret(1)</u>, Bruno Combal(1), Sophie Moulin(1), Cédric Bacour (1), Marie Weiss(1, 2) and Sébastien Garrigues (1)

(1) INRA-CSE, Avignon, <u>baret@avignon.inra.fr/Fax</u> +33-432722362,

(2) Noveltis, Parc du Canal, Avenue Hermès, 31 055 Toulouse

Leaf area index (LAI) is a very important variable required in many hydrological processes. It controls evapotranspiration in several ways, rain interception and run-off. However, because LAI may change rapidly with space and time, estimates derived from remote sensing data could be used as input to spatially distributed hydrological models running at a range of scales.

The derivation of LAI from remote sensing data is not straightforward since several factors may confound LAI effect on reflectance. We propose to use radiative transfer model inversion to estimate LAI from top of canopy reflectance measurements. Several inversion approaches are compared, with emphasis put on the regularisation of the inverse process by introducing prior information on the variables.

Applications of this approach is made over several agricultural data sets at high spatial resolution (few 10th meters) thanks to hyperspectral (CASI, HYMAP) and BRDF (POLDER) airborne sensors. It includes the ReSeDA experiment on the Alpilles site in 1997 based on POLDER sensor, the Blue Earth experiment based on CASI in 1997, the DAISEX experiment in 1999 with POLDER and HYMAP and the Laon experiment based on CASI data in 2000 and 2001.

The limitations of these approaches are discussed, with due attention on the way to derive prior information, inverse techniques, uncertainties on measurements and models, and scaling effects.