



## Pipelines for semantic annotation and FAIR data production

Christian Pichot, Damien Maurice, Philippe Clastre, Benjamin Jaillet, Rachid Yahiaoui

### ► To cite this version:

Christian Pichot, Damien Maurice, Philippe Clastre, Benjamin Jaillet, Rachid Yahiaoui. Pipelines for semantic annotation and FAIR data production. RDA 17th Plenary Meeting, Apr 2021, Edinburgh, United Kingdom. hal-03234314

HAL Id: hal-03234314

<https://hal.inrae.fr/hal-03234314>

Submitted on 25 May 2021

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

# Pipelines for semantic annotation and FAIR data production

PICHOT C. (1), MAURICE D. (2), YAHIAOUI R. (3), CLASTRE P. (1), JAILLET B. (1)

1. INRAE URFM 228 route de l'Aérodrome 84914 Avignon

2. INRAE UMR SILVA route d'Amance 54280 Champenoux .

3. INRAE US INFOSOL 2163 avenue de la Pomme de Pin 45075 Orléans




## Context and objective

The AnaEE (Analysis and Experimentation on Ecosystems) Research Infrastructure offers experimental facilities for studying ecosystems and biodiversity. The data generated by the AnaEE platforms are most often managed in relational database.

A distributed Information System (IS) is developed, based on semantic interoperability of its components and using common vocabularies (AnaeeThes thesaurus and OBOE-based ontology). Discovery and access portals are fed by information (rdf triples) produced by the semantic annotation of the resources that also generate metadata and datasets.


Two pipelines are developed for facilitating the semantic annotation and exploitation processes which may represent a huge conceptual and practical work.

### Experimental, analytical and modelling platforms




## Semantic data generation from a pipeline for database annotation

Variable semantic description					
AnaEE standard	Category	Context	Entity	Characteristic	Unit
Phytoplankton	Biodiversity	Water	Phytoplankton	Volume Per Volume	MicroMeterCubed Per Millimeter
WaterPH	Physical Chemistry	Water Column	Water	pH	pHUnit
...	...	...	...	...	...



← A **csv input file** describes the main characteristics of the variables submitted for semantic annotation, allowing to parametrize generic semantic graphs (Yed\* format).



The **annotation pipeline\*\*** can be used in different contexts of ontologies and databases.

It includes shell scripts and specific java developments and requires the Yed, Ontop, Corese and Blazegraph softwares. It is deployed as a classical scripted application or as a dockerised one.

The annotation pipeline consists in 4 steps:

1. generation of the mapping files to be used by Ontop\*\*\* (database connexion parameters, sets of sql queries and of the corresponding triples)
2. production of the initial triples (ttl files) by a specific program and Ontop tool.
3. production of inferred triples by Corese\*\*\*\* from the ontology rules
4. uploading of the ttl files within the Blazegraph\*\*\*\*\* software and initialisation of the end point

Current developments will allow data annotation from several relational database software (PostgreSQL, MySQL, ...) and csv flat files.

\*<https://www.yworks.com/products/yed>  
\*\*<https://forgemia.inra.fr/anaee-dev/coby>  
\*\*\*Diego Calvanese, Benjamin Cogrel, Sarah Komla-Ebri, Roman Kontchakov, Davide Lanti, Martin Rezk, Mariano Rodriguez-Muro, and Guohui Xiao. Ontop: Answering SPARQL Queries over Relational Databases. In: Semantic Web Journal 8.3 (2017), pp. 471–487.  
\*\*\*\*<http://wimmics.inria.fr/corese>  
\*\*\*\*\*[https://wiki.blazegraph.com/wiki/index.php/Main\\_Page](https://wiki.blazegraph.com/wiki/index.php/Main_Page)

## Semantic data exploitation by a pipeline for metadata and datasets generation

Outputs of the annotation pipeline are used by an **exploitation pipeline\*** for:

1. generation (through a SPARQL query on raw data) of synthetic data that feeds the discovery portal,
2. generation of standardised GeoDCAT and ISO19115/19139 metadata records,
3. generation of data file (NetCDF as first format) from selected perimeters (e.g years, experimental sites , variable categories..). In that case, the annotation pipeline is launched using a dedicated webservice.

Metadata and data products are transferred to a Dataverse repository

\* <https://forgemia.inra.fr/anaee-dev/semsdata>

