Streamflow naturalization methods: a review

Morgane Terrier, Charles Perrin, Alban de Lavenne, Vazken Andréassian,
Julien Lerat, Jai Vaze

► To cite this version:

Morgane Terrier, Charles Perrin, Alban de Lavenne, Vazken Andréassian, Julien Lerat, et al.. Streamflow naturalization methods: a review. Hydrological Sciences Journal, 2021, 66 (1), pp.12-36. 10.1080/02626667.2020.1839080 . hal-03266329

HAL Id: hal-03266329

<https://hal.inrae.fr/hal-03266329>

Submitted on 21 Jun 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Streamflow Naturalization Methods: a Review

Journal:	<i>Hydrological Sciences Journal</i>
Manuscript ID	HSJ-2019-0348.R1
Manuscript Type:	Original Article
Date Submitted by the Author:	11-Jun-2020
Complete List of Authors:	Terrier, Morgane; Irstea, Perrin, Charles; Irstea (Cemagref), UR HBAN De Lavenne, Alban; SMHI Andréassian, Vazken; Cemagref, Unité de Recherche HBAN, Groupe Hydrologie Lerat, Julien; Bureau of Meteorology, Environment and Research – Forecast Systems Vaze, Jai; CSIRO, Land and Water
Keywords:	Naturalization methods, Influenced catchments, Impacted catchments, Uncertainty, Hydrological modelling

SCHOLARONE™
Manuscripts

Streamflow naturalization methods: a review

Morgane Terrier^a, Charles Perrin^{a*}, Alban de Lavenne^b, Vazken Andréassian^a, Julien Lerat^c, Jai Vaze^d

^a *Université Paris-Saclay, INRAE, UR HYCAR, Antony, France*

^b *SMHI, Hydrology department, Norrköping, Sweden*

^c *Bureau of Meteorology, Canberra, ACT, Australia*

^d *CSIRO Land and Water, Black Mountain Laboratories, Canberra, ACT, Australia*

^{*} *Corresponding author: charles.perrin@inrae.fr*

Abstract

Over the past few decades, several naturalization methods have been developed for removing anthropogenic influences from streamflow time series to the point that naturalized flows are often considered as true natural flows in many studies. However, such a trust in a particular naturalization method does not expose the assumptions underlying the method, nor does it quantifies the associated uncertainty.

This review provides an overview of streamflow naturalization approaches. The terminology associated with naturalization is discussed and a classification of naturalization methods according to the data requirements and main assumptions is proposed.

A large set of studies developing or applying naturalization methods are reviewed and the main challenges associated with the methods applied are assessed. To give a more concrete example, a focus is made on studies conducted in France over the last decade, which applied naturalization methods to estimate water extraction limits in rivers.

Keywords: Naturalization methods; Streamflow; Human influences; Impacted catchments; Uncertainty; Hydrological modelling

1 Introduction

1.1 *Natural, influenced and naturalized flows*

Humans have fundamentally affected the continental hydrological cycle through the impoundment of rivers, land use changes, water extractions and the long-term effect of climate change (Dynesius and Nilsson, 1994; Steffen et al., 2011; Vidal, 2019; Vörösmarty and Sahagian, 2000). Since the 1950s, there has been phenomenal growth of human enterprise, which resulted in an exponential increase in the number of large dams and water consumption (Steffen et al., 2015). These human influences continue to have a significant impact on observed river flows, which will be qualified as "influenced" in the rest of this paper. As highlighted by the Panta Rhei decade launched by the International Association of Hydrological Sciences (IAHS) in 2013, knowledge of the interactions between humans and water remains limited (Montanari et al., 2013). Therefore the natural and anthropogenic parts of the observed flows need to be distinguished (Littlewood and Marsh, 1996). Anthropogenic is understood here as relating to or resulting from the influence of human beings on nature (<https://www.merriam-webster.com/dictionary/anthropogenic>).

In case of existing human influences upstream of a gauging station, observed flows are generated both by natural processes and human activities. Therefore natural flows cannot be directly measured and must be estimated. Two main types of approaches are adopted to get natural flows:

- **Using reference high quality flow observation:** Reference Hydrologic Networks (RHNs) have been established in several countries (Burn et al., 2012; Whitfield et al., 2012). The gauging stations are selected for having stable land-use conditions in upstream catchment, no significant regulation, enough record length, active data collection, high data quality and adequate metadata

1
2
3 51 (Whitfield et al., 2012). They represent how catchments respond to climate
4
5 52 variability and serve as reference to hydrological trends induced by climate-
6
7 53 driven changes and in studies at the regional scale.
8
9

- 10 54 • **Using naturalization methods:** in case there are human influences, dedicated
11
12 55 methods have to be applied to retrieve the natural flow regime from influenced
13
14 56 flow in a target basin. The natural flow estimates are then called naturalized
15
16
17 57 flows.
18

19 58 In this article, we will focus on the second type of approach. Naturalization methods use
20
21 59 various sources of information depending on their availability, typically observed
22
23
24 60 influenced flows, volumes linked to human influences, flows observed before or after
25
26 61 the period of influence, or flows free from influence at the regional scale. Naturalization
27
28 62 methods are all based on models, some of which are very crude (typically a water
29
30 63 balance equation) and others are more complex and comprehensive. Hydrological
31
32 64 models, representing the rainfall-runoff relationship at the catchment scale, or routing
33
34 65 models, representing the upstream-downstream flow propagation, are commonly used in
35
36 66 naturalization methods. In cases of insufficient or too coarse data on influences, models
37
38 67 may be also needed to generate information on these human-induced influences.
39
40
41
42
43

44 68 **1.2 Why do we need natural flows?**

45 69 As noted by the Canadian Science Advisory Secretariat (MPO, 2013), the flow of a
46
47 70 river is the main variable that connects eco-system components along a river corridor
48
49 71 via hydrological, biological, geomorphological, and water quality processes. As a result,
50
51 72 natural flow can be typically used as a reference to estimate hydrological response to
52
53 73 climate regime, to evaluate the ecological state of a river (Poff et al., 1997) and to
54
55 74 estimate the quantity of water available. Here we detail three domains for which natural
56
57 75 flows are needed and naturalization methods can therefore be helpful.
58
59
60

- **Ecological impact assessment**

Naturalization methods contribute to the evaluation of anthropogenic impacts on ecosystems. Comparing naturalized streamflows against influenced streamflows provides a way to assess the anthropogenic impact on the natural environment (Poff et al., 1997, Rahman and Bowling, 2018). The degree of alteration corresponds to the difference between naturalized and observed streamflows (Jacobson and Galat, 2008), or the difference between indicators computed on these streamflows (Richter et al., 1996). These indicators include the magnitude of monthly flows, magnitude and duration of annual extreme floods, timing of annual extreme floods, frequency and duration of high and low pulses, and rate and frequency of flow changes (Birkel et al., 2014; De Girolamo et al., 2015; Fantin-Cruz et al., 2015; Fernández et al., 2012; Laizé et al., 2014; Ryo et al., 2015).

The classical approach to quantify the degree of alteration consists in using the observed natural flow from a pre-influence period. However, if these observations are not available or on a too short duration to give a robust estimates of hydrological indicators (Fantin-Cruz et al., 2015), naturalization methods can provide an estimation of natural flow based on data from the influenced period only. Moreover, observed natural flows over the pre-influence period may not be representative of the climate and physical conditions of the influenced period due to natural evolution and variability. Consequently they may not be exploitable for human impact studies. Naturalization methods also make it possible to separate the impact due to anthropogenic pressures (local or regional) and the impact caused by climate change, and to quantify them. The anthropogenic impact corresponds to the difference between the naturalized and observed streamflow during the influenced period. The climatic impact corresponds to a difference between the naturalized flow over the influenced period and the observed

1
2
3 101 natural flow of an earlier period. As an example, naturalization has been applied in
4
5 102 China to quantify climatic and anthropogenic impacts: on the Haihe River basin (Bao et
6
7 103 al., 2012; Wang et al., 2013; Zhan et al., 2013), the Yellow River basin (Hu et al., 2015;
8
9 104 Li et al., 2007; Wang et al., 2010), the Miyun reservoir (Ma et al., 2010), the Yangtze
10
11 105 River basin (Li et al., 2013) and Poyang Lake (Gu et al., 2017), the Laohahe River basin
12
13 106 (Jiang et al., 2011) and the Shiyang River basin (Huo et al., 2008). Similarly, in
14
15 107 Australia, the CSIRO (2008) conducted the Sustainable Yields project to assess climate
16
17 108 change impacts on the Murray-Darling basin, at a detailed basin scale.

21
22 109 • **Climate impact issue**

23
24 110 In a context of climate change, many studies prefer to focus on projections of "natural
25
26 111 streamflows", even in heavily influenced rivers, because it would be too complex to
27
28 112 address the issues of climate change and water use changes at the same time. Therefore,
29
30 113 flow naturalization becomes necessary to serve as a baseline, as well as to calibrate
31
32 114 hydrological models. For example, in the case study of the Seine River, Dorchies et al.,
33
34 115 (2014) used the naturalized streamflow on the 1990-2011 period to calibrate a model to
35
36 116 estimate the future available water resources for the 2046-2065 period. On a larger
37
38 117 scale, in the SCENES project (water Scenarios for Europe and Neighbouring States),
39
40 118 Laizé et al. (2014) used the naturalized streamflow on the 1961-1990 period as a
41
42 119 baseline to estimate the future of freshwater resources for 2040-2069.

46
47 120 • **Water resources management**

48
49 121 In many countries, regulations on the authorization of abstractions and discharges into
50
51 122 rivers, and on the good ecological status of rivers, are based on naturalized hydrological
52
53 123 indicators. The environmental conditions enabling governmental agencies to protect,
54
55 124 restore or rehabilitate rivers, can be linked to components of the natural flow regime
56
57 125 (Poff et al., 1997). Two of the main approaches to obtain an environmental flow regime
58
59
60

are linked to the natural flow regime (Acreman and Dunbar, 2004): the look-up tables approach is based on the statistical properties of the natural flow regime and the desktop analysis approach is based on the natural seasonality and variability of flows. These methods, failing to have access to observed natural flow, use a naturalized flow regime. In a regulation context, management of water resources is essential to satisfy the supply of drinking water, preserve the ecological status of the aquatic environment, limit the negative consequences of floods and droughts, and provide water for different economic needs such as industry, agriculture, fishing and electricity (European Commission, 1997). In this perspective, naturalized flow can be used to simulate different water management scenarios and the impact of these scenarios on the quantity of available water (Desconnets et al., 1998; Dunn and Ferrier, 1999; Kim and Wurbs, 2011; Maurel et al., 2008; Wurbs, 2006). Naturalization methods also constitute one of the fundamental element supporting water management policies. For example, the Water Framework Directive typically appeals to natural conditions to define the natural status of a river (Bouleau and Pont, 2015). In France, naturalization methods are used to estimate maximum water extractions sustaining environmental flows (Fabre et al., 2016). In the UK, the Environmental Agency developed guidelines to provide naturalized low-flow statistics to enable regulators to make licensing decisions (Bullock et al., 1991; Holmes et al., 2002; Young et al., 2003). These results make it possible, in particular, to define the maximum possible withdrawals to maintain good ecological status (Acreman et al., 2008).

1.3 Key challenges around naturalization

Flow naturalization faces several challenges. From a theoretical point of view, a naturalized flow could be defined as a flow observed in the absence of human activities in the catchment upstream of the gauging station. However, the definition of a natural

status of a catchment may be difficult for various reasons, e.g. when the catchment characteristics and the human influences have been co-evolving over a long period. Therefore, there is not always a clear distinction between the influenced period and the pre- or post-influenced periods, which may limit the naturalization process. Obviously, this will be hugely dependent on the geographical region, since some have known the human influence over centuries though others were only influenced over the last few decades.

Another issue lies in the lack of justification in the choice of naturalization methods in many studies. The application of naturalization methods raises hypotheses, in particular in terms of transposition (i.e. transfer of information) in space and time, which seem rarely verified. This may limit the reliability of naturalized flow estimates.

Finally, naturalized flows are often implicitly considered accurate estimates of natural flow. In practice, naturalized flows include uncertainties arising from method assumptions, data and models used. It is therefore important to be transparent about these uncertainties to avoid mis-use of natural flows data when uncertainty is large.

1.4 Objectives

The main objective of this article is to provide a review on the issue of flow naturalization. More specifically, this paper intends to (1) provide an overview of the naturalization methods, their assumptions and associated tools, and (2) highlight the scientific issues raised by the application of naturalization methods commonly done in scientific or operational studies.

Establishing a corpus of studies on naturalization methods is not straightforward. Indeed, naturalization methods used to estimate flow series free from anthropogenic influence are rarely the main focus of scientific publications, though they remain a necessary step for many issues detailed above. In addition, there is a quite large

terminology to address naturalization issues (see the discussion in section 3.1). Therefore, the literature review presented in this article is probably not exhaustive though it encompasses already a wide range of aspects. Selected articles in this review dates back to the 1970s, with a recent increase in publications after 2010, showing a growing interest in this issue in the water management community.

This paper is organized as follows. Section 2 lists the main human influences considered in this paper and their potential impact on the natural hydrological cycle. Then section 3 investigates the concept of naturalized flow and how it is interpreted in the literature reviewed. Section 4 presents the main types of naturalization methods with their underlying assumptions and uncertainties. Section 5 discusses scientific and technical issues associated with naturalization methods, with an example in France. Finally section 6 gives some concluding remarks.

2 Potential impact of anthropogenic influences on streamflow

2.1 Human impacts considered

A prerequisite for streamflow naturalization is to identify the nature of human impacts and quantify them to determine which influences should be considered in the naturalization process. Figure 1 (Botai et al., 2015) summarizes how human activities potentially affect the different components of the hydrological cycle. The main anthropogenic influences are land cover and land use change, streamflow regulation infrastructure, and withdrawals and discharges associated with different water uses (we did not consider here the impacts of human activities on climate, which ultimately impact water resources). Most of these influences potentially impact several components of the water cycle and so directly or indirectly the observed streamflow. We detail their main impacts in the following paragraphs. Some of these impacts may

be interlinked or show counterbalancing effects. For example, in-basin water abstraction and release may compensate to some extent at the catchment scale, with limited net impact on mean flow at the yearly scale. However, they may more deeply modify catchment dynamics at the seasonal or event scale (high or low flows). Other activities will always strongly impact catchment water yields and hydrological dynamics, e.g. inter-basin water transfers.

[Figure 1 near here]

2.2 Dams and their associated storage

Among the 62 studies applying naturalization methods we reviewed, 47 are considering the impact of dams and artificial reservoirs. The hydrological modifications caused by dams have two origins (McCully, 2001): the impacts due to the management of the dam (alternating operations of water storage and release) and the impacts stemming from the ponding effect of the reservoir. The presence of the stagnant water body, created by the dam, modifies several components of the local hydrological cycle, including evaporation and infiltration, and local precipitation for large dams (Degu and Hossain, 2012; Haberlie et al., 2016). It may also strongly modify water quality (Winton et al., 2019). A permanent rise in the water table downstream can be caused by infiltration from the reservoir. The dam operations, consisting of periods of storage and release, regulate water flows in a way generally opposite to natural processes (typically flood alleviation or low-flow augmentation). They also result in various states of the lake behind the dam: for flood protection, the reservoir should be as empty as possible and for potable water supply, the reservoir should be as full as possible (Margat and Andréassian, 2008). From a temporal point of view, dams can cause changes in flow seasonality and temporary fluctuations, especially hydro-power dams. The management

of hydro-power reservoirs will depend on the profitability of electricity generation; for agriculture purposes, it will depend on crop need. Since each dam has specific management rules, the impacts of the dams and their amplitudes are each time specific. Note that the cumulated effect of dams over a catchment may also be considered. This is often the case when there are many small farm dams spread over a catchment. In that case, this is often much more difficult to access data for each dam and a meta-analysis over all dams may be preferred (Dong et al., 2019; Fowler et al., 2015; Hughes and Mantel, 2010).

2.3 Water withdrawal

Water withdrawals refer to the amount of freshwater that is artificially extracted from groundwater or surface water resources. The consumptive use of water corresponds to "the part of water withdrawn that is evaporated, transpired, incorporated into products or crops, consumed by humans or livestock, or otherwise not available for immediate use" (USGS and National Water-Use Science Project, 2019). In our case, water returned to a different catchment than the point of withdrawal (interbasin transfer) is considered a consumptive use. Therefore the quantity of water withdrawn from a river cannot be considered a good indicator of the actual quantitative impact of withdrawals, and the consumed water quantity should be used instead. According to the report of the World Water Development Program (WWAP, 2009), agriculture is the largest consumer of water with 90% consumption for drip irrigation and 50-60% for surface irrigation. The energy sector has the smallest consumption ratio on the order of 1-2%. Domestic uses consume between 10 and 20% of the water withdrawn, and industry between 5 and 10%. These figures, however, remain overall estimates with large variability between regions. Water withdrawal can have a temporal impact because of the time lag between

the time the water is withdrawn and the moment when the amount of water not consumed returns to the system (Kendy and Bredehoeft, 2006).

Two sources of water are distinguished: water withdrawn from the groundwater and water abstracted from the surface. Surface water withdrawals have a direct and rapid impact on streamflow. Groundwater withdrawals have an indirect or *delayed* impact on river flows. Exchanges between surface water and groundwater can occur in both directions: a water table lower than the free surface of the river leads to a recharge of the aquifer by the river; the situation is reversed if the groundwater level is higher. Disturbance of the river-groundwater table balance can lead to a drop in the water table and/or an increase in the recharge rate, and so indirectly influences streamflow (Theis, 1941). *With only four articles considering groundwater abstraction*, this type of withdrawals remains limited in our article database, but it is more widespread in operational studies to quantify the available water.

2.4 *Water release*

Water releases refer to the amount of water that is artificially brought to rivers. Two cases of water release can be distinguished: water releases originating from a withdrawal on the basin and the releases from an inter-basin water transfer. Inter-basin water transfer corresponds to the artificial withdrawal of water by ditch, canal or pipeline from its source in one basin for use in another (Slabbert, 2007). The streamflow of the receiving basin can consequently be artificially increased. It can also impact the seasonality of river flows. For example, in several rivers in South African, inter-basin transfers aim to counter temporal variability and reduce the economic impact of a localised drought (Blanchon, 2005). In the case of a release following a withdrawal within the catchment, one part of the water withdrawn having been consumed, the

release has a reduced impact on the water resource quantity but an impact on the temporality of observed streamflow. In the case where the release place differs from the withdrawal place, release can impact the spatial distribution of water resources.

2.5 Land use and land cover change

Human activities can lead to a change in land use and land cover through urbanization, agricultural development, afforestation and deforestation. In the article database, human influences related to land use are taken into account in the naturalization process in only eleven studies, although they are the most pervasive anthropogenic impact (Pagano and Sorooshian, 2005). Changes in land use and land cover have an indirect impact on flow. In modifying the quantity of energy absorbed by the surface, the evaporation rate is impacted and the precipitation rate can also be modified in changing the temperature gradient (Giambelluca, 2005). Groundwater recharge and overland flow are also impacted. Moreover, numerous studies on land use and land cover change and its impact on the hydrological cycle have been carried out in relatively small paired catchments (Stednick, 1996), with results that are difficult to generalize to a larger scale (Siriwardena et al., 2006; Zhang et al., 2018). The particularity of land use change is that modification of the evapotranspiration-runoff relation at the local scale can impact the regional water balance because of changes in atmospheric circulation (Bosmans et al., 2017; Chase et al., 2000; Gash and Nobre, 1997).

2.6 Combination of human impacts

In practice, observed flow at gauging stations is potentially influenced by several existing human activities in the basin: industries, energy production at the hydroelectric dam, agriculture, recreational activities (e.g. ski resorts, navigation for pleasure boating) and cities (see illustration in Figure 2).

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

296 [Figure 2 near here]

297 Flow regulation and direct withdrawal and discharge in rivers lead to a sudden change
298 (typically on a daily basis) in river streamflow, whereas the impacts on the other
299 components of the hydrological cycle can take longer to impact the observed
300 streamflow. The time delay of the impact on the observed flow is also conditioned by
301 the distance between the source of the influence and the gauging station, and by the
302 water pathways. For example, in Figure 2, stations A2 and C are both influenced by the
303 dam's management. The A2 station, directly downstream of the dam, is impacted sooner
304 than station C due to shorter propagation time.

305 The importance of the influenced signal contained in the observed streamflow can be
306 conditioned by several factors. Distance plays a role because the intermediate
307 hydrological processes can mitigate the importance of the impact (Mwedzi et al., 2016).
308 Thus, the influence of the dam at station C is much less than at station A2, because dam
309 releases will represent a smaller proportion of the total streamflow at station C than at
310 station A2, due to inflows by the intermediary basin. In the case of basins with multiple
311 influences, there can be compensations of some impacts: dam releases can be planned
312 for agricultural withdrawals downstream, and therefore their impact may not be visible
313 at the catchment outlet, the reservoir can increase groundwater recharge and thus
314 compensate the effects of underground withdrawals in summer (Constantz and Essaid,
315 2007).

316 The impact of human activities on flow therefore depends on several factors specific to
317 each basin (type of influence and location, basin characteristics). The following sections
318 present if and how impacts are taken into account in the naturalization process.

3 Defining the natural state of the flow regime

In naturalization studies, the purpose is to produce a reference flow regime for influenced rivers. First, the question of what the natural regime of a river corresponds to is addressed, followed by the use and identification of the reference period in studies.

3.1 Naturalization terminology

Examples of scientific definitions of "natural streamflow" or "natural regime" are provided in Table 1. For definitions (D1) and (D3), it is possible to have a natural streamflow despite the presence of anthropogenic factors as long as it does not significantly impact streamflow. Moreover, (D1) and (D2) include the notion of runoff, which can be modified by land use change, without specifying whether it is from a natural or anthropic source. Only (D3), which remains quite comprehensive by referring to "human activity", could take into account this notion of land use and land cover change by human intervention. The first three definitions refer to climate as a variable of the natural regime even though climate change is linked to greenhouse gases emitted by humans. Although (D2) does not refer to the catchment in its natural state, it refers to the drainage network, and thus the aspect of the natural geomorphology of the river. (D4) remains quite general by referring to natural conditions without explaining what they are.

[Table 1 near here]

Although there is no common definition of natural streamflow, we summarise the previous definitions as follows: a naturalized streamflow refers to an estimation of the natural flow under specified conditions of river basin development that includes either no human impact or some defined low level of development (Wurbs, 2006).

In the literature, it appears that the streamflow obtained in naturalization is not systematically called "naturalized streamflow" and may be designated by other words which are not necessarily synonymous. We will present the terms by which some authors refer to naturalized flows and discuss the nuances in the definition of naturalized flow that these terms imply. First, there are the terms referring to the influenced state of the basin such as the terms "regulated" or "influenced" streamflow. Following existing definitions of regulated flow (AFB and Ministère chargé de l'environnement, 2016a; Bureau of Meteorology, 2012; Environmental Protection Agency, 2015; WaterNSW, 2015), an unregulated streamflow corresponds to a natural flow not impacted by artificial flow-regulation structures. The influences of land-use changes are therefore not included. The terms "uninfluenced" and "unimpaired" flow refer to the flow of an undisturbed stream caused by human interventions and whose flows retain their general characteristics (AFB and Ministère chargé de l'environnement, 2016b). The uninfluenced flow thus takes into account a wider field of influence such as the change of land use and land cover. Other terms refer to the natural state of the catchment such as "flow under natural conditions" and "natural flow". The "simulated natural streamflow" encountered in some studies refers to a naturalized streamflow obtained using a hydrological model. The terms of "reconstructed or estimated natural/virgin streamflow" are synonymous with naturalized streamflow. Although all these terms refer to a naturalized flow, they may not reflect the same natural reference. So, the nuances between these terms must not be forgotten to avoid confusion.

3.2 Determination of the basin's baseline condition

As illustrated in Figure 3, three periods can be distinguished in naturalization. The

influenced period corresponds to the period when the observed flows are impacted by anthropogenic influences. Over this period, where no observation of the natural flow is available, one seeks to estimate natural streamflow using naturalization methods.

[Figure 3 near here]

The pre-influence period serves as the basin's baseline condition and is assumed to correspond to a past period when the observed flow is considered as free of the impact of the anthropogenic influences **considered in the naturalization processes**. Information from this pre-influence period is used by several naturalization methods. **However, in many cases, the influence dates back before flow measurements were made and there is therefore no information on natural flows.**

The post-influence period corresponds to the period after the influences **considered in the basin has ceased and a return to a natural state, which may be different from the state before the influence. This period is also relevant to serve as a natural reference period if the system has enough time to return to uninfluenced conditions. Obviously, the post-influence period does not exist in catchments under active anthropogenic activities. Studies exploiting the post-influence period mainly focus on sediment dynamics and fauna and flora species after a dam removal (Hart et al., 2002; Kibler et al., 2011; Magirl et al., 2014). Therefore, post-influence periods will not be discussed in this paper, however some comments about the pre-influence period are somewhat transposable to post-influence.**

The use of data from the pre-influence and post-influence periods to estimate the natural regime over a later influenced period raises a question about the reversibility of the system: if all activities stopped, would the river be able to return to a natural state that it would have reached if it had never been influenced (Cooper, 2004)? In some cases, the

influence of humans is so old that it has shaped the characteristics of the basin and it represents the new natural condition. For example in southern France, the system Neste was created in the 19th century for irrigation purposes. This network of canals strongly impacted the land use of a large number of small catchments, with conditions now that are very different from those that were before (Tardieu, 2008; Villocel, 2002). Still in France, many wetlands were dried out for sanitary or agricultural objectives, like the Marais Poitevin since the beginning of the 18th century, and it would be difficult to come back to the pristine conditions (Godet and Thomas, 2013).

Theoretically, the separation of the pre-influence and influenced periods should match the start of the influence on the basin. In practice, in the case of dam commissioning, as illustrated for the Aube dam (Figure 4), the change on the observed flow time series is abrupt and so the separation is easily identifiable. In other cases, like withdrawals or small farm dams, which may gradually appear in the basin and evolve over time, or in the case of gradual land use and land cover change, the date of implementation of all the influences is rarely accessible and there is generally no abrupt change on the observed flow time series, which complicates the separation dating.

[Figure 4 near here]

In naturalization studies, change-point detection tests (Andréassian et al., 2003; Hubert et al., 1989) are mainly used to distinguish the pre-influence and influenced periods (Bao et al., 2012; Gu et al., 2017; Guo et al., 2014; Hu et al., 2015; Jiang et al., 2011; Wang et al., 2009; Wang et al., 2013; Zhan et al., 2013). The identified break point most often corresponds to a statistically significant change in the observed flow time series, but this break can have an anthropogenic origin (dam, urbanization, etc.), be natural (natural change in the morphology of the river) or stem from climatic variability or a

data problem (change in data measurement devices, etc.). With this method, it is important to underline that anthropogenic disturbances can still exist during the period defined as pre-influence (Jiang et al., 2011) and that these influences can therefore impact the naturalized flows obtained.

4 Methods to naturalize streamflows

4.1 Overview on naturalization methods

We have identified six main naturalization methods in the literature: (1) the reconstitution, (2) water balance, (3) routing, (4) the extension, (5) the paired catchment and (6) regionalization (or neighbourhood) methods. These methods differ mainly by their input data and the underlying models used.

The reconstitution, extension and neighbourhood methods are based on a hydrological model simulating a naturalized streamflow with an estimated set of parameters reflecting the natural hydrological conditions. In reconstitution, failing to have past observations, information on the observed influenced streamflow and the anthropogenic influences are exploited to indirectly estimate the set of parameters representing natural hydrological conditions. In extension, past observations of natural flows on the target catchment are used to estimate the set of parameters reflecting the natural hydrological conditions. In neighbourhood, the observations that exist on neighbouring basins are exploited to estimate the set of parameters. Although these methods use a hydrological model, they rely on different assumptions and data to obtain the model parameter set.

Figure 5 provides a decision tree for the use of the various methods. The starting key question is generally the availability of input data on influences, followed by the availability of data from pre- or post-influenced period, or of regional data. The use of these different data raises hypotheses for the application of the methods. Figure 5 shows

which methods can be applied based on the available data. If all the data are available, all the methods can be applied. If no data is available, one may end up to the conclusion that no flow naturalization is possible (black ellipse on the graph). In that case, one may appeal to hydrological models implemented at the global scale, which do not require local or regional data. However, the reliability of these models at the local scale remains limited. That is why this option will not be further discussed in this review.

In the following sections, an explanation of the main hypotheses raised by the naturalization methods is provided in order to identify their application conditions. Figure 6 shows which methods are used in our articles database.

[Figure 5 near here]

[Figure 6 near here]

4.2 Methods using data on influences

4.2.1 Water Balance

The Water Balance method consists in decomposing flow into a natural part and an influence part at the scale of the influenced system (typically an artificial reservoir), by removing the volume variation in the river induced by the source of influence, ΔV , during the time interval Δt , from the influenced observed flow, Q_{observed} , to obtain the naturalized flow, $Q_{\text{naturalized}}$ (equation 1). The system studied can be a river reach where there is a water withdrawal or release, or a reach downstream of an influence. By convention, in the case of a water discharge, ΔV will be negative. In the case of a water withdrawal, ΔV will be positive. This method is generally applied at a gauging station located downstream of the influences in the river, although in principle it is also applicable to a fictitious point where flow data obtained through regionalization methods are available. Hydraulic propagation between the influence and the station can

have an impact on the computation of the naturalized streamflow. The ΔV computed at a moment t will not have an immediate impact on the observed streamflow at the downstream station, but will have an impact at the time $t + \Delta p$, where Δp corresponds to the propagation time. If the propagation time is much lower than the study time step, then the propagation effect can be ignored. Otherwise, it is advisable to use a propagation model. The choice of time step will define the hydrological processes to be taken into account and their influences to be considered.

$$Q_{\text{naturalized}} = Q_{\text{observed}} + \frac{\Delta V}{\Delta t} \quad (1)$$

The Water Balance method is the most widely used in the studies. Table 2 lists the studies using this method. It appears that this method, mainly constrained by the availability of data, is mostly applied to a daily time step over periods ranging from a few months to several decades. However, if the method is applied over a long period of time, there may be disparities in the quality of the naturalized flows obtained over the entire period. This may be due to the evolution of the quality of the measured flows (Littlewood and Marsh, 1996). In the studies taking into account the influence of dams, it appears that, for the most part, only the impact of dam regulation operations is taken into account (Assani et al., 1999; Kim and Wurbs, 2011; Naik and Jay, 2005; Page et al., 2005; Peters and Prowse, 2001; Yuan et al., 2017). Some studies also take into account evaporation from the reservoirs (Fantin-Cruz et al., 2015; Tongal et al., 2017) and precipitation falling on the reservoirs (Gu et al., 2017), but no studies seem to take into account the underground exchanges induced by the reservoir. For studies taking into account withdrawals, it appears that it is the volume of water consumed that is taken into account in naturalization and not the volume of water withdrawn (Davtalab et al., 2017; Littlewood and Marsh, 1996; Wallace and Pavvloski, 1988; Wurbs, 2006).

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

[Table 2 near here]

4.2.2 Reconstitution method

The Reconstitution method is based on the exploitation of the influenced observed streamflow and the information available on influences during the influenced period and on the use of hydrological models taking anthropogenic influences explicitly into account. As illustrated in Figure 7, the Reconstitution method consists first in calibrating the hydrological model on the influenced observed streamflow taking into account the anthropogenic influences. Then the set of parameters obtained is used to simulate a naturalized streamflow without taking into account the anthropogenic influences. In cases where the signal of influence in the observed flow is predominant over the natural signal, it is important to ensure that the calibrated parameter set is able to reflect the natural catchment behaviour. Step 1 is common to all studies applying the Reconstitution method, with more or less complex calibration methods depending on the model used and the influence considered. There are some variants of step 2, for the estimation of the naturalized streamflow. One variant corresponds to the case where the model output considered is the time series of the influences. The second step then corresponds to the application of the Water Balance method where the volume variation of the influences is added to the observed streamflow (Dunn and Ferrier, 1999; Maheshwari et al., 1995; Wurbs, 2006). Another more hydraulics-oriented variant, relevant for the semi-distributed and distributed models with an in-stream flow routing, consists at step 2 of propagating the upstream natural streamflow if available (Kim et al., 2012). In the case of an impact of land use and cover change, in the second step the parameter and input corresponding to influenced land use are changed to correspond to the pre-influenced state (Nobert and Jeremiah, 2012; Shi et al., 2013; Yin et al., 2017; Zhang et al., 2016).

[Figure 7 near here]

Since studies are often not very explicit in terms of the model calibration with anthropogenic influences, it is difficult to clearly identify which studies apply Reconstitution methods. Table 3 presents a synthesis of the models used in studies applying the Reconstitution method, the time step of the naturalized flow, the influence taken into account as input in the studies and the simulated flow. The impact of dams and reservoirs are often the main issue in Reconstitution studies. This can be explained by the fact that their management can be simulated. The second most studied influence is land use and land cover changes, which are taken into account by physically based hydrological models such as SWAT (see Table 3). The semi-distributed spatial resolution is adopted by most studies. In the case of large catchments, the influences can be localized in space and attenuation of the influences along the river are more accurately considered.

[Table 3 near here]

4.2.3 Comparison

The Reconstitution and Water Balance methods are based on the hypothesis that by knowing the impacts of the various influences on the observed flow, it is possible to have a naturalized flow free from these influences. As no study has made a comparison between the Reconstitution method and the Water Balance method, it is not possible to know which one is the most suitable. However, here are a few elements that differentiate these methods and may guide their choice:

- **Data availability.** The Water Balance method requires time series data on the entire period to naturalize. The advantage of the Reconstitution method is that once the parameter set has been obtained, it is theoretically applicable to other periods.

- **Setting up the model.** The Water Balance method seems to be easier to apply than the Reconstitution method which requires the implementation of a hydrological model on the basin. However, the use of a hydrological model can facilitate several steps such as estimating the volumes of influences that can be incorporated into the model or estimating travel time. It is difficult to say a priori which method will be easier to apply. This depends primarily on the catchment area and the influences considered.

4.3 Methods using observation from the pre-influenced period

4.3.1 Extension method

The Extension method is based on the exploitation of observed data of the target catchment from the pre-influence period and on the use of a hydrological model able to simulate the natural streamflow of the target catchment. The required data for the pre-influence period are at least the natural observed streamflow and the input data required by the model. On the influenced period, the input data required to use the model are necessary. The Extension method consists in calibrating the hydrological model on the natural observed streamflow of the pre-influence period and then in using the set of parameters obtained on the influenced period to simulate a naturalized streamflow (Figure 8).

[Figure 8 near here]

Table 4 presents an overview of the studies applying the Extension method and the hydrological models used. The common point of the models is their ability to simulate a natural flow. The models used in these studies show differences in terms of the type and level of complexity. Some studies used empirical models which establish a purely mathematical relationship between natural flow and weather variables over the pre-

influence period. Wen (2009) established a multi-regression model with the precipitation and the maximum temperature data at the monthly time step; Jiang et al. (2011) built a multi-regression model with the precipitation and the potential evapotranspiration; Ahn and Merwade (2014) also take into account the drainage area. Other studies applied more complex models such as conceptual hydrological models (Chang et al., 2015; Guo et al., 2014; Wang et al., 2013; Zhan et al., 2013), or physical models (Bao et al., 2012; Chang, Zhang, et al., 2015; Jiang et al., 2011; Ma et al., 2010; Wang et al., 2010). Jiang et al. (2011) and Chang et al. (2015), who used models of different types, showed that the results obtained with the two models are comparable. [Table 4 near here]

4.3.2 Paired catchment method

This method is explained here but also partly belongs to the family of methods exploiting regional information (see Figure 5). This method is based on the implementation of a statistical flow-rate relationship between the target station to naturalize and natural donor stations over the pre-influence period. The natural donor catchment is generally a catchment that is spatially close to (but not nested in) the target catchment, with similar size. There is no hydrological model involved in this method. This approach is not limited to cases of experimental basins to evaluate land use and land cover changes (Brown et al., 2005). To naturalize the flows of La Grande Rivière in Canada, Hernández-Henríquez et al. (2010) established a flow-rate relation over the pre-influence period by applying a variant of the Hirsh MOVE I method (Hirsch, 1982). On the Lena River in the Arctic, influenced by a reservoir dam, Ye et al. (2003) established a regression on the pre-influence period between a station downstream of the dam and five natural upstream uninfluenced stations. Smakhtin, (1999) proposed the same principle for catchments in South Africa. In China, Huo et al. (2008) established

1
2
3 585 flow-rate relationships, including climatic variables (precipitation and temperature),
4
5 586 between the uninfluenced upstream and downstream stations. The relation proposed by
6
7 587 Huo et al. (2008) differs from the conventional paired basin methods (Andréassian et
8
9 588 al., 2012) because they also use climatic information. Other variants exploiting the
10
11 589 paired catchment relationship can be applied without parameter calibration. The
12
13 590 drainage area ratio method (Hirsch, 1979) and different variants, requiring only an
14
15 591 access to the catchment's area value, are applied in many naturalization studies (Kim,
16
17 592 2015; Rahman and Bowling, 2018; Wurbs, 2006). In any case, these approaches make
18
19 593 the strong assumption that the departure of observed influenced flows from the
20
21 594 relationship with paired catchment flow would be due to the influence only, which may
22
23 595 not be always the case.
24
25
26
27
28
29

30 596 4.3.3 Comparison

31
32 597 Extension and Paired catchment methods are based on the hypothesis that relations
33
34 598 established over the pre-influence period are stationary and remain valid over the
35
36 599 influenced period. For the Extension method, running a hydrological model under
37
38 600 climatic conditions that are different for the calibration period can generate uncertainties
39
40 601 (Coron et al., 2012). The source of these uncertainties can be partly explained by the
41
42 602 fact that, in the models, several physical parameters (soil, vegetation, etc.) are related to
43
44 603 climatic conditions. The calibration of the model creates an interaction between the
45
46 604 parameters and the climatic characteristics of the calibration period. The robustness of
47
48 605 the model is usually tested on the pre-influence period by calibrating the model on a
49
50 606 sub-period and validating it on another one (Bao et al., 2012; Guo et al., 2014; Jiang et
51
52 607 al., 2011; Wang et al., 2010; Wang et al., 2013). For the Paired Catchment method, the
53
54 608 limitation is the climatic gradient between the basins, which could lead to the two basins
55
56 609 evolving differently. On the pre-influenced period, similar climatic conditions,
57
58
59
60

landforms, soils, vegetation and hydrological processes between the basins can reduce the uncertainties associated with the natural evolution state of the target catchment (Hernández-Henríquez et al., 2010). These two methods can be distinguished by their level of complexity. The Extension method requires a rainfall-runoff model and meteorological data as input, whereas the paired basins method is simpler because it consists in establishing a relationship between two neighbouring catchments and only requires streamflow measurements. Despite these differences in complexity, Andréassian et al. (2012) showed that the paired basin methods can give better performance than the use of a rainfall-runoff model when the density of gauging stations is quite high.

4.4 Methods using regional information

4.4.1 Routing modelling

Routing models can propagate the observed streamflow from upstream to downstream. In the case where the upstream recorded streamflow is uninfluenced, it can be propagated by a hydraulic model (or other simpler propagation or statistical methods) to obtain a naturalized downstream streamflow. Table 5 presents studies applying Routing modelling methods to naturalize. The influences taken into account in these studies directly affect flows due to infrastructures built in the river. In these studies, the hydraulic models used assume that the river bed topography is still the same without the dams or levees. The implementation of Routing modelling methods is often time consuming and requires many data to calibrate the hydraulic model (Shiklomanov and Lammers, 2009). This is especially the case when important transmission losses occur and must be accounted for (Hughes, 2019; Pacheco-Guerrero et al., 2017). When the upstream flows are influenced, the flow can

be naturalized and then propagated using a hydraulic model (Peters and Prowse, 2001). Another variant consists in using a hydraulic model that explicitly takes into account the different structures (dam, weir, levee, etc.) that may alter streamflow. The model is first calibrated on the flow conditions of the influenced period. Then, to obtain a naturalized flow, the various obstacles are removed from the propagation model (Ahn et al., 2006; Peters et al., 2006; Wyrick et al., 2009). Wu et al. (2015) assume that the hydraulic propagation has no impact and sum the natural upstream flows to naturalize.

[Table 5 near here]

4.4.2 Regionalization

Regionalization methods exploit the similarity between catchments to estimate streamflow. Although mainly used for ungauged or poorly gauged basins, their application in naturalization studies is an interesting option for several reasons. First, the Water Balance and Reconstitution methods require good knowledge and an access to the data used to characterize the influences, whereas regionalization methods are usable on a basin with limited data (Hernández-Henríquez et al., 2010; Ye et al., 2003). Secondly, the principle of the Extension methods is based on the temporal transposability of streamflow. Regionalisation methods can be viewed as a variant based on spatial transposability.

Regionalization of the hydrological regimes and flow duration curves. In the case where only the flow characteristics of the natural basin's behaviour are investigated and not complete time series are sought, the regionalization of a hydrological regime can be used. For example, in Switzerland, the natural monthly regimes of Alpine basins have been classified into six groups according to the average altitude of the catchments and the proportion of their glacier-covered area. Therefore, due to the physical characteristics of the influenced catchments and an estimate of the average annual flow,

Weingartner and Aschwanden (1994) estimated their natural monthly regime, with an uncertainty ranging from 10 to 20%. In Spanish basins, Fernández et al. (2012) estimated the naturalized monthly flow with a hydrological model at the influenced stations. Then, to estimate the naturalized regime at a daily time step, they calculated daily distribution coefficients on neighbouring natural stations. These distribution coefficients were then applied to the naturalized monthly flows that had a naturalized daily regime. Here, since the focus is on methods for obtaining naturalized flow time series, the methods of this subsection will not be further discussed. However, they remain used operationally in many countries, in cases where only synthetic streamflow descriptors are needed.

Neighbourhood method. The Neighbourhood method consists in estimating the hydrological model parameters on natural neighbouring basins. The selection criteria for natural neighbouring basins are related to geographical distance or the physical characteristics of the basins (Hrachowitz et al., 2013). This method is not currently used on gauged stations in naturalization studies. However, like the Extension and Reconstitution methods it uses a hydrological model with an alternative approach to estimate the model parameter. It may be of particular interest when there are no existing natural flow data on the pre-influence period nor on the influences themselves during the influenced period.

4.4.3 Comparison

In this family, the Routing method seems to be a priori the method giving the best estimate of natural flow since it directly exploits measurements of natural flows upstream of the basins. However, in the case where the intermediate basin has a significant influence on the flow, it may be necessary to also use a hydrological model to simulate the contribution of the intermediate flow (Wyrick et al., 2009). It is also a

complex method to use in the case of large transmission losses between the upstream and downstream station (e.g. in arid regions) (Schreiner-McGraw and Vivoni, 2018). The Paired catchment method can also be applied in cases where upstream uninfluenced flow measurements are available. What differentiates it from the Routing method is that it is based on a flow rate relationship that can indirectly take into account the inflows from the intermediate basin. Like the Paired Catchment method, the Neighbourhood method also exploits information from basins with a natural regime. The significant difference between these two methods is that Neighbourhood is primarily aimed at transferring parameter sets from a natural catchment to the influenced catchment. The assumptions involved in these methods, and their strengths and weaknesses, have been the topic of several studies within the framework of the IAHS decade on Prediction in Ungauged Basins (Hrachowitz et al., 2013; Sivapalan et al., 2003).

5 Discussion

5.1 Defining naturalized streamflow

When discussing the definition of a natural regime, we showed that there is no consensus on what a naturalized flow and the natural state of a basin should exactly refer to. This impacts the choice of the reference period in the various studies. In practice, the definition of naturalized streamflow should be a compromise between:

- Our knowledge of the interactions between human activities and the water cycle and the limit of the definition to be adopted. Since the water cycle is linked to several other environmental cycles (energy, chemistry, sedimentation, etc.), this raises the question of the natural state of these other environmental cycles and their interactions with the water cycle. Typically, the issue of defining a natural reference in the climate or ecological domains has been discussed and results

from a compromise between knowledge, data availability and objectives in the use of the reference (Brázdil et al., 2005; Davis, 2015; Gatti et al., 2015; Roubicek, 2010).

- A definition not too restrictive to be applicable to a large number of case studies. Ideally, the reference conditions should correspond to minimally disturbed conditions (Stoddard et al., 2006), i.e. conditions where there is no significant anthropogenic disturbance. In practice this would be very constraining because it is difficult nowadays to access data from basins that are not disturbed by human activities. In Europe, there are no data on the natural state of a catchment because the continent has long been densely populated, and the landscapes and land use have been modified by human presence (Stahl et al., 2010). Moreover, in some studies, only the naturalization of major influences is desired. In some cases, the naturalized flow can be obtained by removing a single influence to quantify the role of the influence in the observed flow.

The summary of previous definitions we gave in section 3.1 may meet this compromise. This is actually a key issue when establishing hydrometric reference networks. Since they should be representative of natural flow conditions, the question of the criteria to be met in order to consider the corresponding catchments as natural references is raised (Whitfield et al., 2012). It appears that the definition of conditions vary between national networks. In Canada, where there are many catchments in pristine conditions, criteria are more rigorous whereas the impact of influences on natural flow regimes is visible across much of the UK rivers for instance.

The current perspectives would be to define the naturalized flow as corresponding to a more or less natural state of the basin and to express which influences and associated

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

impacts are considered in each study. Another perspective is to use a more comprehensive approach, consistent with the definition of naturalized flow chosen, to identify the pre-influence period. In the reviewed studies applying naturalization methods, the methods to identify the reference period are currently limited to change-point detection tests, which raise several issues concerning the origin of the change-point. It would also be interesting to have methods to detect a certain level of influence on the basin.

Although defining terms appears essential to understand and compare studies, the definition process can lead to a reflection on the role of the influences in the methods and the hypotheses raised. For example, in the case of the Extension method, setting it at a pre-influence period may imply to account for change in land use to obtain the naturalized flow.

5.2 Choice of naturalization methods

By comparing the characteristics of the studies with the choice of the naturalization methods applied, it appears that the same methods are applied on basins with different areas, from the basin scale (100 - 10,000 km²) to the regional scale (100,000 - 1,000,000 km²), and with different influences. Methodological aspects of the studies such as the time step and the length of the available time series to naturalize do not seem to play a major role in the choice. This raises the question of the criteria that can motivate authors to choose one method over another.

5.2.1 Data availability

From a practical point of view, data availability is the first selection criterion (Table 6), which is also reflected in the decision tree illustrated in Figure 5. Thus, the Water

Balance and Reconstitution methods use data on influences. The Paired Catchment and Neighbourhood methods need data on non-influenced catchments. The Routing modelling method requires a natural upstream flow to propagate it downstream. The Extension and Paired Catchment methods need data on the past observed natural streamflow. It is clear that several of these methods are relatively similar and that they differ only in the tools used. In this section, we will discuss the aspects that can influence the choice of the applied methods.

[Table 6 near here]

5.2.2 *Distance between the source of influence and the gauging station*

Distance is taken into account by the Water Balance and the Routing modelling methods with the propagation time, and by the Reconstitution methods, which take it into account according to the structure of the model used and the parameters. For the transfer modelling family methods, in the case where intermediate hydrological phenomena such as runoff or river-groundwater exchange have a potential impact on the routed flow, a hydrological model should be used to simulate them.

5.2.3 *Type of influences*

In the transfer modelling family, Routing modelling methods are used only to take into account influences that directly impact the flow, as is the case for dams and withdrawals. For the Water Balance method, all the influences and their associated impact on the hydrological cycle could theoretically be taken into account via the ΔV . In practice, indirect impacts on river streamflow are easier to take into account with a hydrological model family method.

In the hydrological method family, theoretically the entire impact on the hydrological cycle could be considered. In practice, the type of influences present in the basin seem

to impact the choice of method. In studies that take into account land use and land cover changes in their naturalization process, only Extension and Reconstitution methods are used. The Extension method is calibrated on the basin conditions before the evolution of the cover. The Reconstitution method makes it possible to take the land cover directly into account during the calibration and then modify it. As land use changes indirectly modify the flow, it is easier to take these interactions into account with a hydrological model. For the Regionalization methods, this would require a neighbouring basin with a land cover similar to the influenced basin in its natural state. These methods could be applied on small experimental Paired Catchments (Brown et al., 2005) but do not seem to be applicable to large catchments.

Regionalization methods are applied on catchments which are strongly influenced by dams and other influences. This can be explained by the fact that it is now difficult to access databases with completely uninfluenced catchments. Weingartner and Aschwanden (1994) explain that Regionalization methods are easier to apply in cases where the hydrological conditions encountered are very complex, as in multi-influenced basins. The complexity of the influences and their impact on the catchment could be a limit of the Reconstitution method. For example, in the case where irrigation return flow is taken into account, the difficulty in quantifying them (Dewandel et al., 2008) may lead to eliminating the choice of Reconstitution method.

5.3 Operational implementation of naturalization methods: the case study on the Rhône basin (France)

From theory to practice, it is always useful to see the way practitioners implement methods proposed in the scientific literature. We describe a case study from France. In France, one of the objectives of the Law on Water and Aquatic Environments (LEMA in French) of 30 December 2006 is to restore the balance between water supply and

1
2
3 804 demand. Consequently, studies of “withdrawable” water volumes (i.e. water available
4
5 805 for withdraw/human-use) were carried out at the catchment scale in order to determine
6
7 806 the quantitative state of water resources and then to propose a preservation strategy of
8
9 807 the existing balance or reduce the deficit. These studies include several phases,
10
11 808 including an important phase on the identification and quantification of anthropogenic
12
13 809 influences and a phase on the estimation of the water resource using naturalization
14
15 810 methods. The reports produced at the end of these studies are a useful source of
16
17 811 information on the application of naturalization methods in operational contexts.
18
19 812 Because low-flow periods are of particular concern, naturalized flows are preferentially
20
21 813 obtained at a daily scale to calculate drought indicators.
22
23
24
25

26
27 814 Among the many reports available, we made a selection over 20 basins in the the
28
29 815 Rhône-Mediterranean Water Agency district (Appendix 1, figure 9). These reports were
30
31 816 generally produced by consulting firms and were chosen here in order to have the
32
33 817 widest possible panorama (Appendix 1, Table 7). Naturalization methods were applied
34
35 818 on sub-basins from a few dozen to several hundreds of square kilometres.
36
37
38

39 819 With regard to the choice of methods, the most widely used methods are the Water
40
41 820 Balance and the Reconstitution methods. The choice of the methods is not clearly
42
43 821 justified but can be explained by several factors. First, all influences in the basin are
44
45 822 taken into account. This excludes the Extension method where it is almost impossible to
46
47 823 have a period when there is no withdrawal, and the Regionalization method where it is
48
49 824 also complicated to have neighbouring basins with no withdrawals. However, a variant
50
51 825 of the Neighbourhood method used in an operational context consists in calibrating the
52
53 826 hydrological model on the naturalized flow of the upstream influenced sub-basins, and
54
55 827 then to use the set of parameters obtained on the influenced downstream basin (CEREG
56
57 828 Ingénierie, 2011). Moreover, in these studies considerable preliminary work is
58
59
60

undertaken to identify and quantify the anthropogenic influences present in the basins. This facilitates the application of the Water Balance and Reconstitution methods. The synthesis of these reports also highlights the implementation of hybrid naturalization methods to address data gaps. Given that hydrological indicators are calculated on the naturalized flow series, the times series must be long enough. These hybrid versions are presented as a solution in cases where the observational data on influence and streamflow are too short. One version is to first naturalize the streamflow with the Water Balance method and then to apply the Extension method in calibrating the hydrological model on these naturalized flows. Inversely, the influenced flow time series can be extended with a hydrological model and then be naturalized with the Water Balance method. It should be noted that each addition of steps in the naturalization process is a potential source of uncertainty.

In the terms of reference of these studies, authors were requested to clarify the limits and uncertainties related to the naturalization process. The level of reflection is very heterogeneous depending on the studies. It appears that most of the authors were able to identify sources of uncertainty. The main sources of uncertainties cited were the streamflow data, the data on the influence and the climatic data used as model input and model calibration. No study has clearly quantified the global uncertainty of the naturalized streamflow obtained. In the Les Gardons catchment, it was highlighted that a 7% error on the naturalized flow had an impact on the study conclusions.

5.4 Level of confidence associated with naturalized streamflow

The previous section on the operational application of naturalization methods in France showed that there is a request on how to assign a level of confidence to naturalized flow. **Because naturalized streamflow is used as a reference for many applications (as**

discussed in section 1.2), it is important to quantify the associated uncertainties in order to make robust decisions (Refsgaard et al., 2007). The error associated with naturalized flows is not directly quantifiable because there is no observation of natural flows over the influenced period. The estimation of the confidence in the methods can therefore only be done indirectly. Among the articles analysed, there does not currently seem to be a methodology to evaluate the naturalization process. In this part, we discuss how to indirectly estimate the confidence in results.

5.4.1 Uncertainties in data

To estimate which method is the most appropriate, a first reflection can be carried out on the quality of the input data (McMillan et al., 2012). As shown in part 5.2, naturalization methods use different input data which can generate different levels of uncertainty. The main categories of input data are:

- Streamflow time series. We distinguish the streamflow time series corresponding to an observed natural flow and the time series corresponding to an influenced observed flow. The main uncertainties come from the measurement system in place, the operational conditions and the post-processing step to estimate the flow (e.g. the stage-discharge relationship). Usually a post-processing step corrects the occasional errors. In case of a direct impact, the influenced series can be distinguished from the natural series by the presence of sudden changes in the time series. This implies a more thorough post-treatment to distinguish changes due to measurement errors from those due to anthropogenic influences. Ideally, the measurement system should not change in time. Naik and Jay (2005) pointed out that flow errors can be much more important at the beginning of the period of record. When choosing a method

from the hydrological modelling family, questions should be raised on the confidence placed in the natural flow in the past and the observed flow in the present. When the observed data appear uncertain in both cases, it may be beneficial to use the Neighbouring basin method.

- Climatic time series. The main climatic variables used in the studies are precipitation and evapotranspiration. Precipitation estimation at the catchment scale is carried out using interpolation methods of local rainfall measurements. The measurement system put in place must therefore be adapted to the spatial and temporal variability of rainfall events in the basin (Lebecherel, 2015). Since actual evapotranspiration is not measurable at the catchment scale, point evapotranspiration is used most of the time in the studies. However, this potential evapotranspiration corresponds to a model output (Oudin et al., 2005), and therefore includes uncertainties. Precipitation can also be estimated by radar data. In contrast to the raingauge, it is an indirect measurement which is also uncertain.
- Volume time series of human influences. Since the influence measurements are not always available, different techniques and assumptions are used to estimate influence time series. For example, in the naturalization studies examining agricultural withdrawals, the volume time series are estimated based on data reported by farmers (Irwin et al., 1975) or models based on cropping patterns, irrigation water needs and irrigation efficiency (Davtalab et al., 2017; Wallace and Pavvloski, 1988). Uncertainties associated with these processes seem not to be quantified, but it can be assumed that these uncertainties could be greater than for the other input data. It is also difficult in naturalization studies to get sufficient data to characterize all the influences at play on the catchment. Often

one has data on the major influences (typically dams, abstractions in rivers), but it is harder to quantify the impact of other influences on flows (land use change, groundwater abstractions). This may leave a level of uncertainty difficult to remove in naturalized flow estimates.

A first perspective would be to assess the impact of the quality of these data on the naturalized flow obtained in a sensitivity study (Devak and Dhanya, 2017). Model parameters are sensitive to the errors contained in input data. Several studies have already shown the sensitivity of the models to climate variables (Andréassian et al., 2004; Oudin et al., 2006). For example, Andréassian et al. (2004) showed that having a better estimate of potential evapotranspiration does not give better results. In the case of withdrawable water volume studies in France, there are often strong uncertainties on the influence data, especially on irrigation data. It would therefore have been interesting to see the sensitivity of the calculated hydrological indicators to influence data.

5.4.2 Uncertainties in model structure

Model structures can be a source of uncertainties if they are not in line with reality (Pechlivanidis et al., 2011). The model is a simplification of reality and it may be that not all processes are represented. In the Reconstitution method, where the model takes anthropogenic influences into account in the model, it is important to ensure that the structure of the model is adapted to represent the potential impacts of the human activities on the different components of the hydrological cycle. The structure of the Water Balance method can be attractive because of its simplicity, but, during low-flow periods, errors can lead to obtaining abnormally low or even negative flow rates (Agosta, 2007; Littlewood and Marsh, 1996). With the Reconstitution method, the simulated streamflow can be extremely low, which raises questions about its

interpretability, especially in intermittent rivers (De Girolamo et al., 2015).

5.4.3 Validation of the method's hypothesis

Each naturalization method is based on different assumptions (see section 4). One key issue in all methods is the uncertainty linked to the transfer of information in space and time. This aspect is however not so easy to quantify in the case of naturalization since no natural flow observation is available on the influenced period and standard split sample or proxy-basin approaches (Klemes, 1986) cannot be directly applied.

To assess if the method and tools used are appropriate and thus reinforce our confidence in the results, several methods applied in the literature can be used.

In the case of the hydrological modelling family, methods are based on the transferability of the parameter set. In fact, there is no single set of parameters that can perfectly reproduce the uninfluenced flow (Beven, 2000). The problem in naturalization is to know which method makes it possible to transfer the parameter sets with the least possible uncertainty. With a temporal transposition, robustness can be assessed using the split-sample test (Coron et al., 2012; Klemes, 1986). This method consists of evaluating the performance obtained over a subperiod different from the calibration period. In the case of a spatial-proximity-transposition, robustness can be assessed using the hydrometrical desert method (Lebecherel et al., 2016). For the Reconstitution method, the uncertainty obtained at calibration on the simulated influenced streamflow can be transferred to the simulated naturalized streamflow.

6 Conclusion

Human activities can directly impact the observed flow or several components of the hydrological cycle. These human influences can have an impact at the catchment,

1
2
3 949 regional or global levels. Consequently, most of the observed flows are influenced. To
4
5 950 have a reference to the natural regime of influenced rivers, an increasing number of
6
7 951 studies apply different naturalization methods. However, no state of the art on the topic
8
9 952 has yet been made. The inventory of the terms to designate a naturalized streamflow
10
11 953 shows that there are several definitions considering different human influences. We
12
13 954 believe that it would currently be too restrictive to propose a single definition of the
14
15 955 naturalized flow. We advise that studies propose a clear definition of the influences and
16
17 956 impacts considered by the naturalization process.
18
19
20
21

22 957 The main naturalization methods were presented and a classification into three families
23
24 958 based on the information they used. Although data availability appears to be the main
25
26 959 constraint in the choice of methods to be applied, other criteria play an important role.
27
28 960 When intermediate phenomena such as runoff impact the water flow from upstream to
29
30 961 downstream, a method from the hydrological modelling family will be more
31
32 962 appropriate. The influences and their impacts considered in the naturalization process
33
34 963 also lead to questioning the choice of methods and tools used.
35
36
37
38

39 964 The example of the application of operational methods shows that the most commonly
40
41 965 applied methods for estimating water resources are the Water Balance and
42
43 966 Reconstitution methods. This choice is explained by the fact that the authors' goal is to
44
45 967 take into account all the influences of the basins and by the difficulty of having access
46
47 968 at a completely natural reference over an earlier period or a neighbouring basin. The
48
49 969 development of hybrid methods is a consequence of the difficulty of having both an
50
51 970 estimate of the natural flow without any influence and a sufficiently long series to
52
53 971 calculate robust hydrological indicators.
54
55
56
57
58
59
60

In these studies of withdrawable water volumes, the uncertainties associated with the naturalization procedure were investigated. It appeared that the authors could identify most sources of uncertainty, but did not quantify the total uncertainty of the naturalized flow obtained. The difficulty in estimating the error associated with naturalized flows is that this can only be done indirectly because the naturalized flow is obtained over a period when there is no direct observation of the natural flow. A first perspective to estimate the confidence of the naturalized flow would be to assess their sensitivity to the input data, knowing that very often these inputs do not correspond to observations. A second perspective would be to indirectly assess the assumptions raised by the methods. Methodologies have been established in the literature to assess the ability of models to transfer a set of parameters spatially or temporally.

7 Acknowledgements

The authors thank the Office français de la biodiversité (OFB) for the financial support of the first author. The Land and Water team of CSIRO is thanked for supporting a research residency of the first author at Canberra, and The Bureau of Meteorology is acknowledged for making data available for this study. Rob Pipunic and Christopher Pickett-Heaps from Bureau of Meteorology are thanked for their comments prior to submission.

8 References

Acreman, M. C., & Dunbar, M. J. (2004). Defining environmental river flow requirements - a review. *Hydrology and Earth System Sciences*, 8(5), 861–876.
<https://doi.org/10.5194/hess-8-861-2004>

Acreman, M., Dunbar, M., Hannaford, J., Mountford, O., Wood, P., Holmes, N., Cowx, I., Noble, R., Extence, C., Aldrick, J., King, J., Black, A., & Crookall, D. (2008).

- 996 Developing environmental standards for abstractions from UK rivers to
 997 implement the EU Water Framework Directive / Développement de standards
 998 environnementaux sur les prélèvements d'eau en rivière au Royaume Uni pour
 999 la mise en œuvre de la directive cadre sur l'eau de l'Union Européenne.
 1000 *Hydrological Sciences Journal*, 53(6), 1105–1120.
 1001 <https://doi.org/10.1623/hysj.53.6.1105>
- 1002 AFB, & Ministère chargé de l'environnement. (2016a). *Débit contrôlé - Glossaire sur*
 1003 *l'eau* [Site de Eaufrance]. Glossaire Sur l'eau.
 1004 [http://www.glossaire.eaufrance.fr/fr/concept/d%C3%A9bit-](http://www.glossaire.eaufrance.fr/fr/concept/d%C3%A9bit-contr%C3%B4l%C3%A9)
 1005 [contr%C3%B4l%C3%A9](http://www.glossaire.eaufrance.fr/fr/concept/d%C3%A9bit-contr%C3%B4l%C3%A9)
- 1006 AFB, & Ministère chargé de l'environnement. (2016b). *Débit influencé - Glossaire sur*
 1007 *l'eau* [Site de Eaufrance]. Glossaire Sur l'eau.
 1008 <http://www.glossaire.eaufrance.fr/fr/concept/d%C3%A9bit-influenc%C3%A9>
- 1009 Agosta, C. (2007). *Naturalisation des débits et modélisation hydrologique sur des sous-*
 1010 *bassins versant de la Garonne à Lamagistère (in French)* (Mémoire de Master 2
 1011 Sciences de l'Univers, Environnement, Ecologie - Parcours Hydrologie-
 1012 hydrogéologie, Université Pierre et Marie Curie, Paris, Laboratoire National en
 1013 Hydraulique et Environnement, EDF Recherche et développement, Chatou. /; p.
 1014 51). EDF.
- 1015 Ahn, C., Johnston, D. M., Sparks, R. E., & White, D. C. (2006). Analysis of
 1016 Naturalization Alternatives for the Recovery of Moist-soil Plants in the
 1017 Floodplain of the Illinois River. *Hydrobiologia*, 565(1), 217–228.
- 1018 Ahn, K.-H., & Merwade, V. (2014). Quantifying the relative impact of climate and
 1019 human activities on streamflow. *Journal of Hydrology*, 515, 257–266.
 1020 <https://doi.org/10.1016/j.jhydrol.2014.04.062>

- 1021 Andréassian, V., Lerat, J., Le Moine, N., & Perrin, C. (2012). Neighbors : Nature's own
 1022 hydrological models. *Journal of Hydrology*, 414–415, 49–58.
 1023 <https://doi.org/10.1016/j.jhydrol.2011.10.007>
- 1024 Andréassian, V., Parent, E., & Michel, C. (2003). A distribution-free test to detect
 1025 gradual changes in watershed behavior. *Water Resources Research*, 39(9).
 1026 <https://doi.org/10.1029/2003WR002081>
- 1027 Andréassian, V., Perrin, C., & Michel, C. (2004). Impact of imperfect potential
 1028 evapotranspiration knowledge on the efficiency and parameters of watershed
 1029 models. *Journal of Hydrology*, 286(1–4), 19–35.
 1030 <https://doi.org/10.1016/j.jhydrol.2003.09.030>
- 1031 Artelia Eau et Environnement, & Maison régionale de l'Eau. (2012a). *Etudes*
 1032 *d'estimation des volumes prélevables globaux - Sous bassin versant de la Drôme*
 1033 *des collines (in french)* (p. 262). Agence de l'Eau Rhône Méditerranée et Corse.
 1034 [http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Drome-des-collines/EVP_Drome_collines_rapport_juillet2012.pdf)
 1035 [quantitative/EEVPG/Drome-des-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Drome-des-collines/EVP_Drome_collines_rapport_juillet2012.pdf)
 1036 [collines/EVP_Drome_collines_rapport_juillet2012.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Drome-des-collines/EVP_Drome_collines_rapport_juillet2012.pdf)
- 1037 Artelia Eau et Environnement, & Maison régionale de l'Eau. (2012b). *Etudes*
 1038 *d'estimation des volumes prélevables globaux - sous bassin versant de la*
 1039 *Galaure (in french)* (p. 218). Agence de l'Eau Rhône Méditerranée et Corse.
 1040 [http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Galaure/EVP_Galaure_rapport_juillet2012.pdf)
 1041 [quantitative/EEVPG/Galaure/EVP_Galaure_rapport_juillet2012.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Galaure/EVP_Galaure_rapport_juillet2012.pdf)
- 1042 Assani, A. A., Petit, F., & Mabilie, G. (1999). Analyse des débits de la Wache aux
 1043 barrages de Butgenbach et de Robertville (Ardenne belge). *Bulletin de La*
 1044 *Société Géographique de Liège*, 36, 17–30.

- 1
2
3 1045 Bao, Z., Zhang, J., Wang, G., Fu, G., He, R., Yan, X., Jin, J., Liu, Y., & Zhang, A.
4
5 1046 (2012). Attribution for decreasing streamflow of the Haihe River basin, northern
6
7 1047 China: Climate variability or human activities? *Journal of Hydrology*, 460–461,
8
9 1048 117–129. <https://doi.org/10.1016/j.jhydrol.2012.06.054>
11
12 1049 Beven, K. (2000). Uniqueness of place and process representations in hydrological
13
14 1050 modelling. *Hydrology and Earth System Sciences*, 4(2), 203–213.
15
16 1051 <https://doi.org/10.5194/hess-4-203-2000>
17
18 1052 Birkel, C., Soulsby, C., Ali, G., & Tetzlaff, D. (2014). Assessing the cumulative impacts
19
20 1053 of hydropower regulation on the flow characteristics of a large atlantic salmon
21
22 1054 river system. *River Research and Applications*, 30(4), 456–475.
23
24 1055 <https://doi.org/10.1002/rra.2656>
25
26 1056 Blanchon, D. (2005). Enjeux territoriaux et impacts environnementaux des transferts
27
28 1057 d'eau inter bassins en Afrique du Sud. *La Houille Blanche*, 5, 97–100.
29
30 1058 <https://doi.org/10.1051/lhb:200505010>
31
32 1059 Bosmans, J. H. C., van Beek, L. P. H., Sutanudjaja, E. H., & Bierkens, M. F. P. (2017).
33
34 1060 Hydrological impacts of global land cover change and human water use.
35
36 1061 *Hydrology and Earth System Sciences*, 21(11), 5603–5626.
37
38 1062 <https://doi.org/10.5194/hess-21-5603-2017>
39
40 1063 Botai, C., Botai, O. J., Muchuru, S., & Ngwana, I. (2015). Hydrometeorological
41
42 1064 Research in South Africa: A Review. *Water*, 7(4), 1580–1594.
43
44 1065 <https://doi.org/10.3390/w7041580>
45
46 1066 Bouleau, G., & Pont, D. (2015). Did you say reference conditions? Ecological and
47
48 1067 socio-economic perspectives on the European Water Framework Directive.
49
50 1068 *Environmental Science & Policy*, 47, 32–41.
51
52 1069 <https://doi.org/10.1016/j.envsci.2014.10.012f>
53
54
55
56
57
58
59
60

- 1070 Brázdil, R., Pfister, C., Wanner, H., Von Storch, H., & Luterbacher, J. (2005).
 1071 Historical Climatology In Europe – The State Of The Art. *Climatic Change*,
 1072 70(3), 363–430. <https://doi.org/10.1007/s10584-005-5924-1>
- 1073 BRL Ingénierie. (2011). *Détermination des volumes prélevables maximum sur le bassin*
 1074 *versant de la Cèze. Rapport de phase 2: Analyse de la ressource en eau.*
 1075 *Rapport final (in french).* (p. 89). Agence de l'Eau Rhône Méditerranée et
 1076 Corse. [http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Ceze/EVP_Ceze_rapport-phase2_mars2011.pdf)
 1077 [quantitative/EEVPG/Ceze/EVP_Ceze_rapport-phase2_mars2011.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Ceze/EVP_Ceze_rapport-phase2_mars2011.pdf)
- 1078 BRL Ingénierie. (2012). *Etudes d'estimation des volumes prélevables globaux - Sous*
 1079 *bassin versant de l'Yzeron - Phase 3: Impact des prélèvements et quantification*
 1080 *des ressources existantes (in french)* (p. 99). Agence de l'Eau Rhône
 1081 Méditerranée et Corse. [http://www.rhone-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Yseron/EVP_Yseron_Ph3_2012.pdf)
 1082 [mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Yseron/EVP_Yseron_Ph3_2012.pdf)
 1083 [quantitative/EEVPG/Yseron/EVP_Yseron_Ph3_2012.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Yseron/EVP_Yseron_Ph3_2012.pdf)
- 1084 BRL Ingénierie. (2013). *Etudes d'estimation des volumes prélevables globaux - Sous*
 1085 *bassin versant du Garon - Phase 1 - Rapport B (in french)* (p. 124). Agence de
 1086 l'Eau Rhône Méditerranée et Corse. [http://www.rhone-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Garon/EVP_garon_rapport_phase1B_janvier2013.pdf)
 1087 [mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Garon/EVP_garon_rapport_phase1B_janvier2013.pdf)
 1088 [quantitative/EEVPG/Garon/EVP_garon_rapport_phase1B_janvier2013.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Garon/EVP_garon_rapport_phase1B_janvier2013.pdf)
- 1089 BRL Ingénierie. (2014). *Etude de détermination des volumes prélevables - Sous bassin*
 1090 *versant des 3 rivières - Rapport de phase 3* (p. 146). Agence de l'Eau Rhône
 1091 Méditerranée et Corse. [http://www.rhone-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Cance/EVP_Cance_rapport_phase3_fevrier2014.pdf)
 1092 [mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Cance/EVP_Cance_rapport_phase3_fevrier2014.pdf)
 1093 [quantitative/EEVPG/Cance/EVP_Cance_rapport_phase3_fevrier2014.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Cance/EVP_Cance_rapport_phase3_fevrier2014.pdf)

- 1094 BRL Ingénierie. (2015). *Gestion quantitative de la ressource en eau du bassin versant*
 1095 *des Gardons - Etude des volumes prélevables (in french)* (p. 274). Agence de
 1096 l'Eau Rhône Méditerranée et Corse. [http://www.rhone-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Gardons/EVP_Gardons_Rapport_01122015.pdf)
 1097 [mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Gardons/EVP_Gardons_Rapport_01122015.pdf)
 1098 [quantitative/EEVPG/Gardons/EVP_Gardons_Rapport_01122015.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Gardons/EVP_Gardons_Rapport_01122015.pdf)
 1099 Brown, A. E., Zhang, L., McMahon, T. A., Western, A. W., & Vertessy, R. A. (2005).
 1100 A review of paired catchment studies for determining changes in water yield
 1101 resulting from alterations in vegetation. *Journal of Hydrology*, 310(1–4), 28–61.
 1102 <https://doi.org/10.1016/j.jhydrol.2004.12.010>
 1103 Bullock, A., Gustard, A., Irving, K., & Young, A. (1991). *Low Flow Estimation in*
 1104 *Artificially Influenced Catchments* (NRA R & D Project 257; p. 73). NRA,
 1105 Institute of Hydrology.
 1106 Bureau of Meteorology. (2012). *Australian Water Information Dictionary - Water*
 1107 *status: National Water Account 2012-2015 - line item 1.3 - regulated river*.
 1108 Australian Government - Bureau of Meteorology.
 1109 [http://www.bom.gov.au/water/awid/product-water-status-national-water-](http://www.bom.gov.au/water/awid/product-water-status-national-water-account-2012-2015.shtml)
 1110 [account-2012-2015.shtml](http://www.bom.gov.au/water/awid/product-water-status-national-water-account-2012-2015.shtml)
 1111 Burn, D. H., Hannaford, J., Hodgkins, G. A., Whitfield, P. H., Thorne, R., & Marsh, T.
 1112 (2012). Reference hydrologic networks II. Using reference hydrologic networks
 1113 to assess climate-driven changes in streamflow. *Hydrological Sciences Journal*,
 1114 57(8), 1580–1593. <https://doi.org/10.1080/02626667.2012.728705>
 1115 Cabinet Reilé. (2012). *Etude de détermination des volumes prélevables dans le sous-*
 1116 *bassin de la Savoureuse - Rapport d'étape phase III (in french)* (p. 86). Agence
 1117 de l'Eau Rhône Méditerranée et Corse. [http://www.rhone-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Gardons/EVP_Gardons_Rapport_01122015.pdf)
 1118 [mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Gardons/EVP_Gardons_Rapport_01122015.pdf)

- 1119 quantitative/EEVPG/Savoureuse/EVP_savoureuse_rapport_phase3_aout2012.pdf
- 1120 f
- 1121 CEREG Ingénierie. (2011). *Etudes d'estimation des volumes prélevables globaux - Sous*
- 1122 *bassin versant de l'Asse - Rapport définitif phase 3 (in french)* (No. M09067; p.
- 1123 77). Agence de l'Eau Rhône Méditerranée et Corse. [http://www.rhone-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Asse/EVP_Asse_rapport-phases3_oct2011.pdf)
- 1124 [mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Asse/EVP_Asse_rapport-phases3_oct2011.pdf)
- 1125 [quantitative/EEVPG/Asse/EVP_Asse_rapport-phases3_oct2011.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Asse/EVP_Asse_rapport-phases3_oct2011.pdf)
- 1126 CEREG Ingénierie, Idée Eaux, Lisode, Hydriad, & Brigitte Lambey. (2013). *Etudes*
- 1127 *d'estimation des volumes prélevables globaux - Sous bassin versant du Lez -*
- 1128 *Rapport de phase 3 (in french)* (p. 115). Agence de l'Eau Rhône Méditerranée et
- 1129 Corse. [http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/lez/EVP_lez_rapport_phase3_janvier2013.pdf)
- 1130 [quantitative/EEVPG/lez/EVP_lez_rapport_phase3_janvier2013.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/lez/EVP_lez_rapport_phase3_janvier2013.pdf)
- 1131 Chang, J., Wang, Y., Istanbuluoglu, E., Bai, T., Huang, Q., Yang, D., & Huang, S.
- 1132 (2015). Impact of climate change and human activities on runoff in the Weihe
- 1133 River Basin, China. *Quaternary International*, 380–381, 169–179.
- 1134 <https://doi.org/10.1016/j.quaint.2014.03.048>
- 1135 Chang, J., Zhang, H., Wang, Y., & Zhu, Y. (2015). Assessing the impact of climate
- 1136 variability and human activity to streamflow variation. *Hydrology and Earth*
- 1137 *System Sciences Discussions*, 12(6), 5251–5291. [https://doi.org/10.5194/hessd-](https://doi.org/10.5194/hessd-12-5251-2015)
- 1138 [12-5251-2015](https://doi.org/10.5194/hessd-12-5251-2015)
- 1139 Chase, T. N., Pielke Sr, R. A., Kittel, T. G. F., Nemani, R. R., & Running, S. W. (2000).
- 1140 Simulated impacts of historical land cover changes on global climate in northern
- 1141 winter. *Climate Dynamics*, 16(2–3), 93–105.
- 1142 <https://doi.org/10.1007/s003820050007>

- 1143 Constantz, J., & Essaid, H. (2007). Influence of groundwater pumping on streamflow
 1144 restoration following upstream dam removal. *Hydrological Processes*, 21(21),
 1145 2823–2834. Scopus. <https://doi.org/10.1002/hyp.6520>
- 1146 Cooper, R. (2004). *Natural flow estimates for streams in the Klamath basin*. (Report
 1147 SW 04 – 001; p. 245). State of Oregon, Water Resources Department.
- 1148 Coron, L., Andréassian, V., Perrin, C., Lerat, J., Vaze, J., Bourqui, M., & Hendrickx, F.
 1149 (2012). Crash testing hydrological models in contrasted climate conditions: An
 1150 experiment on 216 Australian catchments. *Water Resources Research*, 48(5).
 1151 Scopus. <https://doi.org/10.1029/2011WR011721>
- 1152 CSIRO. (2008). *Water availability in the Murray-Darling Basin. A report to the*
 1153 *Australian Government from the CSIRO Murray-Darling Basin Sustainable*
 1154 *Yields Project*. (p. 67). CSIRO.
 1155 <https://publications.csiro.au/rpr/download?pid=legacy:530&dsid=DS1>
- 1156 Davis, J. (2015). The 30-year “baseline” and the reality of climate change. *Weather*,
 1157 70(6), 190–190. <https://doi.org/10.1002/wea.2502>
- 1158 Davtalab, R., Mirchi, A., Khatami, S., Gyawali, R., Massah, A., Farajzadeh, M., &
 1159 Madani, K. (2017). Improving Continuous Hydrologic Modeling of Data-Poor
 1160 River Basins Using Hydrologic Engineering Center’s Hydrologic Modeling
 1161 System: Case Study of Karkheh River Basin. *Journal of Hydrologic*
 1162 *Engineering*, 22(8), 05017011. [https://doi.org/10.1061/\(ASCE\)HE.1943-](https://doi.org/10.1061/(ASCE)HE.1943-5584.0001525)
 1163 [5584.0001525](https://doi.org/10.1061/(ASCE)HE.1943-5584.0001525)
- 1164 De Girolamo, A. M., Lo Porto, A., Pappagallo, G., & Gallart, F. (2015). Assessing flow
 1165 regime alterations in a temporary river - The River Celone case study. *Journal of*
 1166 *Hydrology and Hydromechanics*, 63(3), 263–272. Scopus.
 1167 <https://doi.org/10.1515/johh-2015-0027>

- 1168 Degu, A. M., & Hossain, F. (2012). Investigating the mesoscale impact of artificial
 1169 reservoirs on frequency of rain during growing season: dams and rainfall
 1170 frequency. *Water Resources Research*, 48(5).
 1171 <https://doi.org/10.1029/2011WR010966>
- 1172 Département des Alpes-Maritimes. (2013). *Etude de détermination des volumes*
 1173 *prélevables - Bassin versant du Loup - Rapport de phase 3 (in french)* (p. 69).
 1174 Agence de l'Eau Rhône Méditerranée et Corse. [http://www.rhone-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Loup/EVP_Loup_rapport_phase3_nov2013.pdf)
 1175 [mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Loup/EVP_Loup_rapport_phase3_nov2013.pdf)
 1176 [quantitative/EEVPG/Loup/EVP_Loup_rapport_phase3_nov2013.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Loup/EVP_Loup_rapport_phase3_nov2013.pdf)
- 1177 Desconnets, J. C., Diallo, A., Traore, O., Chene, J. M., & Morin, G. (1998). Exemple
 1178 d'application du modèle CEQUEAU-ONU: Évaluation de l'impact des
 1179 aménagements sur les écoulements de la rivière Nakambé, Burkina Faso. *IAHS-*
 1180 *AISH Publication*, 252, 375–385.
- 1181 Devak, M., & Dhanya, C. T. (2017). Sensitivity analysis of hydrological models: review
 1182 and way forward. *Journal of Water and Climate Change*, 8(4), 557–575.
- 1183 Dewandel, B., Gandolfi, J.-M., De Condappa, D., & Ahmed, S. (2008). An efficient
 1184 methodology for estimating irrigation return flow coefficients of irrigated crops
 1185 at watershed and seasonal scale. *Hydrological Processes: An International*
 1186 *Journal*, 22(11), 1700–1712. <https://doi.org/10.1002/hyp.6738>
- 1187 Dong, N., Yu, Z., Yang, C., Yang, M., & Wenzhuo, W. (2019). Hydrological impact of
 1188 a reservoir network in the upper Gan River Basin, China. *Hydrological*
 1189 *Processes*, 33(12), 1709–1723. <https://doi.org/10.1002/hyp.13433>
- 1190 Dorchies, D., Thirel, G., Jay-Allemand, M., Chauveau, M., Dehay, F., Bourgin, P.-Y.,
 1191 Perrin, C., Jost, C., Rizzoli, J.-L., Demerliac, S., & Thépot, R. (2014). Climate
 1192 change impacts on multi-objective reservoir management: case study on the

- 1193 Seine River basin, France. *International Journal of River Basin Management*,
1194 12(3), 265–283. <https://doi.org/10.1080/15715124.2013.865636>
- 1195 Dunn, S. M., & Ferrier, R. C. (1999). Natural flow in managed catchments: A case
1196 study of a modelling approach. *Water Research*, 33(3), 621–630.
1197 [https://doi.org/10.1016/S0043-1354\(98\)00268-1](https://doi.org/10.1016/S0043-1354(98)00268-1)
- 1198 Dynesius, M., & Nilsson, C. (1994). Fragmentation and Flow Regulation of River
1199 Systems in the Northern Third of the World. *Science*, 266(5186), 753–762.
1200 <https://doi.org/10.1126/science.266.5186.753>
- 1201 Environmental Protection Agency. (2015). *Definition and Characteristics of Low Flows*
1202 *from DFLOW - Design Flows: Definitions and Methods*. United States
1203 Environmental Protection Agency. [https://www.epa.gov/waterdata/definition-](https://www.epa.gov/waterdata/definition-and-characteristics-low-flows-dflow#methods)
1204 [and-characteristics-low-flows-dflow#methods](https://www.epa.gov/waterdata/definition-and-characteristics-low-flows-dflow#methods)
- 1205 European Commission. (1997). Avis du Comité des régions sur la “Communication de
1206 la Commission au Conseil et au Parlement européen sur la politique
1207 communautaire dans le domaine de l’eau”. *Journal Officiel Des Communautés*
1208 *Européennes C 34/30*, 30–33.
- 1209 Fantin-Cruz, I., Pedrollo, O., Girard, P., Zeilhofer, P., & Hamilton, S. K. (2015). Effects
1210 of a diversion hydropower facility on the hydrological regime of the Correntes
1211 River, a tributary to the Pantanal floodplain, Brazil. *Journal of Hydrology*, 531,
1212 810–820. <https://doi.org/10.1016/j.jhydrol.2015.10.045>
- 1213 Fernández, J. A., Martínez, C., & Magdaleno, F. (2012). Application of indicators of
1214 hydrologic alterations in the designation of heavily modified water bodies in
1215 Spain. *Environmental Science & Policy*, 16, 31–43.
1216 <https://doi.org/10.1016/j.envsci.2011.10.004>

- 1217 Fowler, K., Morden, R., Lowe, L., & Nathan, R. (2015). Advances in assessing the
 1218 impact of hillside farm dams on streamflow. *Australasian Journal of Water
 1219 Resources*, 19(2), 96–108. <https://doi.org/10.1080/13241583.2015.1116182>
- 1220 Gash, J. H. C., & Nobre, C. A. (1997). Climatic Effects of Amazonian Deforestation:
 1221 Some Results from ABRACOS. *Bulletin of the American Meteorological
 1222 Society*, 78(5), 823–830. [https://doi.org/10.1175/1520-
 1223 0477\(1997\)078<0823:CEOADS>2.0.CO;2](https://doi.org/10.1175/1520-0477(1997)078<0823:CEOADS>2.0.CO;2)
- 1224 Gatti, G., Bianchi, C. N., Parravicini, V., Rovere, A., Peirano, A., Montefalcone, M.,
 1225 Massa, M., & Morri, C. (2015). Ecological Change, Sliding Baselines and the
 1226 Importance of Historical Data: Lessons from Combining Observational and
 1227 Quantitative Data on a Temperate Reef Over 70 Years. *Plos One*, 10(2).
 1228 <https://doi.org/10.1371/journal.pone.0118581>
- 1229 Giambelluca, T. W. (2005). 189: Land Use and Water Resources Under a Changing
 1230 Climate. In *Encyclopedia of Hydrological Sciences* (Wiley-Blackwell, Vol. 5,
 1231 pp. 2931–2937). Malcolm G. Anderson.
- 1232 GINGER Environnement & Infrastructures. (2012a). *Etude de détermination des
 1233 volumes prélevables - Bassin versant de l'Agly - Phases 1, 2 et 3 - Bilan et
 1234 impact des prélèvements; Quantification des ressources (in french)* (p. 304).
 1235 Agence de l'Eau Rhône Méditerranée et Corse. [http://www.rhone-
 1236 mediterranee.eaufrance.fr/docs/gestion-
 1237 quantitative/EEVPG/agly/EVP_Agly_rapport_phase1a3_janv2012.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/agly/EVP_Agly_rapport_phase1a3_janv2012.pdf)
- 1238 GINGER Environnement & Infrastructures. (2012b). *Etude de détermination des
 1239 volumes prélevables - Bassin versant du Vidourle - Phase 1, 2 et 3 (in french)* (p.
 1240 290). Agence de l'Eau Rhône Méditerranée et Corse. <http://www.rhone->

- 1241 mediterranee.eaufrance.fr/docs/gestion-
- 1242 quantitative/EEVPG/Vidourle/EVP_Vidourle_rapport_phase1a3_oct2012.pdf
- 1243 Godet, L., & Thomas, A. (2013). Three centuries of land cover changes in the largest
- 1244 French Atlantic wetland provide new insights for wetland conservation. *Applied*
- 1245 *Geography*, 42, 133–139. <https://doi.org/10.1016/j.apgeog.2013.05.011>
- 1246 Gosain, A. K., Rao, S., Srinivasan, R., & Reddy, N. G. (2005). Return-flow assessment
- 1247 for irrigation command in the Palleru river basin using SWAT model.
- 1248 *Hydrological Processes*, 19(3), 673–682. <https://doi.org/10.1002/hyp.5622>
- 1249 Gu, C., Mu, X., Gao, P., Zhao, G., Sun, W., & Li, P. (2017). Effects of climate change
- 1250 and human activities on runoff and sediment inputs of the largest freshwater lake
- 1251 in China, Poyang Lake. *Hydrological Sciences Journal*, 62(14), 2313–2330.
- 1252 <https://doi.org/10.1080/02626667.2017.1372856>
- 1253 Guo, Y., Li, Z., Amo-Boateng, M., Deng, P., & Huang, P. (2014). Quantitative
- 1254 assessment of the impact of climate variability and human activities on runoff
- 1255 changes for the upper reaches of Weihe River. *Stochastic Environmental*
- 1256 *Research and Risk Assessment*, 28(2), 333–346. [https://doi.org/10.1007/s00477-](https://doi.org/10.1007/s00477-013-0752-8)
- 1257 [013-0752-8](https://doi.org/10.1007/s00477-013-0752-8)
- 1258 Haberlie, A. M., Ashley, W. S., Fultz, A. J., & Eagan, S. M. (2016). The effect of
- 1259 reservoirs on the climatology of warm-season thunderstorms in Southeast Texas,
- 1260 USA: reservoirs and thunderstorms. *International Journal of Climatology*,
- 1261 36(4), 1808–1820. <https://doi.org/10.1002/joc.4461>
- 1262 Hart, D. D., Johnson, T. E., Bushaw-Newton, K. L., Horwitz, R. J., Bednarek, A. T.,
- 1263 Charles, D. F., Kreeger, D. A., & Velinsky, D. J. (2002). Dam removal:
- 1264 challenges and opportunities for ecological research and river restoration: we
- 1265 develop a risk assessment framework for understanding how potential responses

- 1266 to dam removal vary with dam and watershed characteristics, which can lead to
- 1267 more effective use of this restoration method. *AIBS Bulletin*, 52(8), 669–682.
- 1268 Hernández-Henríquez, M. A., Mlynowski, T. J., & Déry, S. J. (2010). Reconstructing
- 1269 the natural streamflow of a regulated river: A case study of la grande rivière,
- 1270 Québec, Canada. *Canadian Water Resources Journal*, 35(3), 301–316. Scopus.
- 1271 <https://doi.org/10.4296/cwrj3503301>
- 1272 Hirsch, R. M. (1979). An Evaluation of Some Record Reconstruction Techniques.
- 1273 *Water Resources Management*, 15(6), 1781–1790. [https://doi.org/10](https://doi.org/10.1029/WR015i006p01781)
- 1274 [.1029/WR015i006p01781](https://doi.org/10.1029/WR015i006p01781)
- 1275 Hirsch, R. M. (1982). A comparison of four streamflow record extension techniques.
- 1276 *Water Resources Research*, 18(4), 1081–1088. Scopus.
- 1277 <https://doi.org/10.1029/WR018i004p01081>
- 1278 Holmes, M. G. R., Young, A. R., Gustard, A., & Grew, R. (2002). A region of influence
- 1279 approach to predicting flow duration curves within ungauged catchments.
- 1280 *Hydrology and Earth System Sciences*, 6(4), 721–731.
- 1281 <https://doi.org/10.5194/hess-6-721-2002>
- 1282 Hrachowitz, M., Savenije, H. H. G., Blöschl, G., McDonnell, J. J., Sivapalan, M.,
- 1283 Pomeroy, J. W., Arheimer, B., Blume, T., Clark, M. P., Ehret, U., Fenicia, F.,
- 1284 Freer, J. E., Gelfan, A., Gupta, H. V., Hughes, D. A., Hut, R. W., Montanari, A.,
- 1285 Pande, S., Tetzlaff, D., ... Cudennec, C. (2013). A decade of Predictions in
- 1286 Ungauged Basins (PUB)—a review. *Hydrological Sciences Journal*, 58(6),
- 1287 1198–1255. <https://doi.org/10.1080/02626667.2013.803183>
- 1288 Hu, Z., Wang, L., Wang, Z., Hong, Y., & Zheng, H. (2015). Quantitative assessment of
- 1289 climate and human impacts on surface water resources in a typical semi-arid
- 1290 watershed in the middle reaches of the Yellow River from 1985 to 2006.

- 1291 *International Journal of Climatology*, 35(1), 97–113.
- 1292 <https://doi.org/10.1002/joc.3965>
- 1293 Hubert, P., Carbonnel, J. P., & Chaouche, A. (1989). Segmentation des séries
- 1294 hydrométéorologiques - application à des séries de précipitations et de débits de
- 1295 l’afrique de l’ouest. *Journal of Hydrology*, 110(3–4), 349–367.
- 1296 [https://doi.org/10.1016/0022-1694\(89\)90197-2](https://doi.org/10.1016/0022-1694(89)90197-2)
- 1297 Hughes, D. A. (2019). A simple approach to estimating channel transmission losses in
- 1298 large South African river basins. *Journal of Hydrology: Regional Studies*, 25.
- 1299 <https://doi.org/10.1016/j.ejrh.2019.100619>
- 1300 Hughes, D. A., & Mantel, S. K. (2010). Estimating the uncertainty in simulating the
- 1301 impacts of small farm dams on streamflow regimes in South Africa.
- 1302 *Hydrological Sciences Journal*, 55(4), 578–592.
- 1303 <https://doi.org/10.1080/02626667.2010.484903>
- 1304 Huo, Z., Feng, S., Kang, S., Li, W., & Chen, S. (2008). Effect of climate changes and
- 1305 water-related human activities on annual stream flows of the Shiyang river basin
- 1306 in arid north-west China. *Hydrological Processes*, 22(16), 3155–3167.
- 1307 <https://doi.org/10.1002/hyp.6900>
- 1308 Irwin, R. W., Dickinson, W. T., & Lammers, W. (1975). Model for the determination of
- 1309 the natural streamflow of Venison Creek. *Canadian Agricultural Engineering*,
- 1310 17(1).
- 1311 ISL. (2011). *Etude de détermination des volumes prélevables - Bassin versant du Doux*
- 1312 *- Rapport de phase 3 (in french)* (p. 87). Agence de l’Eau Rhône Méditerranée et
- 1313 Corse. [http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Doux/EVP_Doux_rapport_phase3_janv2011.pdf)
- 1314 [quantitative/EEVPG/Doux/EVP_Doux_rapport_phase3_janv2011.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Doux/EVP_Doux_rapport_phase3_janv2011.pdf)

- 1315 Jacobson, R. B., & Galat, D. L. (2008). Design of a naturalized flow regime - an
 1316 example from the Lower Missouri River, USA. *Ecohydrology*, 1, 81–104.
 1317 <https://doi.org/DOI: 10.1002/eco.9>
- 1318 Jiang, S., Ren, L., Yong, B., Singh, V. P., Yang, X., & Yuan, F. (2011). Quantifying the
 1319 effects of climate variability and human activities on runoff from the Laohahe
 1320 basin in northern China using three different methods. *Hydrological Processes*,
 1321 25(16), 2492–2505. <https://doi.org/10.1002/hyp.8002>
- 1322 Jiongxin, X. (2005). The Water Fluxes of the Yellow River to the Sea in the Past 50
 1323 Years, in Response to Climate Change and Human Activities. *Environmental*
 1324 *Management*, 35(5), 620–631. <https://doi.org/10.1007/s00267-004-3094-y>
- 1325 Kendy, E., & Bredehoeft, J. D. (2006). Transient effects of groundwater pumping and
 1326 surface-water-irrigation returns on streamflow: transient effects of groundwater
 1327 stress. *Water Resources Research*, 42(8).
 1328 <https://doi.org/10.1029/2005WR004792>
- 1329 Kibler, K., Tullos, D., & Kondolf, M. (2011). Evolving Expectations of Dam Removal
 1330 Outcomes: Downstream Geomorphic Effects Following Removal of a Small,
 1331 Gravel-Filled Dam. *JAWRA Journal of the American Water Resources*
 1332 *Association*, 47(2), 408–423. <https://doi.org/10.1111/j.1752-1688.2011.00523.x>
- 1333 Kim, N. W., Lee, J. E., & Kim, J. T. (2012). Assessment of Flow Regulation Effects by
 1334 Dams in the Han River, Korea, on the Downstream Flow Regimes Using
 1335 SWAT. *Journal of Water Resources Planning and Management*, 138(1), 24–35.
 1336 [https://doi.org/10.1061/\(ASCE\)WR.1943-5452.0000148](https://doi.org/10.1061/(ASCE)WR.1943-5452.0000148)
- 1337 Kim, T. J. (2015). Generation of daily naturalized flow at ungaged control points.
 1338 *Journal of Water Supply: Research and Technology - AQUA*, 64(3), 354–364.
 1339 Scopus. <https://doi.org/10.2166/aqua.2015.096>

- 1340 Kim, T. J., & Wurbs, R. A. (2011). Development of monthly naturalized flow using
 1341 Water Rights Analysis Package (WRAP)-based methods. *KSCE Journal of Civil
 1342 Engineering*, 15(7), 1299–1307. <https://doi.org/10.1007/s12205-011-1184-y>
- 1343 Klemes, V. (1986). Operational testing of hydrological simulation models. *Hydrological
 1344 Sciences Journal*, 31(1), 13–24. Scopus.
 1345 <https://doi.org/10.1080/02626668609491024>
- 1346 Laizé, C. L. R., Acreman, M. C., Schneider, C., Dunbar, M. J., Houghton-Carr, H. A.,
 1347 Flörke, M., & Hannah, D. M. (2014). Projected flow alteration and ecological
 1348 risk for pan-european rivers. *River Research and Applications*, 30(3), 299–314.
 1349 <https://doi.org/10.1002/rra.2645>
- 1350 Lebecherel, L. (2015). *Sensibilité des calculs hydrologiques à la densité des réseaux de
 1351 mesure hydrométrique et pluviométrique* [Thèse de doctorat]. Irstea,
 1352 AgroParisTech.
- 1353 Lebecherel, Laure, Andréassian, V., & Perrin, C. (2016). On evaluating the robustness
 1354 of spatial-proximity-based regionalization methods. *Journal of Hydrology*, 539,
 1355 196–203. <http://dx.doi.org/10.1016/j.jhydrol.2016.05.031>
- 1356 Li, L.-J., Zhang, L., Wang, H., Wang, J., Yang, J.-W., Jiang, D.-J., Li, J.-Y., & Qin, D.-
 1357 Y. (2007). Assessing the impact of climate variability and human activities on
 1358 streamflow from the Wuding River basin in China. *Hydrological Processes*,
 1359 21(25), 3485–3491. <https://doi.org/10.1002/hyp.6485>
- 1360 Li, S., Xiong, L., Dong, L., & Zhang, J. (2013). Effects of the Three Gorges Reservoir
 1361 on the hydrological droughts at the downstream Yichang station during 2003–
 1362 2011. *Hydrological Processes*, 27(26), 3981–3993.
 1363 <https://doi.org/10.1002/hyp.9541>

- 1364 Littlewood, I. G., & Marsh, T. J. (1996). Re-assessment of the monthly naturalized flow
 1365 record for the River Thames at Kingston since 1883, and the implications for the
 1366 relative severity of historical droughts. *River Research and Applications*, 12(1),
 1367 13–26. [https://doi.org/10.1002/\(SICI\)1099-1646\(199601\)12:1<13::AID-RRR364>3.0.CO;2-N](https://doi.org/10.1002/(SICI)1099-1646(199601)12:1<13::AID-RRR364>3.0.CO;2-N)
- 1369 Ma, H., Yang, D., Tan, S. K., Gao, B., & Hu, Q. (2010). Impact of climate variability
 1370 and human activity on streamflow decrease in the Miyun Reservoir catchment.
 1371 *Journal of Hydrology*, 389(3–4), 317–324.
 1372 <https://doi.org/10.1016/j.jhydrol.2010.06.010>
- 1373 Magirl, C. S., Hildale, R. C., Curran, C. A., Duda, J. J., Straub, T. D., Domanski, M., &
 1374 Foreman, J. R. (2014). Large-scale dam removal on the Elwha River,
 1375 Washington, USA: Fluvial sediment load. *Geomorphology*, 246, 669–686.
 1376 <https://doi.org/10.1016/j.geomorph.2014.12.032>
- 1377 Maheshwari, B. L., Walker, K. F., & McMahon, T. A. (1995). Effects of regulation on
 1378 the flow regime of the River Murray, Australia. *River Research and*
 1379 *Applications*, 10(1), 15–38. <https://doi.org/10.1002/rrr.3450100103>
- 1380 Margat, J., & Andréassian, V. (2008). *L'eau* (Le Cavalier Bleu).
- 1381 Maurel, F., Lepelletier, T., Moreau, J., Noeueglise, C., & Lancelot, B. (2008).
 1382 Prospective assessment in water consumption-resources in Seine-Normandie
 1383 basin. *Houille Blanche*, 5, 45–52. <https://doi.org/10.1051/lhb:2008053>
- 1384 McCully, P. (2001). A new order for river and society: the world commission on dams,
 1385 and beyond. In *Silenced rivers. The ecology and politics of large dams*. (pp. i–
 1386 lxxii). Zed books.

- 1387 McMillan, H., Krueger, T., & Freer, J. (2012). Benchmarking observational
 1388 uncertainties for hydrology: rainfall, river discharge and water quality.
 1389 *Hydrological Processes*, 26(26), 4078–4111. <https://doi.org/10.1002/hyp.9384>
- 1390 Montanari, A., Young, G., Savenije, H. H. G., Hughes, D., Wagener, T., Ren, L. L.,
 1391 Koutsoyiannis, D., Cudennec, C., Toth, E., Grimaldi, S., Blöschl, G., Sivapalan,
 1392 M., Beven, K., Gupta, H., Hipsey, M., Schaeffli, B., Arheimer, B., Boegh, E.,
 1393 Schymanski, S. J., ... Belyaev, V. (2013). “Panta Rhei—Everything Flows”:
 1394 Change in hydrology and society—The IAHS Scientific Decade 2013–2022.
 1395 *Hydrological Sciences Journal*, 58(6), 1256–1275.
 1396 <https://doi.org/10.1080/02626667.2013.809088>
- 1397 Morin, G., Fortin, J. P., & Charbonneau, R. (1975). Utilisation du modèle
 1398 hydrophysiographique CEQUEAU pour l’exploitation des réservoirs artificiels.
 1399 *IAHS Publication*, 115, 176–184.
- 1400 MPO. (2013). *Cadre d’évalutaion des exigences relatives au débit écologique*
 1401 *nécessaire pour soutenir les pêches au Canada. Secr. can. de consult. sci. du*
 1402 *MPO, Avis. sci. 2013/017. (p. 18).*
- 1403 Mwedzi, T., Katiyo, L., Mugabe, F. T., Bere, T., Bangira, C., Mangadze, T., & Kupika,
 1404 O. L. (2016). A spatial assessment of stream-flow characteristics and hydrologic
 1405 alterations, post dam construction in the Manyame catchment, Zimbabwe. *Water*
 1406 *SA*, 42(2), 194–202. <https://doi.org/10.4314/wsa.v42i2.03>
- 1407 Naik, P. K., & Jay, D. A. (2005). Estimation of Columbia River virgin flow: 1879 to
 1408 1928. *Hydrological Processes*, 19(9), 1807–1824.
 1409 <https://doi.org/10.1002/hyp.5636>

- 1410 Nobert, J., & Jeremiah, J. (2012). Hydrological Response of Watershed Systems to
 1411 Land Use/Cover Change. A Case of Wami River Basin. *The Open Hydrology*
 1412 *Journal*, 6, 78–87. <https://doi.org/10.2174/1874378101206010078>
- 1413 NSW Scientific Committee. (2002). *Alteration to the natural flow regimes of rivers,*
 1414 *streams, floodplains & wetlands - key threatening process listing. NSW*
 1415 *Scientific Committee - final determination.*
 1416 <http://www.environment.nsw.gov.au/threatenedspecies/AlterationNaturalFlowK>
 1417 [TPListing.htm](http://www.environment.nsw.gov.au/threatenedspecies/AlterationNaturalFlowK)
- 1418 Oudin, L., Michel, C., & Anctil, F. (2005). Which potential evapotranspiration input for
 1419 a lumped rainfall-runoff model? Part 1 - Can rainfall-runoff models effectively
 1420 handle detailed potential evapotranspiration inputs? *Journal of Hydrology*,
 1421 303(1–4), 275–289. <https://doi.org/10.1016/j.jhydrol.2004.08.025>
- 1422 Oudin, L., Perrin, C., Mathevet, T., Andréassian, V., & Michel, C. (2006). Impact of
 1423 biased and randomly corrupted inputs on the efficiency and the parameters of
 1424 watershed models. *Journal of Hydrology*, 320(1–2), 62–83. Scopus.
 1425 <https://doi.org/10.1016/j.jhydrol.2005.07.016>
- 1426 Pacheco-Guerrero, A., Goodrich, D. C., Gonzalez-Trinidad, J., Junez-Ferreira, H. E., &
 1427 Bautista-Capetillo, C. F. (2017). Flooding in ephemeral streams: incorporating
 1428 transmission losses. *Journal of Maps*, 13(2), 350–357.
 1429 <https://doi.org/10.1080/17445647.2017.1305303>
- 1430 Pagano, T. C., & Sorooshian, S. (2005). 173: Global Water Cycle (Fundamental,
 1431 Theory, Mechanisms). In *Encyclopedia of Hydrological Sciences* (Wiley-
 1432 Blackwell, Vol. 5, pp. 2697–2711). Malcolm G. Anderson.
- 1433 Page, K., Read, A., Frazier, P., & Mount, N. (2005). The effect of altered flow regime
 1434 on the frequency and duration of bankfull discharge: Murrumbidgee River,

- 1
2
3 1435 Australia. *River Research and Applications*, 21(5), 567–578.
4
5 1436 <https://doi.org/10.1002/rra.828>
6
7 1437 Pechlivanidis, I. G., Jackson, B. M., McIntyre, N. R., & Wheeler, H. S. (2011).
8
9 1438 Catchment scale hydrological modelling: a review of model types, calibration
10
11 1439 approaches and uncertainty analysis methods in the context of recent
12
13 1440 developments in technology and applications. *Global NEST Journal*, 13(3),
14
15 1441 193–214.
16
17 1442 Peters, D. L., & Prowse, T. D. (2001). Regulation effects on the lower Peace River,
18
19 1443 Canada. *Hydrological Processes*, 15(16), 3181–3194.
20
21 1444 <https://doi.org/10.1002/hyp.321>
22
23 1445 Peters, D. L., Prowse, T. D., Pietroniro, A., & Leconte, R. (2006). Flood hydrology of
24
25 1446 the Peace-Athabasca Delta, northern Canada. *Hydrological Processes*, 20(19),
26
27 1447 4073–4096. <https://doi.org/10.1002/hyp.6420>
28
29 1448 Poff, N. L., Allan, J. D., Bain, M. B., Karr, J. R., Prestegard, K. L., Richter, B. D.,
30
31 1449 Sparks, R. E., & Stromberg, J. C. (1997). The natural flow regime: A paradigm
32
33 1450 for river conservation and restoration. *BioScience*, 47(11), 769–784. Scopus.
34
35 1451 <https://doi.org/10.2307/1313099>
36
37 1452 Rahman, S., & Bowling, L. (2018). Streamflow Impacts of Management and
38
39 1453 Environmental Change in the Upper Wabash River Basin. *Journal of Hydrologic*
40
41 1454 *Engineering*, 24(3), 05018034. [https://doi.org/10.1061/\(ASCE\)HE.1943-](https://doi.org/10.1061/(ASCE)HE.1943-)
42
43 1455 5584.0001750
44
45 1456 Refsgaard, J. C., van der Sluijs, J. P., Højberg, A. L., & Vanrolleghem, P. A. (2007).
46
47 1457 Uncertainty in the environmental modelling process – A framework and
48
49 1458 guidance. *Environmental Modelling & Software*, 22(11), 1543–1556.
50
51 1459 <https://doi.org/10.1016/j.envsoft.2007.02.004>
52
53
54
55
56
57
58
59
60

- 1460 Richter, B. D., Baumgartner, J.V., Powell, J., & Braun, D. (1996). A Method for
 1461 Assessing Hydrologic Alteration within Ecosystems. *Conservation Biology*,
 1462 10(4), 1163–1174. <https://doi.org/10.1046/j.1523-1739.1996.10041163.x>
- 1463 Risques et Développement, & Maison régionale de l'Eau. (2012). *Etudes d'estimation*
 1464 *des volumes prélevables globaux - Sous bassin versant des Usses - Rapport final*
 1465 *(in french)* (p. 214). Agence de l'Eau Rhône Méditerranée et Corse.
 1466 [http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Usses/EVP_Usses_rapport_phase1a3_dec2012.pdf)
 1467 [quantitative/EEVPG/Usses/EVP_Usses_rapport_phase1a3_dec2012.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Usses/EVP_Usses_rapport_phase1a3_dec2012.pdf)
- 1468 Roubicek, A. J. (2010). Does the choice of climate baseline matter in ecological niche
 1469 modelling? *Ecological Modelling*, 221(19), 2280–2286.
 1470 <https://doi.org/10.1016/j.ecolmodel.2010.06.021>
- 1471 Ryo, M., Iwasaki, Y., Yoshimura, C., & Saavedra V, O. C. (2015). Evaluation of spatial
 1472 pattern of altered flow regimes on a river network using a distributed
 1473 hydrological model. *PLoS ONE*, 10(7).
 1474 <https://doi.org/10.1371/journal.pone.0133833>
- 1475 SAFEGE Ingénieurs Conseils. (2011). *Etude de détermination des volumes prélevables*
 1476 *sur le bassin versant de la Tille - Rapport de Phase 3 (in french)* (Version finale
 1477 (3.2); p. 118). Agence de l'Eau Rhône Méditerranée et Corse. [http://www.rhone-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Tille/EVP_Tille_rapport_phase3_dec2011.pdf)
 1478 [mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Tille/EVP_Tille_rapport_phase3_dec2011.pdf)
 1479 [quantitative/EEVPG/Tille/EVP_Tille_rapport_phase3_dec2011.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Tille/EVP_Tille_rapport_phase3_dec2011.pdf)
- 1480 Schreiner-McGraw, A. P., & Vivoni, E. R. (2018). On the Sensitivity of Hillslope
 1481 Runoff and Channel Transmission Losses in Arid Piedmont Slopes. *Water*
 1482 *Resources Research*, 54(7), 4498–4518. <https://doi.org/10.1029/2018WR022842>
- 1483 Shi, P., Ma, X., Hou, Y., Li, Q., Zhang, Z., Qu, S., Chen, C., Cai, T., & Fang, X. (2013).
 1484 Effects of Land-Use and Climate Change on Hydrological Processes in the

- 1485 Upstream of Huai River, China. *Water Resources Management*, 27(5), 1263–
1486 1278. <https://doi.org/10.1007/s11269-012-0237-4>
- 1487 Shiklomanov, A. I., & Lammers, R. B. (2009). Record Russian river discharge in 2007
1488 and the limits of analysis. *Environmental Research Letters*, 4(4), 045015.
1489 <https://doi.org/10.1088/1748-9326/4/4/045015>
- 1490 Siriwardena, L., Finlayson, B. L., & McMahon, T. A. (2006). The impact of land use
1491 change on catchment hydrology in large catchments: The Comet River, Central
1492 Queensland, Australia. *Journal of Hydrology*, 326(1–4), 199–214.
1493 <https://doi.org/10.1016/j.jhydrol.2005.10.030>
- 1494 Sivapalan, M., Takeuchi, K., Franks, S. W., Gupta, V. K., Karambiri, H., Lakshmi, V.,
1495 Liang, X., McDONNELL, J. J., Mendiando, E. M., O’Connell, P. E., Oki, T.,
1496 Pomeroy, J. W., Schertzer, D., Uhlenbrook, S., & Zehe, E. (2003). IAHS Decade
1497 on Predictions in Ungauged Basins (PUB), 2003–2012: Shaping an exciting
1498 future for the hydrological sciences. *Hydrological Sciences Journal*, 48(6), 857–
1499 880. <https://doi.org/10.1623/hysj.48.6.857.51421>
- 1500 Slabbert, N. (2007). *The potential impact of an inter-basin water transfer on the
1501 Modder and Caledon river systems - Chapter 1: An overview of inter-basin
1502 transfer schemes and the South African perspectives*. [University of the Free
1503 State].
1504 [http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.471.5502&rep=rep1&
1505 type=pdf](http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.471.5502&rep=rep1&type=pdf)
- 1506 Smakhtin, V. Y. (1999). Generation of natural daily flow time-series in regulated rivers
1507 using a non-linear spatial interpolation technique. *River Research and
1508 Applications*, 15(4), 311–323.

- 1509 Société du Canal de Provence, & ASCONIT Consultants. (2012). *Etudes d'estimation*
 1510 *des volumes prélevables globaux - Sous bassin versant de la Berre - Rapport*
 1511 *final phase 3 (in french)* (p. 73). Agence de l'Eau Rhône Méditerranée et Corse.
 1512 [http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/berre-dromoise/EVP_berre_rapport-ph3_juillet2012.pdf)
 1513 [quantitative/EEVPG/berre-dromoise/EVP_berre_rapport-ph3_juillet2012.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/berre-dromoise/EVP_berre_rapport-ph3_juillet2012.pdf)
 1514 SOGREAH. (2012). *Etudes de détermination des volumes prélevables - Bassin versant*
 1515 *du Sègre - Rapport de phases 1, 2 et 3 (in french)* (No. 4331135-v10; p. 116).
 1516 Agence de l'Eau Rhône Méditerranée et Corse. [http://www.rhone-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Segre/EVP_Segre_rapport_phase1a3_nov2012.pdf)
 1517 [mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Segre/EVP_Segre_rapport_phase1a3_nov2012.pdf)
 1518 [quantitative/EEVPG/Segre/EVP_Segre_rapport_phase1a3_nov2012.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Segre/EVP_Segre_rapport_phase1a3_nov2012.pdf)
 1519 SOGREAH, anteagroup, & Pierre Paris Consultant. (2011). *Etude de détermination des*
 1520 *volumes maximum prélevables - Phase 3: Impact des prélèvements et*
 1521 *quantification des ressources existantes (in french)*. (No. 1741452; p. 116).
 1522 Agence de l'Eau Rhône Méditerranée et Corse. [http://www.rhone-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Ouche/EVP_Ouche_rapport_phase3_juin2011.pdf)
 1523 [mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Ouche/EVP_Ouche_rapport_phase3_juin2011.pdf)
 1524 [quantitative/EEVPG/Ouche/EVP_Ouche_rapport_phase3_juin2011.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/Ouche/EVP_Ouche_rapport_phase3_juin2011.pdf)
 1525 SOGREAH Consultants, & EPTEAU. (2012). *Etudes d'estimation des volumes*
 1526 *prélevables globaux - Sous bassin versant de La Basse Vallée de l'Ain - Rapport*
 1527 *de phase 3 (in french)* (p. 115). Agence de l'Eau Rhône Méditerranée et Corse.
 1528 [http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/bv_Ain/EVP_BVA_rapport_phase3_juin2012.pdf)
 1529 [quantitative/EEVPG/bv_Ain/EVP_BVA_rapport_phase3_juin2012.pdf](http://www.rhone-mediterranee.eaufrance.fr/docs/gestion-quantitative/EEVPG/bv_Ain/EVP_BVA_rapport_phase3_juin2012.pdf)
 1530 Stahl, K., Hisdal, H., Hannaford, J., Tallaksen, L. M., van Lanen, H. A. J., Sauquet, E.,
 1531 Demuth, S., Fendekova, M., & Jodar, J. (2010). Streamflow trends in Europe:
 1532 evidence from a dataset of near-natural catchments. *Hydrology and Earth*
 1533 *System Sciences*, 14, 2367–2382. <https://doi.org/10.5194/hess-14-2367-2010>

- 1534 Stednick, J. D. (1996). Monitoring the effects of timber harvest on annual water yield.
 1535 *Journal of Hydrology*, 176(1–4), 79–95. <https://doi.org/10.1016/0022->
 1536 1694(95)02780-7
- 1537 Steffen, W., Broadgate, W., Deutsch, L., Gaffney, O., & Ludwig, C. (2015). The
 1538 trajectory of the Anthropocene: The Great Acceleration. *The Anthropocene*
 1539 *Review*, 2(1), 81–98. <https://doi.org/10.1177/2053019614564785>
- 1540 Steffen, W., Grinevald, J., Crutzen, P., & McNeill, J. (2011). The Anthropocene:
 1541 conceptual and historical perspectives. *Philosophical Transactions of the Royal*
 1542 *Society A: Mathematical, Physical and Engineering Sciences*, 369(1938), 842–
 1543 867. <https://doi.org/10.1098/rsta.2010.0327>
- 1544 Stoddard, J. L., Larsen, D. P., Hawkins, C. P., Johnson, R. K., & Norris, R. H. (2006).
 1545 Setting expectations for the ecological condition of streams: the concept of
 1546 reference condition. *Ecological Applications*, 16(4), 1267–1276.
 1547 [https://doi.org/10.1890/1051-0761\(2006\)016\[1267:SEFTEC\]2.0.CO;2](https://doi.org/10.1890/1051-0761(2006)016[1267:SEFTEC]2.0.CO;2)
- 1548 Tardieu, H. (2008). Water scarcity, new challenges for the operational management of "
 1549 sustainable infrastructures ". *La Houille Blanche*, 6, 85–92.
 1550 <https://doi.org/10.1051/lhb:2008076>
- 1551 Theis, C. V. (1941). The effect of a weel on the flow of a nearby stream. *Eos*,
 1552 *Transactions American Geophysical Union*, 22(3), 734–738.
 1553 <https://doi.org/10.1029/TR022i003p00734>
- 1554 Tongal, H., Demirel, M. C., & Moradkhani, H. (2017). Analysis of dam-induced cyclic
 1555 patterns on river flow dynamics. *Hydrological Sciences Journal*, 62(4), 626–
 1556 641. <https://doi.org/DOI: 10.1080/02626667.2016.1252841>

- 1557 USGS, & National Water-Use Science Project. (2019). *Water-Use Terminology*.
 1558 [https://www.usgs.gov/mission-areas/water-resources/science/water-use-](https://www.usgs.gov/mission-areas/water-resources/science/water-use-terminology?qt-science_center_objects=0#qt-science_center_objects)
 1559 [terminology?qt-science_center_objects=0#qt-science_center_objects](https://www.usgs.gov/mission-areas/water-resources/science/water-use-terminology?qt-science_center_objects=0#qt-science_center_objects)
- 1560 Vidal, J. P. (2019). *Écrire l'hydrologie de l'Anthropocène* [Mémoire d'Habilitation à
 1561 diriger des recherches]. Université Grenoble Alpes, Ecole Doctorale Terre,
 1562 Univers, Environnement.
- 1563 Villocel, A. (2002). Le système Neste Développement d'une approche citoyenne de la
 1564 ressource en eau (The Neste system-Development of a citizen-based approach of
 1565 water resources management). *La Houille Blanche*, 4–5(78–82).
- 1566 Vörösmarty, C. J., & Sahagian, D. (2000). Anthropogenic Disturbance of the Terrestrial
 1567 Water Cycle. *BioScience*, 50(9), 753. [https://doi.org/10.1641/0006-](https://doi.org/10.1641/0006-3568(2000)050[0753:ADOTTW]2.0.CO;2)
 1568 [3568\(2000\)050\[0753:ADOTTW\]2.0.CO;2](https://doi.org/10.1641/0006-3568(2000)050[0753:ADOTTW]2.0.CO;2)
- 1569 Wallace, R. B., & Pavvloski, J. T. (1988). Assessing impacts of irrigation on
 1570 streamflow. *Journal of Irrigation and Drainage Engineering*, 114(2), 211–225.
 1571 [https://doi.org/10.1061/\(ASCE\)0733-9437\(1988\)114:2\(211\)](https://doi.org/10.1061/(ASCE)0733-9437(1988)114:2(211))
- 1572 Wang, G., Xia, J., & Chen, J. (2009). Quantification of effects of climate variations and
 1573 human activities on runoff by a monthly water balance model: A case study of
 1574 the Chaobai River basin in northern China: Climate variations and human
 1575 activities. *Water Resources Research*, 45(7).
 1576 <https://doi.org/10.1029/2007WR006768>
- 1577 Wang, J., Hong, Y., Gourley, J., Adhikari, P., Li, L., & Su, F. (2010). Quantitative
 1578 assessment of climate change and human impacts on long-term hydrologic
 1579 response: a case study in a sub-basin of the Yellow River, China. *International*
 1580 *Journal of Climatology*, 30(14), 2130–2137. <https://doi.org/10.1002/joc.2023>

- 1581 Wang, W., Shao, Q., Yang, T., Peng, S., Xing, W., Sun, F., & Luo, Y. (2013).
 1582 Quantitative assessment of the impact of climate variability and human activities
 1583 on runoff changes: a case study in four catchments of the Haihe River basin,
 1584 China. *Hydrological Processes*, 27(8), 1158–1174.
 1585 <https://doi.org/10.1002/hyp.9299>
- 1586 WaterNSW. (2015). *Glossary of water terms*. WaterNSW.
 1587 <http://www.watarnsw.com.au/customer-service/iwas/glossary>
- 1588 Weingartner, R., & Aschwanden, H. (1994). Quantification des débits des cours d'eau
 1589 des Alpes suisses et des influences anthropiques qui les affectent. *Revue de*
 1590 *géographie alpine*, 82(2), 45–57. <https://doi.org/10.3406/rga.1994.3749>
- 1591 Wen, L. (2009). Reconstruction natural flow in a regulated system, the Murrumbidgee
 1592 River, Australia, using time series analysis. *Journal of Hydrology*, 364(3–4),
 1593 216–226. Scopus. <https://doi.org/10.1016/j.jhydrol.2008.10.023>
- 1594 Whitfield, P. H., Burn, D. H., Hannaford, J., Higgins, H., Hodgkins, G. A., Marsh, T., &
 1595 Looser, U. (2012). Reference hydrologic networks I. The status and potential
 1596 future directions of national reference hydrologic networks for detecting trends.
 1597 *Hydrological Sciences Journal*, 57(8), 1562–1579.
 1598 <https://doi.org/10.1080/02626667.2012.728706>
- 1599 Winton, R. S., Calamita, E., & Wehrli, B. (2019). Reviews and syntheses: Dams, water
 1600 quality and tropical reservoir stratification. *Biogeosciences*, 16, 1657–1671.
 1601 <https://doi.org/10.5194/bg-16-1657-2019>
- 1602 WMO. (2012). *Glossaire international d'hydrologie - International glossary of*
 1603 *hydrology*. (Vol. 385). World Meteorological Organization.
- 1604 Wu, F. C., Chang, C. F., & Shiau, J. T. (2015). Assessment of flow regime alterations
 1605 over a spectrum of temporal scales using wavelet-based approaches. *Water*

- 1606 *Resources Research*, 51(5), 3317–3338. Scopus.
- 1607 <https://doi.org/10.1002/2014WR016595>
- 1608 Wurbs, R. A. (2006). Methods for developing naturalized monthly flows at gaged and
- 1609 ungaged sites. *Journal of Hydrologic Engineering*, 11(1), 55–64. Scopus.
- 1610 [https://doi.org/10.1061/\(ASCE\)1084-0699\(2006\)11:1\(55\)](https://doi.org/10.1061/(ASCE)1084-0699(2006)11:1(55))
- 1611 WWAP. (2009). *The United Nations World Water Development Report 3: Water in a*
- 1612 *changing world* (p. 429). Paris: UNESCO & London: Earthscan.
- 1613 Wyrick, J. R., Rischman, B. A., Burke, C. A., McGee, C., & Williams, C. (2009a).
- 1614 Using hydraulic modeling to address social impacts of small dam removals in
- 1615 southern New Jersey. *Journal of Environmental Management*, 90, S270–S278.
- 1616 <https://doi.org/10.1016/j.jenvman.2008.07.027>
- 1617 Wyrick, J. R., Rischman, B. A., Burke, C. A., McGee, C., & Williams, C. (2009b).
- 1618 Using hydraulic modeling to address social impacts of small dam removals in
- 1619 southern New Jersey. *Journal of Environmental Management*, 90, S270–S278.
- 1620 <https://doi.org/10.1016/j.jenvman.2008.07.027>
- 1621 Ye, B., Yang, D., & Kane, D. L. (2003). Changes in Lena River streamflow hydrology:
- 1622 Human impacts versus natural variations. *Water Resources Research*, 39(7).
- 1623 <https://doi.org/10.1029/2003WR001991>
- 1624 Yin, J., He, F., Xiong, Y. J., & Qiu, G. Y. (2017). Effects of land use/land cover and
- 1625 climate changes on surface runoff in a semi-humid and semi-arid transition zone
- 1626 in northwest China. *Hydrology and Earth System Sciences*, 21(1), 183–196.
- 1627 <https://doi.org/10.5194/hess-21-183-2017>
- 1628 Young, A. R., Grew, R., & Holmes, M. G. R. (2003). Low Flows 2000: a national water
- 1629 resources assessment and decision support tool. *Water Science and Technology*,
- 1630 48(10), 119–126. <https://doi.org/10.2166/wst.2003.0554>

- 1
2
3 1631 Yuan, X., Zhang, M., Wang, L., & Zhou, T. (2017). Understanding and seasonal
4
5 1632 forecasting of hydrological drought in the Anthropocene. *Hydrology and Earth*
6
7 1633 *System Sciences*, 21(11), 5477–5492. <https://doi.org/10.5194/hess-21-5477-2017>
8
9
10 1634 Zhan, C., Niu, C., Song, X., & Xu, C. (2013). The impacts of climate variability and
11
12 1635 human activities on streamflow in Bai River basin, northern China. *Hydrology*
13
14 1636 *Research*, 44(5), 875. <https://doi.org/10.2166/nh.2012.146>
15
16
17 1637 Zhang, Ling, Nan, Z., Xu, Y., & Li, S. (2016). Hydrological Impacts of Land Use
18
19 1638 Change and Climate Variability in the Headwater Region of the Heihe River
20
21 1639 Basin, Northwest China. *PLOS ONE*, 11(6), e0158394.
22
23
24 1640 <https://doi.org/10.1371/journal.pone.0158394>
25
26 1641 Zhang, Lu, Cheng, L., Chiew, F., & Fu, B. (2018). Understanding the impacts of
27
28 1642 climate and landuse change on water yield. *Current Opinion in Environmental*
29
30 1643 *Sustainability*, 33, 167–174. <https://doi.org/10.1016/j.cosust.2018.04.017>
31
32
33
34 1644
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

10 Appendix 1: Operational implementation of naturalization methods

[Figure 9 here]

For Peer Review Only

1647 [Table 7 here]

1648

1649

For Peer Review Only

- 1651 Table 1. Definitions of "natural streamflow" and "natural regime" found in the
1652 literature.
- 1653 Table 2. Synthesis of studies applying Water Balance methods.
- 1654 Table 3. Synthesis of studies applying Reconstitution methods.
- 1655 Table 4. Synthesis of studies applying Extension methods.
- 1656 Table 5. Synthesis of models used in studies applying Routing modelling methods.
- 1657 Table 6. Synthesis of input data and tools used by each of the naturalization methods.
- 1658 Table 7. Synthesis of withdrawable water volume studies. WB corresponds to the Water
1659 Balance method, R to the Reconstitution method, E to the Extension method and N to
1660 the Neighbourhood method.
- 1661 Figure 1. Schematic representation of the impacts of human activities and the water
1662 cycle components they may directly impact (derived from Botai et al., 2015).
- 1663 Figure 2. A catchment impacted by human activities: gauging stations A1 and B1 are
1664 uninfluenced, gauging stations A2, B2 and C are candidates for naturalization
1665 procedures (Source: INRAE).
- 1666 Figure 3. Diagram of the three periods distinguished in naturalization.
- 1667 Figure 4. Hydrograph at logarithmic scale of the daily observed streamflow of the Aube
1668 River at Arcis-sur-Aube (France, 3560 km²). The red line corresponds to the upstream
1669 dam's commissioning in 1990.
- 1670 Figure 5. Diagram of the choice of naturalization according to the available data.
- 1671 Figure 6. Naturalization methods applied in the studies reviewed.
- 1672 Figure 7. Illustration of the two application steps of the Reconstitution method.
- 1673 Figure 8. Illustration of the two application steps of the Extension method.
- 1674 Figure 9. Map of the withdrawable water volumes in the catchments studied (Rhône-
1675 Mediterranean district).

Schematic representation of the impacts of human activities and the water cycle components they may directly impact (derived from Botai et al., 2015)

218x108mm (150 x 150 DPI)

A catchment impacted by human activities: gauging stations A1 and B1 are uninfluenced, gauging stations A2, B2 and C are candidates for naturalization procedures (Source: INRAE)

162x110mm (150 x 150 DPI)

Diagram of the three periods distinguished in naturalization.

168x31mm (150 x 150 DPI)

Hydrograph at logarithmic scale of the daily observed streamflow of the Aube River at Arcis-sur-Aube (France, 3560 km²). The red line corresponds to the upstream dam’s commissioning in 1990.

180x88mm (150 x 150 DPI)

Diagram of the choice of naturalization according to the available data.

252x183mm (150 x 150 DPI)

Naturalization methods applied in the studies reviewed.

Illustration of the two application steps of the Reconstitution method.

148x76mm (150 x 150 DPI)

Illustration of the two application steps of the Extension method.

162x92mm (150 x 150 DPI)

Map of the withdrawable water volumes in the catchments studied (Rhône-Mediterranean district).

638x718mm (72 x 72 DPI)

Source	Definition
New South Wales Scientific Committee in Australia, 2002	(D1) Natural flow regimes are determined by the climate, run-off, catchment size and geomorphology without the impacts of dams, weirs, extraction and river management (NSW Scientific Committee, 2002).
Environmental Protection Agency in the USA, 2015	(D2) A stream's natural flow regime is a function of the climate and physical properties of its unique upstream drainage area (Novak et al., 2015).
Canadian Science Advisory Secretariat, 2013	(D3) A “natural flow regime” can be defined as a flow regime that is only affected by the variability in hydrological inputs and outputs (precipitation, evaporation) and natural water storage (such as groundwater) and for which the response in terms of amplitude, timing, duration and frequency of events is unaltered by human impacts (DFO, 2013).
World Meteorological Organization, 2012	(D4) Natural flow corresponds to flow in a stream that would occur under natural conditions (WMO, 2012).

Authors	Basins	Size of the catchments	Influence	Time step	Period	Length[year]
Irwin et al., 1975	Venison Creek, Canada	90	Irrigation abstraction	Daily	July and August from 1967 to 1969	0.3
Wallace et Pawloski, 1988	Small stream in central Michigan	78	Irrigation abstraction	Monthly	From June to August 1983	0.3
Littlewood et Marsh, 1996	Thames basin to Kingston, United Kingdom	9,950	Reservoirs and abstraction	Monthly	1883-1992	99
Assani et al., 1999	La Wache river, Belgium	118	Two dams	Daily	1930-1995	65
Peters et Prowse, 2001	Lower Peace River, Canada	293,000	Hydroelectric dam	Daily	1972-1996	24
Wurbs, 2006	23 basins in Texas, USA	648 to 685 000		Monthly		
Page et al., 2005	Murrumbidgee river, Murray-Darling river system, Australia	84,000	26 dams, weir, and irrigation canals	Daily	1970-1998	28
Jiongxin, 2005	Lijin station (outlet of the river), Yellow river, China		Diversions	Annual	1952-1996	44
Naik et Jay, 2005	Columbia river at the Dalles	660,480	Irrigation abstraction and dam	Daily	1879-1928	49
Agosta, 2007	Ariege river at Foix, Garonne, France	1,360	Hydroelectric dams	Daily	1990-2004	14
Maurel et al., 2008	Seine basins, France	78,000	Industrial, agricultural and drinking water abstraction	Daily	1975-2004	29
Kim et Wurbs, 2011	Brazos river basin	115,565	Dam and diversions	Monthly	1998-2007	9
Fantin-Cruz et al., 2015	Correntes river, Brazil	3,898	Hydroelectric dam	Daily	2005-2012	7
Tongal et al., 2016	South Fork Flathead river	4,248	Dam	Daily	1953-2000	47
Davtalab et al., 2017	Karkheh river, Iran	50,000	Withdrawal for irrigation and canals	Daily		
Gu et al., 2017	Poyang Lake, China	162,200	14 reservoirs		1961-2013	52
Yuan et al., 2017	Yellow river, China	752,000	Irrigation, diversion, reservoirs, withdrawal for industry and civil sectors	Monthly	1961-2010	49

Study	Name	Spatial resolution	Temporal scale	Reservoirs and associated withdrawals in input	Reservoirs and associated withdrawals model	Irrigation in input	Crop model	Land use and land cover	Withdrawal for domestic and industrial purpose
Maheshwari et al. (1995)	Model of the Murray-Darling Commission	Semi-distributed	Monthly	Yes	No	No	No	No	No
Gosain et al. (2005)	SWAT	Semi-distributed	Daily	Yes	No	Yes	No	Yes	No
Kim et al. (2012)	SWAT	Semi-distributed	Daily	Yes	Yes	No	No	No	No
Nobert and Jeremiah (2012)	SWAT	Semi-distributed	Daily	No	No	No	No	Yes	No
Shi et al. (2013)	SWAT	Semi-distributed	Daily	No	No	No	No	Yes	No
De Girolamo et al. (2015)	SWAT	Semi-distributed	Daily	No	No	Yes	Yes	No	Yes
Zhang et al. (2016)	SWAT	Semi-distributed	Daily	No	No	No	No	Yes	No
Yin et al. (2017)		Semi-distributed	Daily	No	No	No	Yes	No	No
Morin et al. (1975)	CEQUEAU	Distributed	Daily	Yes	Yes	No	No	No	No
Desconnets et al. (1998)	CEQUEAU-ONU	Distributed	Daily	Yes	Yes	No	No	No	No

Authors	Catchment	Country	Influence	Model	Time step	Calibration period	Naturalization period
Siriwardena et al. (2006)	Comet River basin (1 400 km ²)	Australia	Land use and land cover change	SIMHYD (Chiew et al., 2008)	Daily	1970-2000	1970-2000
Wen (2009)	Murrumbidgee river (84,000 km ²)	Australia	Fourteen dams and eight large weirs	Regressive model	Monthly	1889-1920	1921-2007
Ma et al.(2010)	Junction of Chao and Bai River basin (15,800 km ²)	China	Direct withdrawal for irrigation and land use changes	GBHM (Yang et al. 2002, 1998)	Hourly	1956-1965	1984-2005
Wang et al. (2010)	Baimasi basin (13,915 km ²), Yellow River	China	River water withdrawals for irrigation, land use changes	VIC model (Liang et al., 1994)	Daily	1961-1970	1971-2000
Jiang et al. (2011)	Laohahe basin (18,112 km ²)	China	Agricultural and industrial withdrawals, dams and reservoirs	1. Multi-regression 2. VIC model	1. Monthly 2. Daily	1964-1979	1980-2008
Bao et al. (2012)	Three catchments of the Haihe River (from 1,800 to 24,000 km ²)	China	Surface water and groundwater withdrawals for farm, industry and population and land use changes	VIC model (Liang et al., 1994)	Daily	11/16 years in the 1952-1972 period	5/40 years in the 1965-2004 period
Wang et al. (2013)	Haihe River basin (189,000 km ²)	China	Surface water and groundwater withdrawals for farming, industry and population and land use changes	Two-parameter monthly hydrological model (Xiong and Guo, 1999)	Monthly	1957-1978	1978/1980-2000
Zhan et al. (2013)	Bai River (9,228 km ²)	China	Dams, farmland	SIMHYD (Chiew et al., 2008)	Daily	1986-1990	1991-1998
Ahn and Merwade (2014)	103 Stations in New York, Indiana, Arizona and Georgia	USA		Regression (Jiang et al., 2011)	Monthly	1950-1979	1981-2010
Guo et al. (2014)	Weihe River (30,661 km ²)	China	Agricultural irrigation, industrial development, dam construction	HBV model	Daily	1972/1975-19	1985-2007
Chang et al. (2015)	Jinghe River basin (45,400 km ²)	China	Withdrawals	1.TOPMODEL 2.VIC model (Liang et al., 1994)	1. Monthly 2. Daily	1960-1970	1971-2010

Authors	Catchment	Country	Influence	Model
Peters and Prowse (2011)	Lower Peace River (293 000 km ²)	Canada	Hydroelectric dam	Hydraulic: one-dimensional hydraulic flood routing model
Ahn et al. (2006)	Illinois river	United States	Seven locks and dams, 36 levees	Hydraulic (UNET)
Peters et al. (2006)	Peace-Athabasca Delta (6000 km ²)	Canada	Hydroelectric dam	Hydraulic: one-dimensional hydrodynamic model
Shiklomanov and Lammers (2009)	Large Russian Arctic rivers	Russia	Reservoirs	Hydraulic: hydrograph routing model
Wyrick et al. (2009)	Mantua Creek (19 km ²), New Jersey	United States	Two small dams	Hydraulic (HEC-RAS) + Hydrology (HEC-HMS)
Wu et al. (2015)	Taiwan (680 km ²)	Taiwan	Reservoirs and diversions	

	Data required	Water Balance	Reconstitution	Extension	Paired Catchment	Neighbourhood	Routing modelling
Based on access to	Influenced period information: _ Influenced observed streamflow	X	X				
	_ Influence volume time series	X	X				
	Uninfluenced period information: Natural observed streamflow on a pre- or postinfluence period			X	X		
	Regional information: _ Upstream natural flow				X	X	X
	_ Natural observed streamflow on neighbourhood catchment				X	X	
Tool used	Hydrological model		X	X	X	X	
	Hydraulic model	X					X
	Mass balance method (catchment area scaling , equipercetile methods, etc.)	X					

FicheEVPG2_EN

Index	Catchments	Area [km²]	Influences	Naturalization method				Models	Reference
				WB	R	E	N		
1	La Cance	From 11 to 380	Withdrawals and discharges, and farm dams	X			X	GR2M	BRL Ingénierie (2014)
2	Le Loup	283	Dam and withdrawals	X			X	Grloieau-pixel monthly model	Département des Alpes-Maritimes (2013)
3	Les Gardons	From 69 to 2034	Withdrawal for water supply, agriculture and industry, and dam	X			X	GR4J	BRL Ingénierie (2015)
4	Basse vallée de l'Ain	3630	Five dams and, surface and groundwater withdrawals		X			Modflow	SOGREAH Consultants et EPTEAU (2012)
5	Drôme des collines	470	Withdrawals		X			Conceptual semi-distributed daily model	Artelia Eau et Environnement et Maison régionale de l'Eau (2012a)
6	Hérault	2622	Withdrawals		X			ATHYS and hydrogeological model with withdrawal module	CEREG Ingénierie et Berga Sud (2015)
7	La Galaure	240	Withdrawals		X			Conceptual semi-distributed daily model	Artelia Eau et Environnement et Maison régionale de l'Eau (2012b)
8	Lez provençal	From 110 to 455	Surface and groundwater withdrawals for irrigation and water supply		X			Hydrological model (ATHYS) and hydrogeological model (MODFLOW) with withdrawal module	CEREG Ingénierie et al. (2013)
9	Ouche	916	Surface and groundwater withdrawals		X			Semi-distributed model	SOGREAH et al. (2011)
10	Tille	1300	Surface and groundwater withdrawals		X			NAM (MIKE11)	SAFEGE Ingénieurs Conseils (2011)
11	L'Asse	692	Withdrawals		X		X	ATHYS with withdrawal module	CEREG Ingénierie (2011)
12	La Berre drômoise	138	Withdrawals	X					Société du Canal de Provence et ASCONIT Consultants (2012)
13	L'Agly	From 157 to 1100	Surface and groundwater withdrawals, and dam	X					GINGER Environnement & Infrastructures (2012a)
14	Le Sègre		Withdrawals for irrigation, water supply, industry and artificial snow, and hydroelectric dam	X					SOGREAH (2012)
15	Le Vidourle	800	Surface and groundwater withdrawals, and dams	X					GINGER Environnement & Infrastructures (2012b)
16	Les Usses	310	Withdrawals	X					Risques et Développement et Maison régionale de l'Eau (2012)
17	Savoireuse	235	Withdrawals and farm dams	X					Cabinet Reilé (2012)
18	Le Garon	208	Groundwater withdrawals, farm reservoirs, inter-basin transferts, dam, irrigation	X		X		GR2M	BRL Ingénierie (2013)
19	Yzeron	150	130 farm dams, inter-basin transfert, irrigation	X		X		GR2M	BRL Ingénierie (2012)
20	Le Doux	630	Withdrawals and discharges, dams and farm reservoirs	X		X		GR4J	ISL (2011)
21	La Cèze	1359	Withdrawal for water supply, agriculture and industry, and dam	X		X		GR2M	BRL Ingénierie (2011)