



HAL
open science

INTEGRATED EX-ANTE EMERGY EVALUATION OF PRODUCING BIOELECTRICITY FROM ENERGY CANE IN A SMALL ISLAND (GUADELOUPE)

Shimrith, Stan Selbonne, Killian Chary, Aurélie Wilfart, Loïc Ginde, Jorge Sierra, Jean-Marc Blazy

► **To cite this version:**

Shimrith, Stan Selbonne, Killian Chary, Aurélie Wilfart, Loïc Ginde, Jorge Sierra, et al.. INTEGRATED EX-ANTE EMERGY EVALUATION OF PRODUCING BIOELECTRICITY FROM ENERGY CANE IN A SMALL ISLAND (GUADELOUPE). Biennial Emergy Conference, University of Florida, Feb 2016, Gainesville, United States. hal-04146948

HAL Id: hal-04146948

<https://hal.inrae.fr/hal-04146948>

Submitted on 30 Jun 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.


INTEGRATED EX-ANTE ENERGY EVALUATION OF PRODUCING BIOELECTRICITY FROM ENERGY CANE IN A SMALL ISLAND (GUADELOUPE)



STAN SELBONNE, KILLIAN CHARY, AURÉLIE WILFART, LOÏC GINDE,


JORGE SIERRA, JEAN-MARC BLAZY

Studied area



Context

Energy mix in Guadeloupe (2014)



■ Fossil fuel

■ Photovoltaics

■ Wind power

■ Geothermal energy

■ Bagasse

■ Hydropower

- 50% of renewable energy over 2020 horizon
- Intermittent energy sources: 30% maximum
- REBECCA project: electricity from energy-cane

□ Energy-cane

Selection of *Saccharum sp.* for:

- High fiber content
- High yield and growth rate
- Rusticity




Photo 1: Variety WI 79 460 at 11.5 months

Table 1: Comparison of energy-cane productivity with four others common biomasses

Original form (% moisture)	LCV (MW.h/t)	Yield (t/ha/y)	Yield (MW.h/ha/y)
Energy cane (65%)	1.20	110	132
Miscanthus (20%)	3.80	17	64.5
Bagasse (50%)	2.08	28	58.2
Switch grass (15%)	3.86	20	77.2
Hardwood (50%)	2.50	10	25.0

□ The Combined Heat and Power plant (CHP)



- **Electrical yield: 27%**
- **No steam outlet**
- **Air-cooled condenser**

□ The biomass production



Conventional energy-cane

- 6 years cycles
- No irrigation
- Herbicides
- Mineral fertilizers
- Mechanical harvesting
- Subsidies



Imported pellet


- Data from literature
- Plant located in Georgia (US)
- Woodchips from natural forest logging
- 9000 t/yr pellet plant



SMART energy-cane

- 6 years cycles
- No irrigation
- Mineral fertilizers
- Mechanical harvesting
- Mechanical weed management
- All the biomass harvested
- Compost amendment
- Additional subsidies


□ The agro-industrial sector



□ The four scenarios

SENARIOS	S0	S1	S2	S3
	Baseline	("SMART")	(Pellet)	(Micro-"SMART")
Plant's capacity (MWth)	40	40	40	4
Energy-cane in energy mix	70%	70%	25%	100%
Pellet in energy mix	25%	25%	70%	0%
Bagasse in energy mix	5%	5%	5%	0%
Plant localisation	Lamentin	Lamentin	Capesterre	Capesterre
Crop management system	Conventional	SMART	Conventional	SMART

Energy cane crop adoption by farmers (MOSAICA, Chopin et al., 2015)



□ Emergy indicators


Indicators	Expression	Meaning
Unit emergy value (UEV)	Y / E	<ul style="list-style-type: none"> ▪ The ratio of the emergy of the output (Y) to the energy of the products (E)
Renewability (%R)	$100 * (R + M_R + S_R) / Y$	<ul style="list-style-type: none"> ▪ The ratio of local renewable emergy (R) plus purchase renewable materials (RM) and services (RM) input, to the total emergy output (Y)
Renewable efficiency indicator (REI)	$UEV / (\%R)$	<ul style="list-style-type: none"> ▪ The ratio of efficiency to the percentage of renewability
Environmental loading ratio (ELR)	$(N + M_N + S_N) / (R + M_R + S_R)$	<ul style="list-style-type: none"> ▪ The ratio of non-renewable emergy to renewable inputs
Emergy yield ratio (EYR)	$Y / (M_N + S_N)$	<ul style="list-style-type: none"> ▪ The ratio of total emergy used to the emergy of non-renewable inputs from the economy
Emergy sustainability index (ESI)	EYR / ELR	<ul style="list-style-type: none"> ▪ Indicates the relative sustainability of the system

□ Indicators obtained for the four scenarios

Indicators	S0 (Baseline)	S1 ("SMART ")	(Δ)	S2 (Pellet)	(Δ)	S3 (Micro-"SMART")	(Δ)
UEV (seJ/J)	3.11E+05	3.05E+05	-2%	3.88E+05	+25%	2.94E+05	-5%
%R	30.21	38.07	+26%	30.94	+2%	36.91	+22%
ELR	2.31	1.63	-29%	2.23	-3%	1.45	-37%
EYR	1.12	1.12	0%	1.09	-3%	1.13	+1%
ESI	0.48	0.69	+44%	0.49	+2%	0.78	+63%
REI (seJ/J)	1.03E+04	8.01E+03	-22%	1.25E+04	+22%	7.97E+03	-23%

□ Energy signature of electricity production (baseline scenario S0)


Baseline CHP plant (S0)



□ UEVs and renewable fractions calculated for the different biomasses


Biomass	UEV (seJ/J)	%R (%)	REI (seJ/J)
Conventional Energy-cane	4.14E+04	26	1.59E+03
Conventional Energy-cane (<i>with transport for S0</i>)	5.95E+04	18	3.31E+03
Pellet	6.63E+04	47	1.41E+03
Pellet (<i>with transport for S0</i>)	1.65E+05	15	1.10E+04
“SMART” energy-cane	3.98E+04	54	7.37E+02
“SMART” energy-cane (<i>with transport for S1</i>)	4.53E+04	48	9.44E+02

□ Emergy signature of conventional energy-cane (without transport)



□ Conclusion

- Overall, even without steam market the baseline scenario presented energy indicators in range of values found in similar studies.
- Pellets presented better indicators than local energy-cane, but the weight of the transport reversed the results.
- REI should be used for the comparison of UEV and renewability between different products
- Through the three other scenarios analysed, we showed that the indicators of electricity produced was very sensible to the biomass used, except for EYR indicator.
- The use of “SMART” crop management system allowed to produce a biomass more sustainable with an UEV (with transport) of $4.53E+04$ seJ/J and a high renewability of 48%.
- The implantation of the smaller CHP plant which operated with 100% “SMART” energy-cane was more sustainable than baseline scenario, surpassing the scale economy issue.
- Nitrogen fertilizers was the most impacting input in energy-cane crops.



Thank you for your attention!

