



HAL
open science

airGRteaching: Teaching Hydrological Modelling with the GR Rainfall-Runoff Models ('Shiny' Interface Included). Manual of the R package version 0.2.9.25

Olivier Delaigue, Laurent Coron, Pierre Brigode

► To cite this version:

Olivier Delaigue, Laurent Coron, Pierre Brigode. airGRteaching: Teaching Hydrological Modelling with the GR Rainfall-Runoff Models ('Shiny' Interface Included). Manual of the R package version 0.2.9.25. 2020, 10.15454/W0SSKT . hal-04162971v8

HAL Id: hal-04162971

<https://hal.inrae.fr/hal-04162971v8>

Submitted on 27 Jul 2021 (v8), last revised 19 Aug 2024 (v15)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Package ‘airGRteaching’

October 19, 2020

Type Package

Title Teaching Hydrological Modelling with the GR Rainfall-Runoff Models ('Shiny' Interface Included)

Version 0.2.9.25

Date 2020-10-19

Depends airGR (\geq 1.4.3.52)

Imports dygraphs (\geq 1.1.1.6), markdown, plotrix, shiny (\geq 1.1.0), shinyjs (\geq 1.0), xts

Suggests knitr, rmarkdown

Description Add-on package to the 'airGR' package that simplifies its use and is aimed at being used for teaching hydrology. The package provides 1) three functions that allow to complete very simply a hydrological modelling exercise 2) plotting functions to help students to explore observed data and to interpret the results of calibration and simulation of the GR ('Génie rural') models 3) a 'Shiny' graphical interface that allows for displaying the impact of model parameters on hydrographs and models internal variables.

License GPL-2

NeedsCompilation no

URL <https://hydrogr.github.io/airGRteaching/>

Encoding UTF-8

VignetteBuilder knitr

Author Olivier Delaigue [aut, cre] (<<https://orcid.org/0000-0002-7668-8468>>),
Laurent Coron [aut] (<<https://orcid.org/0000-0002-1503-6204>>),
Pierre Brigode [aut] (<<https://orcid.org/0000-0001-8257-0741>>),
Guillaume Thirel [ctb] (<<https://orcid.org/0000-0002-1444-1830>>)

Maintainer Olivier Delaigue <airGR@inrae.fr>

Repository CRAN

Date/Publication 2020-10-19 15:40:03 UTC

R topics documented:

airGRteaching	2
as.data.frame	4
CalGR	6
dyplot	7
plot	9
PrepGR	10
ShinyGR	12
SimGR	14

Index	17
--------------	-----------

airGRteaching	<i>Tools to Simplify the Use of the airGR Hydrological Package for Education (Including a Shiny Application)</i>
---------------	--

Description

airGRteaching is an add-on package to the airGR package that simplifies its use and is teaching-oriented. It allows to use with very low programming skills the rainfall-runoff models (GR4H, GR5H, GR4J, GR5J, GR6J, GR2M, GR1A) and a snow melt and accumulation model (CemaNeige). This package also provides graphical devices to help students to explore data and modelling results.

The airGRteaching package has been designed to fulfil a major requirement: facilitating the use of the airGR functionalities by students. The names of the functions and their arguments were chosen to this end.

The package is mostly based on three families of functions:

- the functions that allow to complete very simply a hydrological modelling exercise;
- plotting functions to help students to explore observed data and to interpret the results of calibration and simulation of the GR models;
- a function which runs a 'Shiny' graphical interface that allows for displaying in real-time model parameters impacts on hydrographs.

This package brings into R the hydrological modelling tools developed at INRAE-Antony ([Catchment Hydrology research group](#) of the HYCAR Research Unit, France).

— Modelling Functions

Three functions allow to complete very simply a hydrological modelling exercise:

- preparation of data: [PrepGR\(\)](#);
- calibration of the models: [CalGR\(\)](#);
- simulation with the models: [SimGR\(\)](#)

— Plotting Functions

airGRteaching provides two types of plotting functions that allow to produce static (`plot()`) or dynamic (`dypplot()`) graphics (incl. mouse events and interactive graphics). The devices allow to explore observed data and to interpret the results of calibration and simulation of the GR models.

— Shiny interface

The package also provides the `ShinyGR()` function, which allows to run a Shiny interface. Thus its is possible to perform:

- interactive flow simulations with parameters modifications;
- automatic calibration;
- display of internal variables evolution;
- time period selection.

A demonstrator of the graphical interface is available for free online on the [Sunshine website](#).

— Models

The six hydrological models and the snow melt and accumulation model already available in airGR are available in airGRteaching.

These models can be called within airGRteaching using the following model names:

- GR4H: four-parameter hourly lumped hydrological model (Mathevet, 2005)
- GR5H: five-parameter hourly lumped hydrological model (Ficchi, 2017; Ficchi *et al.*, 2019)
- GR4J*: four-parameter daily lumped hydrological model (Perrin *et al.*, 2003)
- GR5J*: five-parameter daily lumped hydrological model (Le Moine, 2008)
- GR6J*: six-parameter daily lumped hydrological model (Pushpalatha *et al.*, 2011)
- GR2M: two-parameter monthly lumped hydrological model (Mouelhi, 2003; Mouelhi *et al.*, 2006a)
- GR1A: one-parameter annual lumped hydrological model (Mouelhi, 2003; Mouelhi *et al.*, 2006b)
- CemaNeige: two-parameter degree-day snow melt and accumulation daily model (combined with GR4H, GR5H, GR4J, GR5J or GR6J) (Valéry *et al.*, 2014)

*: available in the Shiny interface.

For more information and to get started with the package, you can refer to the vignette (`vignette("get_started")`) and go on the [airGRteaching website](#).

— References

- Coron, L., G. Thirel, O. Delaigue, C. Perrin and V. Andréassian (2017), The Suite of Lumped GR Hydrological Models in an R Package. *Environmental Modelling and Software*, 94, 166–171. doi: 10.1016/j.envsoft.2017.05.002.
- Ficchi, A. (2017). An adaptive hydrological model for multiple time-steps: Diagnostics and improvements based on fluxes consistency. PhD thesis, Irstea (Antony), GRNE (Paris), France.
- Ficchi, A., C. Perrin and V. Andréassian (2019). Hydrological modelling at multiple sub-daily time steps: model improvement via flux-matching. *Journal of Hydrology*, 575, 1308-1327. doi: 10.1016/j.jhydrol.2019.05.084.

- Le Moine, N. (2008), Le bassin versant de surface vu par le souterrain : une voie d'amélioration des performances et du réalisme des modèles pluie-débit ?, PhD thesis (in French), UPMC - Cemagref Antony, Paris, France, 324 pp.
- Mathevet, T. (2005), Quels modèles pluie-débit globaux pour le pas de temps horaire ? Développement empirique et comparaison de modèles sur un large échantillon de bassins versants, PhD thesis (in French), ENGREF - Cemagref Antony, Paris, France, 463 pp.
- Mouelhi S. (2003), Vers une chaîne cohérente de modèles pluie-débit conceptuels globaux aux pas de temps pluriannuel, annuel, mensuel et journalier, PhD thesis (in French), ENGREF - Cemagref Antony, Paris, France, 323 pp.
- Mouelhi, S., C. Michel, C. Perrin and V. Andréassian (2006a), Stepwise development of a two-parameter monthly water balance model, *Journal of Hydrology*, 318(1-4), 200-214, doi: 10.1016/j.jhydrol.2005.06.014.
- Mouelhi, S., C. Michel, C. Perrin. & V. Andreassian (2006b), Linking stream flow to rainfall at the annual time step: the Manabe bucket model revisited, *Journal of Hydrology*, 328, 283-296, doi: 10.1016/j.jhydrol.2005.12.022.
- Perrin, C., C. Michel and V. Andréassian (2003), Improvement of a parsimonious model for streamflow simulation, *Journal of Hydrology*, 279(1-4), 275-289, doi:10.1016/S0022-1694(03)00225-7.
- Pushpalatha, R., C. Perrin, N. Le Moine, T. Mathevet and V. Andréassian (2011), A downward structural sensitivity analysis of hydrological models to improve low-flow simulation, *Journal of Hydrology*, 411(1-2), 66-76, doi: 10.1016/j.jhydrol.2011.09.034.
- Valéry, A., V. Andréassian and C. Perrin (2014), "As simple as possible but not simpler": What is useful in a temperature-based snow-accounting routine? Part 2 - Sensitivity analysis of the Cemanège snow accounting routine on 380 catchments, *Journal of Hydrology*, 517(0): 1176-1187, doi: 10.1016/j.jhydrol.2014.04.058.

as.data.frame

Function to coerce the outputs of PrepGR, CalGR and SimGR to a data.frame

Description

Function to coerce the outputs of PrepGR, CalGR and SimGR to a data.frame

Usage

```
## S3 method for class 'airGRt'
as.data.frame(x, row.names = NULL, ...)
```

Arguments

x	[object of class <i>airGRt</i>] typically an object of class PrepGR , CalGR or SimGR
row.names	NULL or a character vector giving the row names for the data.frame. Missing values are not allowed
...	additional arguments to be passed to or from methods

Value

data.frame containing:

Dates	[POSIXct] vector of dates
PotEvap	[numeric] time series of potential evapotranspiration (catchment average) [mm/time step]
PrecipObs	[numeric] time series of total precipitation (catchment average) [mm/time step]
PrecipFracSolid_CemaNeige	[numeric] time series of solid precipitation fraction (layer average) [-], must be defined if CemaNeige is used
TempMeanSim_CemaNeige	[numeric] time series of mean air temperature (layer average) [°C], must be defined if CemaNeige is used
Qobs	[numeric] time series of observed flow (for the same time steps than simulated) [mm/time step]
Qsim	[numeric] time series of simulated flow (for the same time steps than simulated) [mm/time step] (only for objects of class CalGR or SimGR)

Author(s)

Olivier Delaigue

See Also

[PrepGR](#), [CalGR](#), [SimGR](#)

Examples

```
library(airGRteaching)

## data.frame of observed data
data(L0123001, package = "airGR")
BasinObs2 <- BasinObs[, c("DatesR", "P", "E", "Qmm", "T")]

## Preparation of observed data for modelling
PREP <- PrepGR(ObsDF = BasinObs2, HydroModel = "GR4J", CemaNeige = FALSE)
head(as.data.frame(PREP))

## Calibration step
CAL <- CalGR(PrepGR = PREP, CalCrit = "KGE2",
            WupPer = NULL, CalPer = c("1990-01-01", "1991-12-31"))
head(as.data.frame(CAL))

## Simulation step using the result of the automatic calibration method to set the model parameters
SIM <- SimGR(PrepGR = PREP, CalGR = CAL, EffCrit = "KGE2",
            WupPer = NULL, SimPer = c("1992-01-01", "1992-12-31"))
head(as.data.frame(SIM))
```

CalGR	<i>Calibration algorithm that optimises the error criterion selected as objective function</i>
-------	--

Description

Calibration algorithm that optimises the error criterion selected as objective function using the INRAE-HYCAR procedure described by C. Michel

Usage

```
CalGR(PrepGR, CalCrit = c("NSE", "KGE", "KGE2", "RMSE"),
      WupPer = NULL, CalPer,
      transfo = c("", "sqrt", "log", "inv", "sort"), verbose = TRUE)
```

Arguments

PrepGR	[object of class PrepGR] see PrepGR for details
CalCrit	[character] name of the objective function (must be one of "NSE", "KGE", "KGE2" or "RMSE")
WupPer	(optional) [character] vector of 2 values to define the beginning and end of the warm-up period ["YYYY-mm-dd" or "YYYY-mm-dd HH:MM:SS"]
CalPer	[character] vector of 2 values to define the beginning and end of the calibration period ["YYYY-mm-dd" or "YYYY-mm-dd HH:MM:SS"]
transfo	(optional) [character] name of the transformation transformation applied to discharge for calculating the objective function (must be one of "", "sqrt", "log", "inv" or "sort")
verbose	(optional) [boolean] logical value indicating if the function is run in verbose mode or not

Value

list object of class CalGR containing:

OptionsCalib	[list] object of class RunOptions (see: CreateRunOptions)
Qobs	[numeric] series of observed discharges [mm/time step]
OutputsCalib	[list] object of class OutputsCalib (see: Calibration)
OutputsModel	[list] object of class OutputsModel (see: RunModel)
TypeModel	[character] name of the function of the hydrological model used
CalCrit	[character] name of the function that computes the error criterion during the calibration step
PeriodModel	[list] \$WarmUp: vector of 2 POSIXct values defining the beginning and end of the warm-up period, \$Run: vector of 2 POSIXct values defining the beginning and end of the calibration period

Author(s)

Olivier Delaigue

See Also

[CreateRunOptions](#), [CreateInputsCrit](#), [CreateCalibOptions](#), [ErrorCrit_RMSE](#), [ErrorCrit_NSE](#), [ErrorCrit_KGE](#), [ErrorCrit_KGE2](#), [Calibration_Michel](#)

Examples

```
library(airGRteaching)

## data.frame of observed data
data(L0123001, package = "airGR")
BasinObs2 <- BasinObs[, c("DatesR", "P", "E", "Qmm", "T")]

## Preparation of observed data for modelling
PREP <- PrepGR(ObsDF = BasinObs2, HydroModel = "GR4J", CemaNeige = TRUE)

## Calibration step
CAL <- CalGR(PrepGR = PREP, CalCrit = "KGE2",
             WupPer = NULL, CalPer = c("1990-01-01", "1993-12-31"))
str(CAL)
```

dyplot

*Interactive time series plotting of GR data***Description**

Interactive time series plotting of objects of classes *PrepGR*, *CalGR* or *SimGR*.

Usage

```
## Default S3 method:
dyplot(x, Qsup = NULL, Qsup.name = "Qsup",
       col.Precip = c("royalblue", "lightblue"),
       col.Q = c("black", "orangered", "grey"), col.na = "lightgrey",
       ylab = NULL, main = NULL,
       plot.na = TRUE, RangeSelector = TRUE, Roller = FALSE,
       LegendShow = c("follow", "auto", "always", "onmouseover", "never"), ...)
```

Arguments

x	[object of class <i>PrepGR</i> , <i>CalGR</i> or <i>SimGR</i>] see PrepGR , CalGR , SimGR for details
Qsup	(optional) [numeric] additional time series of flows (at the same time step than argument x) [mm/time step]
Qsup.name	(optional) [character] a label for the legend of Qsup

<code>col.Precip</code>	(optional) [character] vector of 1 (total precip.) or 2 (liquid and solid precip. with CemaNeige) color codes or names for precipitation (these can be of the form "#AABBCC" or "rgb(255,100,200)" or "yellow"), see par and rgb
<code>col.Q</code>	(optional) [character] vector of up to 3 color codes or names for observed (first value), simulated (second value, if provided) and additional (last value, if provided) flows, respectively (these can be of the form "#AABBCC" or "rgb(255,100,200)" or "yellow"), see par and rgb
<code>col.na</code>	(optional) [character] color code or name for missing values (these can be of the form "#AABBCC" or "rgb(255,100,200)" or "yellow"), see par and rgb
<code>ylab</code>	(optional) [character] a label for the y-axis (flow and precipitation)
<code>main</code>	(optional) [character] a main title for the plot
<code>plot.na</code>	[boolean] indicating if the missing values are plotted on the x-axis
<code>RangeSelector</code>	(optional) [boolean] add a range selector to the bottom of the chart that allows users to pan and zoom to various date ranges (see dyRangeSelector)
<code>Roller</code>	(optional) [numeric] number of time scale units (e.g. days, months, years) to average values over (see dyRoller)
<code>LegendShow</code>	(optional) [character] when to display the legend. Specify "always" to always show the legend. Specify "onmouseover" to only display it when a user mouses over the chart. Specify "follow" (default) to have the legend show as overlay to the chart which follows the mouse. See dyLegend
<code>...</code>	other parameters to be passed through to plotting functions

Author(s)

Olivier Delaigue

See Also[PrepGR](#), [CalGR](#), [SimGR](#)**Examples**

```
library(airGRteaching)

## data.frame of observed data
data(L0123001, package = "airGR")
BasinObs2 <- BasinObs[, c("DatesR", "P", "E", "Qmm", "T")]

## Preparation of observed data for modelling
PREP <- PrepGR(ObsDF = BasinObs2, HydroModel = "GR4J", CemaNeige = FALSE)
dyplot(PREP, main = "Observation")

## Calibration step
CAL <- CalGR(PrepGR = PREP, CalCrit = "KGE2",
            WupPer = NULL, CalPer = c("1990-01-01", "1993-12-31"))
dyplot(CAL, main = "Calibration")

## Simulation
```

```
SIM <- SimGR(PrepGR = PREP, CalGR = CAL, EffCrit = "KGE2",
            WupPer = NULL, SimPer = c("1994-01-01", "1998-12-31"))
dyplot(SIM, main = "Simulation")
```

plot

*Time series plotting GR observation objects***Description**

Time series plotting GR observation objects

Usage

```
## S3 method for class 'PrepGR'
plot(x, type = "l",
     col.Precip = "royalblue", col.Q = "black", col.na = "grey",
     xlab = NULL, ylab = NULL, main = NULL,
     plot.na = TRUE, ...)

## S3 method for class 'CalGR'
plot(x, xlab = NULL, ylab = NULL, main = NULL,
     which = c("perf", "iter", "ts"), ...)

## S3 method for class 'SimGR'
plot(x, ...)
```

Arguments

x	[object of class <i>PrepGR</i>] see PrepGR for details
type	[character] the type of plot that should be drawn (see plot for details)
col.Precip	(optional) [character] color code or name for precipitation, see par
col.Q	(optional) [character] color code or name for observed flow, see par
col.na	(optional) [character] color code or name for missing values, see par
xlab	(optional) [character] a label for the x-axis (see title)
ylab	(optional) [character] a label for the y-axis (vector of 1 or 2 values for rainfall and flow respectively; see title)
main	(optional) [character] a main title for the plot (see title)
plot.na	[boolean] boolean indicating if the missing values are plotted on the x-axis
...	other parameters to be passed through to plotting functions
which	[character] choice of the plot type ("perf" (default): plot diagnostics; "iter": parameter and calibration criterion values during the iterations of the steepest descent step of the airGR calibration algorithm; "ts": time series of observed precipitation and observed and simulated flows)

Author(s)

Olivier Delaigue

See Also[PrepGR](#)**Examples**

```
library(airGRteaching)

## data.frame of observed data
data(L0123001, package = "airGR")
BasinObs2 <- BasinObs[, c("DatesR", "P", "E", "Qmm", "T")]

## Preparation of observed data for modelling
PREP <- PrepGR(ObsDF = BasinObs2, HydroModel = "GR4J", CemaNeige = FALSE)

## Observed data plotting
plot(PREP)
```

PrepGR

*Creation of the inputs required to run the CalGR and SimGR functions***Description**

Creation of the inputs required to run the CalGR and SimGR functions

Usage

```
PrepGR(ObsDF = NULL, DatesR = NULL, Precip = NULL, PotEvap = NULL,
       Qobs = NULL, TempMean = NULL,
       ZInputs = NULL, HypsoData = NULL, NLayers = 5,
       HydroModel, CemaNeige = FALSE)
```

Arguments

ObsDF	(optional) [data.frame] data.frame of dates, total precipitation, potential evapotranspiration, observed discharges and mean air temperature (only if CemaNeige is used) (variables must be in this order; see below for the units)
DatesR	(optional) [POSIXt] vector of dates required to create the GR and CemaNeige (if used) models inputs. Time zone must be defined as "UTC"
Precip	(optional) [numeric] time series of total precipitation (catchment average) [mm/time step], required to create the GR and CemaNeige (if used) models inputs
PotEvap	(optional) [numeric] time series of potential evapotranspiration (catchment average) [mm/time step], required to create the GR model inputs
Qobs	(optional) [numeric] time series of observed discharges [mm/time step]

TempMean	(optional) [numeric] time series of mean air temperature [°C], required to create the CemaNeige model inputs
ZInputs	(optional) [numeric] real giving the mean elevation of the Precip and Temp-Mean series (before extrapolation) [m], possibly used to create the CemaNeige (if used) model inputs
HypsoData	(optional) [numeric] vector of 101 reals: min, q01 to q99 and max of catchment elevation distribution [m]; if not defined a single elevation is used for CemaNeige (if used)
NLayers	(optional) [numeric] integer giving the number of elevation layers requested [-], required to create CemaNeige (if used) model inputs
HydroModel	[character] name of the hydrological model (must be one of "GR1A", "GR2M", "GR4J", "GR5J", "GR6J", "GR4H" or "GR5H")
CemaNeige	[boolean] option indicating whether CemaNeige should be activated (only available for hourly or daily models, when HydroModel is equal to any of "GR4J", "GR5J", "GR6J", "GR4H" or "GR5H"). See details

Details

If the ObsDF argument is provided, DatesR, Precip, PotEvap, Qobs and TempMean are not necessary, and vice-versa. If one variable is provided in ObsDF and also separately, then only the data included in ObsDF are used.

If the CemaNeige argument is set to TRUE, the default version of CemaNeige is used (i.e. without the Linear Hysteresis, see the details part in [CreateRunOptions](#)).

The PrepGR function can be used even if no observed discharges are available. In this case, it is necessary to provide observed discharges time series equal to NA: this means that either the ObsDF observed discharges column or the Qobs arguments, depending on the format of data you provide, must be provided and filled with NAs.

Value

list object of class PrepGR containing the data required to evaluate the model outputs:

InputsModel	[list] object of class <i>InputsModel</i> containing the data required to evaluate the model outputs (see: CreateInputsModel outputs)
Qobs	[numeric] time series of observed discharges [mm/time step]
HydroModel	[character] name of the function of the hydrological model used

Author(s)

Olivier Delaigue

See Also

[CreateInputsModel](#)

Examples

```

library(airGRteaching)

## data.frame of observed data
data(L0123001, package = "airGR")
BasinObs2 <- BasinObs[, c("DatesR", "P", "E", "Qmm", "T")]

## Preparation of observed data for modelling when inputs set by using a data.frame
PREP <- PrepGR(ObsDF = BasinObs2, HydroModel = "GR4J", CemaNeige = FALSE)
str(PREP)

## Preparation of observed data for modelling when inputs set by using independant vectors
PREP <- PrepGR(DatesR = BasinObs2$DatesR, Precip = BasinObs2$P,
               PotEvap = BasinObs2$E, Qobs = BasinObs2$Qmm,
               HydroModel = "GR4J", CemaNeige = FALSE)

## Preparation of observed data for an ungauged catchment (i.e. no observed discharge available)
## Observed discharge set to NA in the Qobs argument
## or in the 4th column of the data.frame if the ObsDF argument is used
PREP <- PrepGR(DatesR = BasinObs2$DatesR, Precip = BasinObs2$P,
               PotEvap = BasinObs2$E, Qobs = NA,
               HydroModel = "GR4J", CemaNeige = FALSE)

```

ShinyGR

Interactive Web application to run manually the GR4J, GR5 and GR6J hydrological models with or without CemaNeige

Description

Shiny application to understand and to display in a interactive way the impact of each parameter of the GR models on the simulated flows

Usage

```

ShinyGR(ObsDF = NULL,
        DatesR = NULL, Precip = NULL, PotEvap = NULL, Qobs = NULL, TempMean = NULL,
        ZInputs = NULL, HypsoData = NULL, NLayers = 5,
        SimPer, NamesObsBV = NULL, theme = "RStudio")

```

Arguments

ObsDF	(optional) [data.frame or list of data.frame] data . frame of dates, total precipitation, potential evapotranspiration, observed discharge and mean air temperature (only if CemaNeige is used) (variables must be in this order; see below for the units)
DatesR	(optional) [POSIXt] vector of dates required to create the GR and CemaNeige models inputs. Time zone must be defined as "UTC"

Precip	(optional) [numeric] time series of total precipitation (catchment average) [mm/time step], required to create the GR and CemaNeige models inputs
PotEvap	(optional) [numeric] time series of potential evapotranspiration (catchment average) [mm/time step], required to create the GR model inputs
Qobs	(optional) [numeric] time series of observed discharge [mm/time step]
TempMean	(optional) [numeric] time series of mean air temperature [°C], required to create the CemaNeige model inputs (if used)
ZInputs	(optional) [numeric or list of numerics] real giving the mean elevation of the Precip and TempMean series (before extrapolation) [m], used to create the CemaNeige model inputs (if used)
HypsoData	(optional) [numeric or list of numerics] vector of 101 reals: min, q01 to q99 and max of catchment elevation distribution [m]; if not defined a single elevation is used for CemaNeige (if used)
NLayers	(optional) [numeric or list of numerics] integer giving the number of elevation layers requested [-], required to create CemaNeige model inputs (if used)
SimPer	[character or list of characters] vector of 2 values to define the beginning and the end of the simulation period ["YYYY-mm-dd" or "YYYY-mm-dd HH:MM:SS"], see below for details
NamesObsBV	(optional) [character] vector of values to define the data inputs name(s) (if the ObsDF list is not already named)
theme	(optional) [character] alternative stylesheet ["RStudio" (default), "Cerulean", "Cyborg", "Flatly", "Inrae", "Saclay", "United" or "Yeti"]

Details

The warm-up period always starts from the first date of the dataset to the time step just before the beginning of the simulation period (SimPer).

The ShinyGR function can be used even if no observed discharges are available. In this case, it is necessary to provide observed discharges time series equal to NA: this means that either the ObsDF observed discharges column or the Qobs arguments, depending on the format of data you provide, must be provided and filled with NAs.

Author(s)

Olivier Delaigue, Laurent Coron, Pierre Brigode

See Also

[CalGR](#), [SimGR](#), [plot.CalGR](#), [plot.SimGR](#)

Examples

```
library(airGRteaching)

## data.frame of observed data of a low-land basin
data(L0123001, package = "airGR")
BV_L0123001 <- BasinObs[0001:6000, c("DatesR", "P", "E", "Qmm", "T")]
```

```

BI_L0123001 <- BasinInfo

## data.frame of observed data of a mountainous basin
data(L0123002, package = "airGR")
BV_L0123002 <- BasinObs[5000:9999, c("DatesR", "P", "E", "Qmm", "T")]
BI_L0123002 <- BasinInfo

## Interactive simulation when inputs set by using a data.frame
if (interactive()) {
  ShinyGR(ObsDF = list("Low-land basin" = BV_L0123001, "Mountainous basin" = BV_L0123002),
    ZInputs = list(NULL, median(BI_L0123002$HypsoData)),
    HypsoData = list(NULL, BI_L0123002$HypsoData),
    NLayers = list(5, 5),
    SimPer = list(c("1994-01-01", "1998-12-31"), c("2004-01-01", "2006-12-31")),
    theme = "United")
}

## Interactive simulation using when inputs set by using independant vectors
if (interactive()) {
  ShinyGR(DatesR = BV_L0123002$DatesR, Precip = BV_L0123002$P,
    PotEvap = BV_L0123002$E, Qobs = BV_L0123002$Qmm,
    Temp = BV_L0123002$T,
    ZInputs = median(BI_L0123002$HypsoData),
    HypsoData = BI_L0123002$HypsoData,
    NLayers = 5,
    SimPer = c("2004-01-01", "2006-12-31"),
    NamesObsBV = "Mountainous basin",
    theme = "Saclay")
}

## Interactive simulation for an ungauged catchment (i.e. no observed discharge available)
## Observed discharge set to NA in the Qobs argument
## or in the 4th column of the data.frame if the ObsDF argument is used
if (interactive()) {
  ShinyGR(DatesR = BV_L0123001$DatesR, Precip = BV_L0123001$P,
    PotEvap = BV_L0123001$E, Qobs = NA,
    SimPer = c("1994-01-01", "1998-12-31"),
    NamesObsBV = "Low-land basin",
    theme = "Cyborg")
}

```

 SimGR

Running one of the GR hydrological models

Description

Function for running the GR hydrological models

Usage

```
SimGR(PrepGR, CalGR = NULL, Param, EffCrit = c("NSE", "KGE", "KGE2", "RMSE"),
      WupPer = NULL, SimPer,
      transfo = c("", "sqrt", "log", "inv", "sort"), verbose = TRUE)
```

Arguments

PrepGR	[object of class <i>PrepGR</i>] see PrepGR for details
CalGR	(deprecated) use the Param argument instead
Param	[object of class <i>CalGR</i> or numeric] see CalGR . The length of the vector of parameters depends on the model used, see below for details
EffCrit	[character] name of the efficiency criterion (must be one of "NSE", "KGE", "KGE2" or "RMSE")
WupPer	(optional) [character] vector of 2 values to define the beginning and end of the warm-up period ["YYYY-mm-dd" or "YYYY-mm-dd HH:MM:SS"]
SimPer	[character] vector of 2 values to define the beginning and end of the simulation period ["YYYY-mm-dd" or "YYYY-mm-dd HH:MM:SS"]
transfo	(optional) [character] name of the transformation applied to discharge for calculating the error criterion (must be one of "", "sqrt", "log", "inv" or "sort")
verbose	(optional) [boolean] logical value indicating if the function is run in verbose mode or not

Details

The user can customize the parameters with the Param argument. The user can also use the parameters resulting from a calibration. In this case, it is necessary to use the [CalGR](#) function.

Value

list object of class SimGR containing:

OptionsSimul	[list] object of class RunOptions (see: CreateRunOptions)
OptionsCrit	[list] object of class InputsCrit (see: CreateInputsCrit)
OutputsModel	[list] object of class OutputsModel (see: RunModel)
Qobs	[numeric] series of observed discharges [mm/time step]
TypeModel	[character] name of the function of the hydrological model used
CalCrit	[character] name of the function that computes the error criterion during the calibration step
EffCrit	[list] name of the function that computes the error criterion during the simulation step
PeriodModel	[list] \$WarmUp: vector of 2 POSIXct values defining the beginning and end of the warm-up period; \$Run: vector of 2 POSIXct values defining the beginning and end of the calibration period

Author(s)

Olivier Delaigue

See Also

[CreateRunOptions](#), [CreateInputsCrit](#), [RunModel](#), [ErrorCrit_RMSE](#), [ErrorCrit_NSE](#), [ErrorCrit_KGE](#), [ErrorCrit_KGE2](#)

Examples

```
library(airGRteaching)

## data.frame of observed data
data(L0123001, package = "airGR")
BasinObs2 <- BasinObs[, c("DatesR", "P", "E", "Qmm", "T")]

## Preparation of observed data for modelling
PREP <- PrepGR(ObsDF = BasinObs2, HydroModel = "GR4J", CemaNeige = FALSE)

## Calibration step
CAL <- CalGR(PrepGR = PREP, CalCrit = "KGE2",
            WupPer = NULL, CalPer = c("1990-01-01", "1993-12-31"))

## Simulation step using the result of the automatic calibration method to set the model parameters
SIM <- SimGR(PrepGR = PREP, Param = CAL, EffCrit = "KGE2",
            WupPer = NULL, SimPer = c("1994-01-01", "1998-12-31"))

## Simulation step using model parameters set by the user
SIM <- SimGR(PrepGR = PREP, Param = c(270.426, 0.984, 108.853, 2.149), EffCrit = "KGE2",
            WupPer = NULL, SimPer = c("1994-01-01", "1998-12-31"))
str(SIM)
```

Index

- * **GR4J**
 - airGRteaching, [2](#)
- * **airGR**
 - airGRteaching, [2](#)
- * **calibration**
 - airGRteaching, [2](#)
- * **efficiency criterion**
 - airGRteaching, [2](#)
- * **hydrology**
 - airGRteaching, [2](#)
- * **model**
 - airGRteaching, [2](#)
- * **shiny**
 - airGRteaching, [2](#)
- * **student**
 - airGRteaching, [2](#)
- * **teaching**
 - airGRteaching, [2](#)

airGRteaching, [2](#)
as.data.frame, [4](#)

CalGR, [2](#), [4](#), [5](#), [6](#), [7](#), [8](#), [13](#), [15](#)
Calibration, [6](#)
Calibration_Michel, [7](#)
CreateCalibOptions, [7](#)
CreateInputsCrit, [7](#), [15](#), [16](#)
CreateInputsModel, [11](#)
CreateRunOptions, [6](#), [7](#), [11](#), [15](#), [16](#)

dyLegend, [8](#)
dyplot, [3](#), [7](#)
dyRangeSelector, [8](#)
dyRoller, [8](#)

ErrorCrit_KGE, [7](#), [16](#)
ErrorCrit_KGE2, [7](#), [16](#)
ErrorCrit_NSE, [7](#), [16](#)
ErrorCrit_RMSE, [7](#), [16](#)

par, [8](#), [9](#)
plot, [9](#), [9](#)
plot.CalGR, [13](#)
plot.SimGR, [13](#)
PrepGR, [2](#), [4–10](#), [10](#), [15](#)
rgb, [8](#)
RunModel, [6](#), [15](#), [16](#)
ShinyGR, [3](#), [12](#)
SimGR, [2](#), [4](#), [5](#), [7](#), [8](#), [13](#), [14](#)
title, [9](#)